# IN 1146 LED LIGHTPRO PROJECTOR



# Easy from the word Go

If you're going mobile, take the InFocus® LightPro™ IN1146 with you. This incredibly small and light projector features an ultra-long-lasting light source that beams up to 1000 lumens of brightness. At about the size of a paperback book and only two pounds, the IN1146 is easy to pack in your bag and carry on.



Better still, its lampless technology makes maintenance easy—or nonexistent—with a light-emitting diode (LED) that lasts up to 30,000 hours. So you can go from place to place, presentation to presentation, without ever giving your projector a thought.

### Why choose the IN1146?

- 30,000-hour LED light source
- Only 1.8 pounds (0.9 kg)
- O WXGA (1280 x 800) widescreen resolution
- Excellent connectivity:
  - HDMI and VGA inputs
  - PC-less presentation via USB drive or SD card
  - Optional USB wireless connectivity
- Striking image quality and contrast
- Auto keystone correction
- Built-in stereo speakers

#### Connectivity

HDMI USB Type A

VGA 3.5 mm composite video/stereo audio in

SD Card Slot 3.5 mm audio out

#### Long-lived lampless light

How long will the light source of IN1146 LED projector really last? The LED is rated for up to 30,000 hours—so if you use it 4 hours a day, 5 days a week, 50 weeks a year, it'll last about 12 years. Until then, it's maintenance-free—not even a filter to clean or replace. And LED projectors even use less power than their conventional cousins, so you can feel more "green" too.



LED projectors are known for their image stability and saturated colors. But the IN1146 features a high contrast of 10,000:1, so it's even better at vividly rendering fine detail and subtle color differences. Even ho-hum business graphics and content pop on the screen.



#### Three presentation options

The IN1146 gives you three easy ways to connect. You can present content from your PC over a HDMI or VGA cable. Or forget the cable and connect wirelessly using your laptop and our optional USB WiFi adapter. Or forget the laptop and dynamically display PowerPoint presentations, Word documents, photos, videos and more from a USB thumb drive or SD card.





#### **Ultra-simple operation**

When giving a presentation, you don't want to focus on your projector too. The IN1146 is ready when you are. It doesn't even have to warm up: it's on when you flip the switch. And auto keystone correction keeps your image square and true wherever you're projecting.



## **Specifications\***

#### IN1146

Native Resolution	WXGA (1280 × 800)
Technology	DLP® with LED light source
Brightness	1000 lumens
Contrast Ratio	10,000:1
Aspect Ratio	16:10 native, 16:9 and 4:3 compatible
Input Connections	HDMI, VGA, USB Type A (PC-less display, optional wireless),
	SD card slot (storage), 3.5 mm composite video/stereo audio in
Output Connections	3.5mm audio out
Media File Types (via USB drive or SD card)	Video: AVI, MKV, TS, DAT, VOB, MPG, MPEG, MOV, MP4, 3GP, RM, RMVB, WMV. Photo: JPEG, JPG, BMP. Document: DOC, DOCX, PPT, PPTX, XLS, XLSX, PDF. Music: MP3, WMA, OSG, WAV, AAC
Throw Distance	23.6 - 213 in (0.6 - 5.4 m)
Throw Ratio	1.4:1
Image Width	20 - 180 in (native 16:10)
Digital Zoom Ratio	1.7:1
Keystone Correction	± 40° vertical
Video Compatibility	SDTV (NTSC, NTSC 4.43, PAL / M / N, SECAM, PAL60", 480i/p, 576i/p), HD (720p, 1080i)
H~Synch Range	30.5 - 91.1 KHz
V~Synch Range	50 - 85 Hz
Product Weight	1.8 lbs (0.8 kg)
Product Dimensions - W × D × H	6.9 × 5.4 × 1.8 in (175 × 138 × 44.5 mm)
Shipping Weight	4.5 lbs (2 kg)
Shipping Dimensions - $W \times D \times H$	13 × 8.7 × 4.3 in (330 × 220 × 110 mm)
Speaker	2 W × 2
LED Life	30,000 hours
Power Consumption	90 W (typical), < 0.5 W (standby)
Audible Noise	32 dBa typical, 34 dBa maximum
Power Supply Range	100V - 240V @ 50~60 Hz (85W)
Operating Temperature	32 – 104° F (0 - 40° C) max
Operating Altitude	0-7,500 feet @ 104° F / 7,500-10,000 feet @ 95° F
Operating Humidity	10~85% RH without condensation
Standard Accessories	VGA cable, carry bag, AC power adaptor,
	Remote control (no batteries), Documentation
Safety Certifications	FCC (US/Canada), CE (Europe), CB
OSD Languages	English, French, German, Spanish, Italian, Portuguese, Russian, Swedish, Dutch

#### **Optional Accessories**

Wireless USB module (SP-WIFIUSB-2)
Presenter RF Remote with USB Receiver
(HW-PRESENTER-2)
Security Lock (SEC-LOCK-01)
Extended warranties (PROJ-EW1YR-MC,
PROJ-EW2YR-MC)
Cables and adapters
Projection screens

#### Warranty

The IN1146 projector comes standard with a 1-year warranty and a 90-day accessories warranty. Extended product warranty programs are available.









www.infocus.com

Infocus Corporate Headquarters 13190 SW 68th Parkway

Portland, Oregon 97223-8368, USA Phone: (1) 503-207-4700 Toll Free: (1) 877-388-8385 Fax: (1) 503-207-1937

\* Product specifications, terms, and offerings are subject to change at any time without notice.

©2014 InFocus Corporation. All rights reserved. InFocus, InFocus The New Way to Collaborate, and LightPro are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. DLP is a trademark of Texas Instruments. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies. InFocus\_IN1146-Datasheet\_EN\_04APR14