speco technologies

GS Hybrid DVR with Full D1 Recording			HYBRI	D D D D D D D D D D D D D D D D D D D
	24 Channel DVR with D 32 Channel DVR with D			Wo kindige
Storage	500GB – 8TE	3		
D24GS500 D24GS1TB D24GS2TB D24GS4TB	D24GS6TB D24GS8TB D32GS500 D32GS1TB	D32GS2TB D32GS4TB D32GS6TB D32GS8TB		.46" T

Features

- EZ Setup: for quick system setup
- EZ Network: for quick set-up on a network
- EZ Search: quickly search events from thumbnails
- EZ Record: quickly setup recording resolutions and recording type
- **EZ Copy:** auto copy what you are playing onto a USB flash drive
- H.264 video compression
- · Full D1 real time recording
- Optimized for full HD surveillance
- · Expanded video display options HDMI support
- Storage expansion via eSATA and iSCSI
- D24GS: 8 analog channels + 16 IP channels
- D32GS: 16 analog channels + 16 IP channels
- ONVIF support*
- · Rack mountable (hardware included)
- 3 year warranty

Monitoring

- · Up to 5 monitors connectable simultaneously
- 16 ch display for every monitor including spot monitor
- Full HD (1920 x 1080p) resolution support
- · Various screen formats for Full HD and standard monitors
- On-Live Playback (Triplex)
- · Data archiving support
- User Access: up to 10 concurrent users
- **Record / Search**
- · Various recording modes: Continuous, Motion, Alarm,
- Pre/Post-Event, Text-In, Panic
- · Easy record scheduling
- · Various searching modes: Date/Time, Calendar, Time Bar, Event, Motion, Alarm, Text-In
- · Disk mirroring, data archiving support
- · Various actions (PTZ preset, record cameras, alarm, save image) configurable

External Device

- · External hard drives attachable via eSATA port
- iSCSI support
- · Remote keyboard support
- Various PTZ protocol support (60+)
- · Free Speco DDNS service for use with dynamic IP addresses
- MAC[®] software provides live view and playback*
- · Simultaneous live view or playback while continuing to record, network transfer
- SNS communication alert via Twitter[™]

Free Apps with support for view on most smart devices

iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Blackberry is registered to Blackberry. Speco Technologies is constantly developing and improving products We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/21/13





External Device (cont.)

- · Remote monitoring, recording, playback, change system settings and camera control via network and/or Internet
- · Real time live display
- · IR remote control included individually control up to 16 DVRs
- · Multiple analytics such as museum search and advanced motion detection
- frame rate & picture quality or globally via EZ record
- · Easy software upgrade via Network or USB flash drive
- · Configurable per channel normal and event recording
- Full system monitoring
- Free Central Management System (Speco Central) software allows viewing of multiple DVRs on a PC
- · Email notification of alarm events
- · Per channel built-in PTZ camera protocol including Pelco D
- Automatic camera detection (Plug & Play)
- · Digital zoom in live mode and playback
- Covert camera operation provides enhanced security and administrator control
- Playback while watching live on same monitor
- Up to 30 mins. pre-alarm recording Up to 15 mins. post-alarm recording
- · Hard drive status monitoring
- · Remote upgrade
- USB mouse supported (not included)
- · Multiple language on-screen menus
- · Password to secure installation with configurable user authentication levels
- Free Central Management System (Speco Central II) software allows viewing of multiple DVRs on a PC
- SNS communication alert via Twitter"
- Digital zoom in live mode and playback
- · Covert camera operation provides enhanced security and
- · Playback while watching live on same monitor
- · Up to 30 minutes pre-alarm recording
- Up to 30 minutes post-alarm recording
- Concurrent User Connections: Admin (2) / Watch (10) / Search (2)
- USB mouse supported (not included)
- · Password to secure installation with configurable user authentication levels
- MAC[®] & PC compatible software included
- Secure Guard[®] compatible

Optional Accessory



IRRPTKIT IR Repeater Kit

administrator control



speco technologies GS Hybrid DVR with Full D1 Recording

Model Name	D24GS	D32GS			
Video Inputs	8 BNC	16 BNC			
•	Primary: 1 HDMI, 1 VGA (HD), 1 BNC (SD)	Primary: 1 HDMI, 1 VGA (HD), 1 BNC (SD)			
/ideo Outputs	Secondary: 1 VGA (SD), 1 BNC (SD)	Secondary: 1 VGA (SD), 1 BNC (SD)			
	Spot: 1 BNC (8CH)	Spot: 1 BNC (16CH)			
Looping Outputs	8 BNC	16 BNC			
Display Resolution		180 . SD: 720 x 480			
	RECORD & PLAYBACK				
Compression		1.264			
Recording Rate	240 fps @ CIF / 240 fps @ 2CIF / 240 fps @ D1	480 fps @ CIF / 480 fps @ 2CIF / 480 fps @ D1			
Playback Rate	240 fps @ CIF	480 fps @ CIF			
Recording Mode	Time-Lapse, Event, Pre-Event (up to 30 min), Text-In, Panic				
Search Mode	Date/Time, Record Table, Calendar, Event, Motion, Museum, Text-In				
	SYSTEM				
Operating System		ddad Linux			
Storage	Embedded Linux Max. 4 HDD + eSATA				
Data Export					
Data Backup	USB (HDD, Flash Drive), SATA DVD_RW Archiving, Mirroring				
	NETWORK	ıg, ivin onng			
Connection		shit Ethornot			
Protocols	2 x Gigabit Ethernet				
Protocols Remote Software	Manual, ADSL, DHCP, DVRNS				
	Speco Central, Speco Remote (Internal, External)				
Max. Transmission Rate		ips @ CIF			
Audia la / Out					
Audio In / Out	RCA 8 / 1 + 1 HDMI	RCA 16 / 1 + 1 HDMI			
Alarm In / Out	16 / 4				
Serial Interface	RS232, RS485				
External Interface	2 x USB 2.0, eSATA				
User Interface		Control, Remote Keyboard (Jog/Shuttle)			
	OTHER				
Dimensions (W x H x D)	16.9" (W) x 3.46" (H) x 19.3" (D)				
Operating Temperature	41° F – 104° F				
Operating Humidity	0% – 90%				
Power	AC100 - 240 V- 50/60 Hz, 2.0 - 1.0A				
Approvals		CB, KCC, KC, PSE			
	HYBRID				
Max. Channels	16CH x 2MP				
Supporting Products	ONVIF, OnSIP				
Megapixel Camera Support	Up to 2MP (max 16ch x 2M	Up to 2MP (max 16ch x 2MP under 70ips@2MP capacity)			
	CIF: 480ips (NTSC or progressive)				
	2CIF: 240ips (NTSC or progressive)				
Display Rate	4CIF: 120ips (NTSC or progressive)				
	1MP: 48ips (progressive) (1HD = 2.5 x 4CIF)				
	2MP: 24ips (progressive) (1HD = 5 x 4CIF)				
	CIF: 480ips (NTSC or progressive)				
	2CIF: 240ips (NTSC or progressive)				
Playback Rate	4CIF: 120ips (NTSC or progressive)				
	1MP: 48ips (progressive) (1HD = 2.5 x 4CIF)				
	2MP: 24ips (progre	ssive) (1HD = 5 x 4CIF)			
	CIF: 140ips (NTSC or progressive)				
	2CIF: 130ips (NTSC or progressive)				
Recording Rate	4CIF: 110ips (NTSC or progressive)				
	1.3MP/720p: 110ips (progressive)				
		os (progressive)			

Please note that specifications and unit exterior design are subject to change without notification.