

Christie GS Series

Boardroom
Conference rooms
Government

Higher education
Houses of worship
Location based entertainment



Long-life laser phosphor projectors with a low-cost of ownership

Free yourself from regular maintenance with the Christie® GS Series of lampless projectors. These laser phosphor, 1-chip DLP® projectors eliminate the need for lamp and filter replacements and provide an astonishing 20,000 hours of low-cost operation. Avoid the down-time, cost of lamps and the maintenance associated with lamp-based projectors by choosing the Christie GS Series for your next project.

Available in three resolutions (WXGA, HD, WUXGA), the Christie GS Series delivers accurate color reproduction, image quality and high-brightness. Wireless connectivity, a small footprint, low-weight, quiet operation and a full suite of lenses satisfies virtually all customer needs, from boardrooms and classrooms to location based entertainment.

CHRISTIE®

		Christie DWX555-GS	Christie DHD555-GS	Christie DWU555-GS
Image	brightness	• 5400 ANSI lumens (typical)	• 5000 ANSI lumens (typical)	• 5400 ANSI lumens (typical)
	contrast	• 1200:1		
Display technology	type	• 1-chip 0.65" DMD	• 1-chip 0.65" DMD	• 1-chip 0.67" DMD
	native resolution	• 1280 x 800 (1,024,000 pixels) (16:10)	• 1920 x 1080 (2,073,600 pixels) (16:9)	• 1920 x 1200 (2,304,000 pixels) (16:10)
Illumination	type	• Solid state (laser phosphor)		
	estimated life	• 20,000 hrs		
Inputs	standard	• HDMI x 1 • DVI-D x 1 (digital only) • DisplayPort x 1 • HD-15 x 1 • Composite video x 1 (RCA) • S-Video x 1 (mini DIN) • USB x 1 (type B mini) – display over USB • Component x 1 (Y/Pb/Pr) • USB x 1 (type A) – image viewer or WiFi dongle (optional) • HDBaseT x 1 • RJ-45 x 1		
	signals	• HDTV formats VGA through to WUXGA (1920 x 1200) • Horizontal and vertical scaling while maintaining aspect ratio (all inputs)		
	pixel clock	• 162 MHz		
	scan rates	• Horizontal: 15-100kHz • Vertical: 24-85Hz		
Signal outputs	monitor out	• HD-15 x 1		
Control and networking		• RS-232 in • Ethernet (10/100) RJ-45 with ChristieNET connectivity • Built-in backlit keypad • Wired remote control (3.5mm stereo) • Compatible with Crestron Connected, AMX Discovery		
Lens mount	type	• Tool-free lens insertion system • Boresight adjustable • Motorized horizontal and vertical lens offset • Motorized zoom and focus adjustment		
Lenses	zoom	• 1.0-1.28:1 (WX) • 1.28-1.60:1 (WX) • 1.60-3.07:1 (WX) • 3.04-5.78:1 (WX)	• 0.95-1.22:1 (HD/WU) • 1.22-1.53:1 (HD/WU) • 1.52-2.92:1 (HD/WU) • 2.9-5.50:1 (HD/WU)	
	offsets	• ±100% Vertical (±400 pixels) • ±30% Horizontal (±192 pixels)	• ±120% Vertical (±648 pixels) • ±30% Horizontal (±288 pixels)	• ±100% Vertical (±600 pixels) • ±30% Horizontal (±288 pixels)
Accessories	standard	• IR Remote with wired remote jack (wire not included) • AC line cord for projector head • User manual		
	optional	• 1DWUSB-BGN (wireless dongle for video and control) (133-113106-01) • Warp module (133-111104-01) • Cable cover (140-106108-01) • Ceiling mount (108-506102-XX)		
Power requirements	operating voltage	• 100-240 VAC @ 50/60Hz		
	power consumption	• 520W max • 340W Eco Mode		
	operating current	• 6.0A max		
	dissipation	• 1774 BTU/hr max • 1160 BTU/hr eco mode		
Audible noise	• Standard mode: 38dB(A) • Eco mode: 34dB(A)			
Physical	size	• (LxWxH): 19.88 x 18.31 x 7.48" (505 x 465 x 190mm) w/o feet		
	shipping size	• (LxWxH): 31.89 x 23.43 x 13.43" (810 x 595 x 341mm)		
	weight	• 35.0lbs (15.9kg)		
	shipping weight	• 47.8lbs (21.7kg)		
Environment	• Operating temperature: 5-40°C (40-104°F) • Humidity (non-condensing): 0-90%			
Regulatory	• This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • UL/CSA/IEC 60950-1 • FCC Class A • CE • CCC • KC • EAC • PSE • CU • BIS • RCM and South Africa			
Warranty	• Three years parts and labor (including light engine) • Contact an authorized Christie representative for full details of our limited warranty			

Corporate offices

Christie Digital Systems USA, Inc.
USA – Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Canada – Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6278 7708

Eastern Europe and
Russian Federation
ph: +36 (0) 1 47 48 100

France
ph: +33 (0) 1 41 21 44 04

Germany
ph: +49 2161 664540

India
ph: +91 (080) 6708 9999

Japan (Tokyo)
ph: 81 3 3599 7481

Korea (Seoul)
ph: +82 2 702 1601

Republic of South Africa
ph: +27 (0)11 510 0094

Singapore
ph: +65 6877 8737

Spain
ph: +34 91 633 9990

United Arab Emirates
ph: +971 4 3206688

United Kingdom
ph: +44 (0) 118 977 8000

**Independent sales
consultant offices**

Italy
ph: +39 (0) 2 9902 1161



For the most current specification information, please visit www.christiedigital.com

Copyright 2014 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 3893 Aug 14

CHRISTIE®