



Cooler  
By  
Design™

**Blizzard Lighting, LLC**

Phone: 1.866.493.6025

Fax: 1.866.870.0031

Email: info@blizzardlighting.com

Website: <http://www.blizzardlighting.com>

## ProPar Seven-6™

Blizzard Lighting's ProPar Seven-6™ LED PAR fixture is the new choice for richly saturated, high output light in any production environment. Offering 7\* 15-watt 6-in-1 color LEDs with full RGBAW+UV mixing and dimming capabilities in a rugged cast aluminum chassis, the ProPar Seven-6™ provides exceptional quality, coverage and ease of use at a lower price than other fixtures in its class.

Plus, with the ability to run built-in programs and perform full RGBAW+UV color mixing with or without DMX control, the ProPar Seven-6™ is perfect for architectural work and installs as well.

Two mounting yokes add positioning flexibility, and a slew of built-in programs in DMX allow the ProPar Seven-6™ to be programmed with ease. An advanced 4-button control panel puts all of the ProPar Seven-6's™ features instantly at your fingertips.

Lux/m	Red	Green	Blue	Amber	White	UV	All
1m	1,000	1,361	1,259	671	2,070	327	4,580
2m	305	355	356	188	590	95	1,240

### Main Features

- User selectable 3/6/8 or 11 DMX channels
- Full color mixing in standalone, master/slave and DMX modes
- Built-in automated programs via master/slave
- Built-in sound activated programs via master/slave
- Easy to use LED digital control panel
- 3-pin male input and 3-pin female output
- Dual mounting yoke allows flexibility in positioning
- Aluminum die-casting housing

### Weight & Dimensions

- Width: 8.3 inches (21.1 cm)
- Depth: 5.4 inches (13.7 cm)
- Height: 7.6 inches (19.3 cm), 9.25 inches (23.5 cm) including bracket
- Weight: 4.4 lbs (2 kg)

PROPAR *Seven-6*™



### Power

- Operating Voltage: 100-240VAC, 50-60 Hertz
- Power Consumption: 67W

### Light Source

- LED: 7x15w 6-in-1 LEDs

### Optical

- Beam Angle: 25 degrees

### Thermal

- Max. Operating Temp.: 104 degrees F (40 degrees C) ambient

### Control

- Protocol: USITT DMX-512
- DMX Channels: 3/6/8/11
- Input: 3-pin XLR Male
- Output: 3-pin XLR Female

### Operating Modes

- Standalone, Master/Slave, Color Preset, Standalone color mixing

### Warranty

- 2-year limited warranty, does not cover malfunction caused by damage to LED's.