TUBE OVERDRIVE TO100

Authentic Tube-Sound Overdrive Effects Pedal

Thank you for showing your confidence in us by purchasing the BEHRINGER TUBE OVERDRIVE TO100. This high-quality effects pedal is ideally suited for giving electric guitars maximum flexibility with state-of-the-art overdrive sounds that capture every nuance of your playing—from smooth overdrive to screaming tube sounds. Thanks to its high-performance features you get tube-like distortion, smooth sustain and super fat tone.

1. Controls



- 1 The **DRIVE** control adjusts the intensity of the overdrive effect.
- The **LEVEL** control adjusts the output level.
- 3 The **TONE** control allows you to shape your overall sound.
- The ON/BATT LED illuminates when the effect is activated. It also serves as a battery level indicator.
- Use the footswitch to activate/deactivate the effect.
- 6 Use this ¼" TS **IN** connector to plug in the instrument cable.
- The ¼" TS **OUT** connector sends the signal to your amp.

Use the **DC IN** connection to plug in a 9 V power supply (not included).

The **BATTERY COMPARTMENT** is located underneath the pedal cover. To install or replace the 9 V battery (not included), press the hinges with a ballpoint pen and remove the pedal cover. Be careful not to scratch the unit.

The T0100 has no on/off switch. As soon as you insert the jack into the in connector, the T0100 begins running. When not using the T0100, remove the jack from the in connector. This extends the life of the battery.

The **SERIAL NUMBER** is located at the bottom.



2. Safety Instructions

Do not use near water, or install near heat sources. Use only authorized attachments/accessories. Do not service product yourself. Contact our qualified servicing personnel for servicing or repairs, especially when power supply cord or plug is damaged.

3. Warranty

Please register your new BEHRINGER equipment right after your purchase by visiting http://behringer.com and read the terms and conditions of our warranty carefully.

4. Specifications

In	
Connector	1⁄4" TS
Impedance	500 kΩ
Out	
Connector	1⁄4" TS
Impedance	1 kΩ
Power Supply	
(11,11,11)	9 V ··· , 100 mA regulated
BEHRINGER PSU-SB	
PSU-SB-CN	220 VAC adaptor China
BEHRINGER	·
PSU-SB-EU	230 VAC adaptor Europe
BEHRINGER	
PSU-SB-JP	100 VAC adaptor Japan
BEHRINGER	
PSU-SB-SAA	240 VAC adaptor Australia
BEHRINGER	
PSU-SB-UK	240 VAC adaptor UK
BEHRINGER	
PSU-SB-UL	120 VAC adaptor USA
BEHRINGER	

Power connector	2 mm DC jack, negative center
Battery	9 V type 6LR61
Power consumption	30 mA

Physical/Weight	
Dimensions	approx. 2 1/8 x 2 3/4 x 4 4/5"
(H x W x D)	approx. 54 x 70 x 123 mm
Weight	approx. 0.73 lbs / 0.33 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may therefore differ from those listed or shown.

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUARANTEED. BEHRINGER IS PART OF THE MUSIC GROUP (MUSIC-GROUP.COM.). ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HERRIC. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS ARE NOT AGENTS OF MUSIC GROUP PAND HAVE ABSOLUTELY NO AUTHORITY TO BIND MUSIC GROUP BY ANY EXPRESS OR IMPLIED UNDERTRAING OR REPRESENTATION. THIS MANUAL IS COPYRIGHTED. NO PART OF THIS MANUAL MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING AND RECORDING OF ANY KIND, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTED IN AUTHORISE CROUP IP LTD. ALL RIGHTS RESERVED. © 2012 MUSIC Group IP Ltd. Trident Chambers, Wickhams Cay, P.O. Box 146, Road Town, Tortola, British Wirgin Islands

