# SAMSUNG



# DM-D 65"/75" COMMERCIAL LED LCD DISPLAYS

**ENSURE MAXIMUM UPTIME** 



## PUT A CLEAR AND COMPELLLING MESSAGE FORWARD WITH 24/7 CONTINUOUS OPERATION

Samsung makes it easy to create a strong impression. The DM65D and DM75D commercial displays offer reliable 24/7 uptime and contain many features and benefits to effectively communicate in the busiest environments. With enhanced SoC (system-on-chip) performance and internal media player functionality, users can display content without the need of an external PC and can control messaging through either a RS232 or LAN connection. Samsung MagicInfo software simplifies content creation and programming. Each unit comes with a built-in quad-core processor to manage graphics-heavy content. Samsung's high-resolution HD graphics ensures messages are sharp and clear. The New Business Experience

#### CONTACT US:

1-800-SAMSUNG | 1-866-SAM4BIZ samsung.com/business samsung.com/prodisplay

#### FOLLOW US:



youtube.com/samsungbizusa



@SamsungBizUSA

#### **KEY FEATURES**



#### Reliable 24/7 Operation

Innovative Samsung cooling technologies enable your messages to be displayed with highly reliable 24/7 continuous operation and come with a 3-year onsite commercial warranty.



#### Built-In Wi-Fi

In addition to HDMI, USB and D-Sub (analog) connectivity, the built-in Wi-Fi lets you easily share or mirror content from a tablet or other



#### Enhanced System-on-Chip Performance with Quad-Core CPU

Powered by a System-on-Chip semiconductor and quad-core CPU, Samsung's Smart Signage Platform reduces TCO for digital signage deployments, providing savings in hardware, installation and operating costs.



#### Super-Slim 2.3" Chassis

The stylishly thin chassis helps simplify installation while meeting ADA compliance requirements.



#### **Easy Content Control**

The Samsung SMART Signage platform eliminates the need for an external media player. With Samsung MagicInfo™ content management software, selecting and scheduling software is simple to control with either a RS232 or LAN connection.



#### Slim-Direct LED Backlight

The slim-direct-lit displays of the DM-D Series feature 1920 x 1080 Full HD resolution with 450 nits brightness and up to 5000:1 contrast ratio for sharp, detail-rich images and crisp, easily legible type.



#### **Optional Touch Overlay**

Add an optional IR touch overlay accessory to enable up to 10 simultaneous touch points.



#### New Industrial Design

A sleek, stylish new look features our new hidden logo tag, for a clean, sophisticated installation.



# Samsung DM-D 65"/75" **Commercial LED LCD Displays**





Display	Model Number		DM65D	DM75D
	Screen Size		65"	75"
	Panel Technology		60Hz Slim D-LED BLU	60Hz Slim D-LED BLU
	Resolution		1920 x 1080 (16:9))	1920 x 1080 (16:9)
	Brightness		450 nits	450 nits
	Contrast Ratio		4000:1	5000:1
	Viewing Angle (Horizontal/Vertical)		178°/178°	178°/178°
	Orientation		Landscape / Portrait	Landscape / Portrait
	Response Time (G-to-G)		6.5ms	8ms
Connectivity  Power  Environmental Conditions	Input	RGB	VGA (D-sub 15 pin), DVI-D, Display Port 1.2	VGA (D-sub 15 pin), DVI-D, Display Port 1.2
		Video	HDMI, Component/Composite	HDMI1, Component/Composite
		Audio	Stereo Mini Jack	Stereo Mini Jack
	Output	RGB	Display Port 1.2 (Loop-out)	Display Port 1.2 (Loop-out)
		Audio	Stereo mini Jack	Stereo mini Jack
	External Control		RS232C (In/Out) thru stereo jack, RJ45	RS232C (In/Out) thru stereo jack, RJ45
	External Sensor		IR, Ambient Light	IR, Ambient Light
			AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
	Power Consumption (Typical/Max)		105W / 264W	147W / 308W
	Power Consumption (Standby)		< 0.5W	< 0.5W
	Operating Temperature		0°C~40°C	0°C~40°C
	Humidity		10~80%	10~80%
Features	Special	Hardware	Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot	Silm & Light LFD with Built-in MagicInfo Player S2  Super Clear Coating, Temperature Sensor, Video Wall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot
		Software	Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain(HDCP Support), Built In MagicInfo Player S2, Firmware Update by Network, LFD New Home Screen, PC-less VideoWall, Predefined Template for Vertical Usage, Multi Channel, Mobile Control, Event Schedule, Backup Player, PC-less Touch, MagicPresenter	Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC,Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain(HDCP Support), Built In Magicinfo Player S2, Firmware Update by Network, LFD New Home Screen, PC-less VideoWall, Predefined Terr for Vertical Usage, Multi Channel, Mobile Control, Event Schedule, Backup Player, PC-less Touch, MagicPresenter
	Tuner		Yes	Yes
	SMART Signage Platform Compliant		Yes	Yes
	Internal Media Player		Cortex-A9 1GHz Quad Core, 1.5GB DDR3, 4GB FDM, USB 2.0, Linux OS	Cortex-A9 1GHz Quad Core, 1.5GB DDR3, 4GB FDM, USB 2.0, Linux OS
	VESA Standard Wall Mount Interface		400 x 400mm	400 x 400mm
	24/7 Operation		Yes	Yes
Dimensions	Product Dimensions (without stand)		57.8" x 33.4" x 2.2"	66.0" x 37.8" x 2.3"
	Packaging Dimensions		63.0" x 38.6" x 8.5"	71.3" x 42.7" x 9.8"
	Bezel Width (mm)		18.0 (Top/Side) / 23.5 (Bottom)	12.0 (Top/Side) / 17.3 (Bottom)
Weight	Product Weight		60.5 lbs.	75.4 lbs.
	Shipping Weight		89.1 lbs.	97.5 lbs.
Service	Standard Warranty		3 Years On-Site (Parts / Labor / Backlight)	3 Years On-Site (Parts / Labor / Backlight)
Accessories	Included		Quick Setup Guide, Warranty Card, D-Sub cable, Power Cord, Remote Controller, Batteries, RS232C(IN) adapter, COVER-JACK	Quick Setup Guide, Warranty Card, D-Sub cable, Power Cord, Remote Controller, Batteries, RS232C(IN) adapter, COVER-JACK
	Optional Mount		WMN-4675MD	WMN-4675MD
	Optional Stand		STN-L6500E	STN-L7585F
	Optional Media Player		PIM-BF7, PIM-BF7P	PIM-BF7, PIM-BF7P
	Optional HDBase-T		PIM-HDBT	PIM-HDBT
	Optional Touch Overlay		CY-TE65LCC	CY-TD75LDAF
Green	Emission Standard		EMC	EMC
Management	RoHS Compliant		Yes	Yes
	Packaging Recycla	hility	Packing Materials Recyclable	Packing Materials Recyclable

### CONNECTIVITY

1. RS232C In

2. RS232C Out

3. IR/Ambient Sensor In

4. Audio In


5. Audio Out 6. SD Card Slot

7. USB

8. DVI In 9. DisplayPort In 10. HDMI In

11. VGA In 12. Display Port Out 13. AV In

14 IR Out 15. RJ45 In



## **SAMSUNG**

For complete product information and accessories, visit samsung.com/business or samsung.com/prodisplay

Sales Support: 1-800-SAMSUNG or 1-866-SAM4BIZ | Follow Us: 🔠 youtube.com/samsungbizusa | 💟 @SamsungBizUSA

Samsung Electronics has been named 2013 ENERGY STAR Partner of the Year in the product manufacturing category by the U.S. Environmental Protection Agency (EPA).

