

## Torrent™ Xray

The Torrent™ Xray is our way cool moving head beam fixture that creates intensely crisp, ultra-bright light beams thanks to its 5x CREE® XLamp MC-E 10-Watt quad-color RGBW LEDs, each with a sharp 2° beam angle! Add some fog and watch either solid colored or definitively split-colored beams sweep and slice through the air with surgical precision!

The CREE® XLamp MC-E LED is a multi-chip LED that provides high lumen output, color consistency and multi-color flexibility in a small-footprint package. Compared to discrete LEDs, XLamp MC-E LEDs reduce the distance between LED die, creating a small optical source for excellent optical control and very efficient color mixing.

Controlling the Torrent™ Xray is a breeze via its easy to use 4-button LCD panel or 12/30/34 DMX channel modes. You'll have full access to individual RGBW pixel control, 12 color macros, 7 built-in programs + sound active mode, mic sensitivity, strobe, speed settings, pan/tilt invert, and 25 fixture ID settings. It's simple to use, feature packed, and a unique and powerful presence!

Even the casing is a work of art, molded with a unique rubberized exterior which resists scratching and cracking. Two sets of built in quick-release mounting points make rigging a breeze, and the included safety cable is an added bonus! The Torrent™ Xray is also equipped with 3-pin DMX input/output and industry standard powerCON® compatible power input/output connections.

### Main Features

- 5x CREE XLamp MC-E 4-IN-1 10W LEDs
- 50,000 hours lifespan and low power consumption
- 5 pixels (each LED is a pixel), individually controllable
- Narrow 2 degree beam angle
- Outstanding beam effects
- High efficiency LED shutter
- Strobe effect with 18 flashes per second and pulse effect
- 0-100% smooth linear dimmer
- Amazing beam color splitting effects
- 8 built-in default programs for easy performance
- 12 default pixel macros effects
- 12/30/34 DMX Channels
- DMX512, master-slave, sound activated, auto mode
- 4-button LCD display control panel menu
- Efficient low noise fan cooling system
- PowerCon™ compatible in/out power connectors
- 3-pin XLR connectors IN/OUT
- Two 1/4 turn fastening Omega Clamps

### Warranty

- 2-year limited warranty, does not cover malfunction caused by damage to LED's.



### **Light Source**

- 5x 10w CREE XLamp MC-E 4-in-1 LED's

### **Control**

- Protocol: USITT DMX-512
- DMX Channels: 12/30/34 channels
- Standalone, Master/Slave, Sound Active
- Input 3-pin XLR Male
- LCD 4-button control panel

### **Optical**

- Beam Angle: 2 degrees
- 420 Lux(R), 492 Lux(G), 610 Lux(B), 1070 Lux @7M

### **Movement Range**

- Pan: 540/630 degrees
- Tilt: 270 degrees

### **Power**

- Operating Voltage 100-230VAC, 50-60Hz
- Fuse 3.15A 250V
- Power Consumption 86W

### **Operating Temperature**

- Max. Operating Temp.: 104 degrees F (40 degrees C) ambient

### **Dimensions**

- Length 18.2 inches (460 mm)
- Width 14.4 inches (365 mm)
- Height 14.8 inches (375 mm)
- Weight 16.6 lbs (7.52 kg)