

IPS Direct LED

Full HD Capable Monitor

▶ 55LS35A-5B

55" class (54.64" diagonal)

▶ 47LS35A-5B

47" class (46.96" diagonal)

▶ 42LS35A-5B

42" class (41.92" diagonal)



IPS In Plane Switching

Super IPS accurately display an image's quality and color at a 178° ultra wide viewing angle. There is no fall-off in color accuracy and no diversion in contrast ratio at wide angles. From bright sunlight to the most challenging lighting environments these displays are designed to reproduce and maintain the ultimate color temperature for lifelike images.

Specifications

Direct-LED Display

Native Display Resolution 1920 x 1080 (FHD)

High Brightness 450cd/m²

Contrast Ratio 1,200:1

178°/178° Ultra Wide Viewing Angle

Suitable for Portrait or Landscape Installation

RJ-45 LAN Control

RGB and HDMI Connection

RS-232C Control

Convenient External L/R Speaker-Out

SuperSign Embedded Player

Free SuperSign Lite S/W For Content Management

Free SuperSign C S/W For Remote Control

Energy Star® 6.0 compliant

Bezel Width 8.5mm (Left/Right/Top), 14mm (Bottom)

USB Playback

USB Port

Temperature Sensor

3-Year Limited Warranty Parts/Labor/Backlight



Features

- Brightness: 450cd/m²
- Direct-LED Display
- Portrait/Landscape Orientation
- Embedded Media Player
- Energy Star 6.0 Compliant




- Low Screen Temperature
- High Resistance to Blackening Defect
- Wide Viewing Angle



SLIM DESIGN

LG monitors featuring a Direct-LED Backlight, have a stylishly slim design that fit perfectly into narrow spaces while ensuring high energy efficiency.



REMOTE MANAGEMENT VIA RS232C & NETWORK

SuperSign embedded player with RJ45 interface allows easy content transfer and control via network.



COST-EFFECTIVE SOLUTION

SuperSign Lite eliminates the need for an additional media player.



ORIENTATION

Supports portrait and landscape modes.




Portrait Scene

Landscape Scene

LG is committed to improving product development, manufacturing and usage to meet the demand for products with environmentally friendlier features. Our televisions have technologies to reduce power consumption and in return increase cost savings per room.

EcoSmart

- Dynamic Power Savings Using built-in algorithms, TV will automatically reduce the power consumption based on incoming video, while maximizing picture performance.
- Static Power Savings Picture brightness level can be set at the preferred power consumption level to reduce power and increase energy savings.
- CEC Compliant Meets the Appliance Efficiency Regulations of the California Energy Commission.
- RoHS Compliant Meets directive on restriction of hazardous substances.
- Energy Star 6.0 Qualified Meets current reduction requirements of energy consumption.




IPS Direct LED

Full HD Capable Monitor

▶ 55LS35A-5B

55" class (54.64" diagonal)



47" class (46.96" diagonal)



42" class (41.92" diagonal)

Pa As Na Br Co Dy Vie Re Su	anel Technology aspect Ratio lative Resolution rightness contrast Ratio lynamic CR iewing Angle esponse Time urface Treatment	42" class (41.92" diagonal)	47" class (46.96" diagonal) IPS 16:9 1920 x 1080 (FHD) 450 cd/m² 1,200:1 500,000:1 178 x 178	55" class (54.64" diagonal)		
As Na Bri Ccc Dy Vie Re Su Or	Ispect Ratio Iative Resolution rightness Iontrast Ratio Inynamic CR Iewing Angle Iesponse Time	11ms(G to G E	16:9 1920 x 1080 (FHD) 450 cd/m ² 1,200:1 500,000:1			
Na Bri Cc Dy Vie Re Su	lative Resolution rightness ontrast Ratio dynamic CR iewing Angle	11ms(G to G E	1920 x 1080 (FHD) 450 cd/m ² 1,200:1 500,000:1			
Bri Ccc Dy Vie Re Su Or	rightness contrast Ratio dynamic CR iewing Angle desponse Time	11ms(G to G E	450 cd/m ² 1,200:1 500,000:1			
Co Dy Vie Re Su Or	ontrast Ratio dynamic CR liewing Angle esponse Time	11ms(G to G E	1,200:1 500,000:1			
Dy Vie Re Su Or	lynamic CR iewing Angle esponse Time	11ms(G to G E	500,000:1			
Vie Re Su Or	iewing Angle esponse Time	11ms(G to G E				
Re Su Or	esponse Time	11ms(G to G E	178 x 178	500,000:1		
Su		11ms(G to G E	178 x 178			
Or	urface Treatment			10ms(G to G BW), 7ms(WOT)		
		Hard coating (3H), Anti-glare treatment of the front polarizer Haze 1% (Typ)				
CONNECTIVITY Inp	rientation	Portrait & Landscape				
	nput					
	Digital	HDMI (1)				
	Analog	RGB (1)				
	Audio	RGB (3.5Ø 1)				
	External Control	RS232C (1), RJ45 (1), IR (1)				
	USB	Yes (1)				
Ou	utput					
	Audio	Speaker L/R				
	External Control	RS232C (1)				
AUDIO Ba	alance	Yes				
Au	udio Power	20W (10W x 2)				
Sp	peaker On/Off	Yes				
Cle	lear Voice II	Yes				
So	ound Mode	Standard, News, Music, Cinema, Sport, Game				
	emperature Sensor	Yes				
FEATURES ISI	SM Method	Normal, White Wash				
Ke	ey Lock	Yes				
DF	PM Select	Yes				
En		Yes (Minimum, Medium, Maximum, Screen off)				
Sn	nergy Saving			, Screen off)		

CABINET Color							
Flat Bezel Width 0.33" (L/R/U), 0.55" (B) 0.51" (L/R/U), 0.73" (B) 0.51" (L/R/U), 0.75" (B)	CABINET	MODEL	42LS35A-5B	47LS35A-5B	55LS35A-5B		
After Curvature 0.52" (L/R/U), 0.74" (B) 0.5" (L/R/U), 0.73" (B) 0.51" (L/R/U), 0.73" (B) 0.51		Color		Black			
Monitor Dimension (WxHxD) 37.7" x 22" x 2.18" 42.1" x 24.4" x 2.1" 48.8" x 28.2" x 2.2" 2.2" Weight (Monitor Only) 20.0 lbs. 26.8 lbs. 39.2 lbs. Monitor w/Opt Stand (WxHxD) 37.7" x 24.0" x 8.5" 42.1" x 26.5" x 9.7" 48.8" x 30.3" x 9.7" Weight (Monitor+Stand) 20.5 lbs. 27.55 lbs. 39.9 lbs. Monitor w/Opt Stand & Speaker (WxHxD) 37.7" x 24.0" x 8.5" 42.1" x 26.5" x 9.7" 48.8" x 30.3" x 9.7" 4		Flat Bezel Width	0.33" (L/R/U), 0.55" (B)	0.33" (L/R/U), 0.55" (B)	0.33" (L/R/U), 0.55" (B)		
Weight (Monitor Only) 20.0 lbs. 26.8 lbs. 39.2 lbs.		After Curvature	0.52" (L/R/U), 0.74" (B)	0.5" (L/R/U), 0.73" (B)	0.51" (L/R/U), 0.73" (B)		
Monitor w/Opt Stand (WxHxD) 37.7" x 24.0" x 8.5" 42.1" x 26.5" x 9.7" 48.8" x 30.3" x 9.7"			37.7" x 22" x 2.18"	42.1" x 24.4" x 2.1"	48.8" x 28.2" x 2.2"		
Weight (Monitor+Stand) 20.5 lbs. 27.55 lbs. 39.9 lbs.		Weight (Monitor Only)	20.0 lbs.	26.8 lbs.	39.2 lbs.		
Monitor w/Opt Stand			37.7" x 24.0" x 8.5"	42.1" x 26.5" x 9.7"	48.8" x 30.3" x 9.7"		
## Speaker (WxHxD) Weight (Monitor+ Stand+Speaker) 22.2 lbs. 29.3 lbs. 41.6 lbs.		3	20.5 lbs.	27.55 lbs.	39.9 lbs.		
Stand+Speaker 22.2 lbs. 29.3 lbs. 41.6 lbs.			37.7" x 24.0" x 8.5"	42.1" x 26.5" x 9.7"	48.8" x 30.3" x 9.7"		
W x H x D		J '	22.2 lbs.	29.3 lbs.	41.6 lbs.		
VESA™ Mount			41.7" x 25.9" x 5.9"	45.2" x 27.9" x 5.9"	52.3" x 31.8" x 6.8"		
ENVIRONIMENT CONDITIONS Operation Temperature Operation Humidity 10 % to 80 % Power Supply Power Type Power Consumption Off / On Operation Humidity Off / On Off / On Off / On Off / On Operation Humidity STANDARD (CERTIFICATION) MEDIA PLAYER COMPATIBILITY SOFTWARE COMPATIBILITY SOFTWARE COMPATIBILITY ACCESSORIES ACCESSORIES ACCESSORIES Optional Accessory Optional Accessory Optional Accessory Optional Accessory Operation Humidity Operation Humidity Optional Accessory		Packed Weight	26.0 lbs.	35.0 lbs.	50.2 lbs.		
Temperature		VESA™ Mount		400 x 400 mm			
Power Supply 100-240V-, 50/60Hz Power Type Built-In Power Power Type Built-In Power Power Consumption 75W (TYP) 80W (TYP) 95W (TYP			0 °C to 40 °C				
Power Type Power Type Built-In Power Power Consumption 75W (TYP) 80W (TYP) 95W (TYP) Smart Energy Saving Off / On Dower off O.5W Department of D.5W Department of D.		Operation Humidity	10 % to 80 %				
Power Consumption 75W (TYP) 80W (TYP) 95W (TYP)	POWER						
Smart Energy Saving Off / On Power off O.5W STANDARD (CERTIFICATION) MEDIA PLAYER COMPATIBILITY SOFTWARE COMPATIBILITY ACCESSORIES Optional Accessory Smart Energy Saving O.7W (DVI-D, HDMI, DP) O.7W (DVI-CB / TUV-CB / T		,,					
Off / On Power off O.5W STANDARD (CERTIFICATION) MEDIA PLAYER COMPATIBILITY SOFTWARE COMPATIBILITY SOFTWARE SuperSign Elite-c ACCESSORIES ACCESSORY Optional Accessory Off / On Power off O.5W Safety UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC FCP / Energy Star Operation Humidity Yes / Yes (Energy Star 6.0) Yes (MP500/MP700) Yes (MP500/MP700) Remote Control (includes batteries (2 ea.)), Power Cord, IR Receiver, CD(Owner's Manual, SuperSign Program / Manual), RGB Cable ST-421T (Stand) for 55" & 47" ST-421T (Stand) for 42" UPC 7 19192 19539 4 7 19192 19540 0 7 19192 19541 7		Power Consumption	75W (TYP)	80W (TYP)	95W (TYP)		
Safety Safety Safety Safety Services SuperSign-white SuperSign-white SuperSign Services		Off / On	, , , ,				
(CERTIFICATION) EMC FCC Class "A" / CE / KCC Er / Energy Star Operation Humidity MEDIA PLAYER COMPATIBILITY SOFTWARE COMPATIBILITY ACCESSORIES ACCESSORIES ACCESSORY Poptional Accessory SP-2100 (External Speaker) for 55", 47" & 42", ST-471T (Stand) for 55" & 47" ST-421T (Stand) for 42" UPC FCC Class "A" / CE / KCC FCC			2,21				
EFP / Energy Star Operation Humidity MEDIA PLAYER COMPATIBILITY SOFTWARE COMPATIBILITY ACCESSORIES ACCESSORIES ACCESSORY Optional Accessory External Media player Attachable Yes (MP500/MP700) Yes (MP500/MP700) Yes (MP500/MP700) Yes Yes Yes ACCESSORIES ACCESSORIES ACCESSORY Remote Control (includes batteries (2 ea.)), Power Cord, IR Receiver, CD(Owner's Manual, SuperSign Program / Manual), RGB Cable SP-2100 (External Speaker) for 55", 47" & 42", ST-471T (Stand) for 55" & 47" ST-421T (Stand) for 42" UPC 7 19192 19539 4 7 19192 19540 0 7 19192 19541 7		•					
Operation Humidity MEDIA PLAYER COMPATIBILITY SOFTWARE COMPATIBILITY ACCESSORIES ACCESSORIES Optional Accessory Optional Accessory Optional Accessory To 19192 19539 4 ACCESSORIES Person (MP500/MP700) Yes (MP500/			FCC Class "A" / CE / KCC				
COMPATIBILITY SOFTWARE COMPATIBILITY ACCESSORIES ACCESSORIES ACCESSORY Poptional Accessory SP-2100 (External Speaker) for 55", 47" & 42", ST-471T (Stand) for 55" & 47" ST-421T (Stand) for 42" UPC 7 19192 19539 4 7 19192 19540 0 7 19192 19541 7			Yes / Yes (Energy Star 6.0)				
COMPATIBILITY SuperSign Elite-c SuperSign Elite-c SuperSign Elite-c SuperSign Elite-c SuperSign Elite-c Remote Control (includes batteries (2 ea.)), Power Cord, IR Receiver, CD(Owner's Manual, SuperSign Program / Manual), RGB Cable Optional Accessory SP-2100 (External Speaker) for 55", 47" & 42", ST-471T (Stand) for 55" & 47" ST-421T (Stand) for 42" UPC 7 19192 19539 4 7 19192 19540 0 7 19192 19541 7			Yes (MP500/MP700)				
ACCESSORIES Accessory Remote Control (includes batteries (2 ea.)), Power Cord, IR Receiver, CD(Owner's Manual, SuperSign Program / Manual), RGB Cable Optional Accessory SP-2100 (External Speaker) for 55", 47" & 42", ST-471T (Stand) for 55" & 47" ST-421T (Stand) for 42" UPC 7 19192 19539 4 7 19192 19540 0 7 19192 19541 7		SuperSign-w lite					
Accessory Receiver, CD(Owner's Manual, SuperSign Program / Manual), RGB Cable Optional Accessory SP-2100 (External Speaker) for 55", 47" & 42", ST-471T (Stand) for 55" & 47" ST-421T (Stand) for 42" 7 19192 19539 4 7 19192 19540 0 7 19192 19541 7	COMPATIBILITY	SuperSign Elite-c					
UPC 7 19192 19539 4 7 19192 19540 0 7 19192 19541 7	ACCESSORIES	Accessory					
7 13 132 1333 4 7 13 132 13340 0 7 13 132 13341 7		Optional Accessory	SP-2100 (External Speaker) for 55", 47" & 42", ST-471T (Stand) for 55" & 47", ST-421T (Stand) for 42"				
WARRANTY 3-Year Limited Warranty Parts/Labor/Backlight	UPC		7 19192 19539 4	7 19192 19540 0	7 19192 19541 7		
	WARRANTY	3-Year Limited Warranty Parts/Labor/Backlight					

 $[\]hbox{* SuperSign software is available from http://www.lg.com/us/commercial/led-backlit-monitors}\\$













LGsolutions.com




LG Electronics U.S.A., Inc. HE B2B Division 2000 Millbrook Drive Lincolnshire, IL 60069

Customer Service: 888.865.3026 www.LGsolutions.com/support

Contact your LG Regional Sales Representative: Channel: 800.897.8871 Hospitality: 800.228.1236 E-mail: info@LGsolutions.com

SPEC_LS35Aseries_101430_PR



@ Copyright 2014 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp.

ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. In Plane Switching is a trademark of LC Display Co., LTD. Java is a trademark of Oracle, Inc. Adobe and Flash are either registered trademarks or trademarks of Adobe Systems incorporated in the United States and/or other countries. VESA is a trademark of Video Electronics Standards Association, HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

All other product and brand names are trademarks or registered trademarks of their respective companies.



