



# VENUE | S6L

The next stage in live sound



VENUE has been one of the most trusted and requested live mixing systems in the world, and now the legacy continues with VENUE | S6L, a modular system designed to take on the most demanding tours and events with ease. Offering unprecedented processing capabilities—with over 300 processing channels—S6L delivers unrelenting performance and reliability through its advanced engine design and backs it up with modern touchscreen workflows and scalability to meet any challenge. It also provides onboard plug-ins and Pro Tools® integration, with more track counts than ever before. Plus, with a comprehensive array of network and I/O offerings, you can easily configure the system to meet the demands of any gig.

## Key highlights

- Meet the most demanding live sound challenges with the industry's most powerful processing engine
- Deliver the best sound quality possible with high-performance preamps and extended sample rate support
- Experience unmatched sound processing and tactile control through fully integrated, onboard plug-ins
- Get unprecedented Pro Tools capabilities, including Virtual Soundcheck, over Ethernet AVB and Thunderbolt\*—no interface required
- Share I/O across multiple networked systems with advanced gain tracking
- Gain unmatched visual feedback and instant access to your most important functions through high-resolution touchscreens and OLED displays
- Freely configure the modular system components and I/O to meet the demands of any live production
- Interface with a range of network and I/O formats—including Ethernet AVB, Dante, MADI, Thunderbolt, and more\*
- Enjoy the familiar VENUE workflows and interface you know and love, with total show file compatibility

\* Please note that option cards are available as separate purchases and not included with core systems.

## Take deep, intelligent control of your mix

The VENUE | S6L control surface is designed for modern live sound workflows, putting extensive control at your fingertips to deliver fast access to any part of your mix. Get unmatched visual feedback and information through high-resolution OLED displays and meters that are visible in even the brightest outdoor conditions. View comprehensive metering and select and adjust plug-ins from the touchscreen. And insert and adjust plug-ins and spill VCAs and groups right from the surface, with instant insight and access to every input, aux, group, VCA, and more through the Universe screen.

## Experience the most powerful processing engine in the industry

From Broadway to broadcast, live productions are more complex than ever, requiring hundreds of channels. With the groundbreaking VENUE | E6L engine, which outperforms the competition hands down, you have two powerhouse technologies working in concert together. The real-time processing engine handles all routing, channel, and mixing functions for maximum stability and power, while the HDX-powered DSP engine manages all AAX plug-in processing, enabling you to create bigger, better sounding mixes.

## Achieve pristine sound through high-performance I/O

Scale your system with as little or as much I/O as you need with the Stage 64 rack, featuring a high-performance preamp design that delivers the best possible sound quality throughout the signal path, with incredible clarity, warmth, and presence.

## Get more creative with expanded plug-in processing

Mix with the same sound processors used in top studios. Thanks to dedicated HDX-powered DSPs handling all plug-in processing, you can deploy an unprecedented number of plug-ins to fine-tune and finesse every channel to get the exact sounds you want. S6L comes with and directly supports 64-bit AAX DSP plug-ins, giving you far more creative choices than other live mixing systems.

## Record and support the biggest shows with Pro Tools

S6L offers the most powerful and integrated live recording capabilities in the industry, providing seamless Pro Tools recording and playback, while enabling you to control your live mixing and recording rigs as one. With Virtual Soundcheck, you can use live recordings to fine-tune mixes, program snapshots, experiment with plug-ins, and more, saving valuable sound check and set-up time.

For more information, visit [www.avid.com/S6L](http://www.avid.com/S6L)

## VENUE | S6L – The next stage in live sound

Control surface	S6L-32D	S6L-24D	S6L-24
Daylight-visible touchscreens	12.1" touchscreen x 4	12.1" touchscreen x 3	12.1" touchscreen x 1
Faders	32 + 2	24 + 2	24 + 2
Knob Modules	3 x 32, each with high-resolution OLEDs and tri-color function indicator	2 x 32, each with high-resolution OLEDs and tri-color function indicator	2 x 32, each with high-resolution OLEDs and tri-color function indicator
Master Live Module	Graphic TFTs with soft buttons; Touch and Turn assignable encoder; 2 assignable faders; monitoring, layout and snapshot controls; transport controls and function buttons		
Metering	30-segment meters per channel, with pre- and post-fade metering options; Nominal indicator, Expander/Gate status and Compressor/Limiter gain reduction meters		
Analog inputs	8 XLR mic/line inputs with 48V and signal present LEDs		
Analog outputs	8 XLR outputs with mute and signal present LEDs		
Digital inputs	4 pairs of XLR stereo AES/EBU (8 channels total)		
Digital outputs	4 pairs of XLR stereo AES/EBU (8 channels total)		
Headphone outputs	2 independent ¼" TRS stereo headphone jacks		
Ancillary I/O	DVI-D video out, 5 USB 2.0 (2 rear, 2 front, 1 internal), ECx Ethernet port for wired/wireless remote control, GPIO (8 in/8 out), 2 footswitch, Linear Time Code input, MIDI I/O		
Ethernet AVB ports	2 etherCON (copper), 2 selectable as etherCON (copper) or SFP (fiber); redundant ring topology		
2-track USB	Stereo record/playback via USB flash drive (transport and playlist integrated into VENUE software)		
Power supply	Dual redundant, internal hot-swappable PSUs		
Height (front, rear)	3.6 x 15.3 inches (91 x 388 mm)		
Width	51.4 inches (1,305 mm)	38.9 inches (989 mm)	38.9 inches (989 mm)
Depth	31 inches (787 mm)		
Weight	154 lbs (70 kg)	121 lbs (55 kg)	121 lbs (55 kg)
Engine	E6L-192		E6L-144
Sample rates	48/96 kHz		
Input channels	192		144
Input processing	True Gain™ gain compensation, HPF, LPF, 4-band PEQ, Expander/Gate, Compressor/Limiter, Delay, 4 plug-in inserts, hardware insert		
Mix busses	96 + LCR		64 + LCR
Output processing	7-band PEQ, Compressor/Limiter, Delay, 4 plug-in inserts, hardware insert		
Matrix	24 x 24		16 x 16
VCAs	24		
Stereo solo busses	2, with independent control		
Graphic EQs (31-band)	32		
Plug-in support	HDX-powered, 64-bit AAX DSP plug-ins via expansion slots		
Plug-in slots	200		128
Pro Tools integration	Record/play back up to 64 audio tracks via Ethernet AVB; higher track counts with Thunderbolt Option Card*		
Ethernet AVB ports	2 per Ethernet AVB card; selectable as etherCON (copper) or SFP (fiber), with redundant ring topology; engine can be expanded with up to three Ethernet AVB cards		
Word Clock I/O	BNC, 75 Ohm coaxial		
USB ports	5 USB 2.0 ports (2 front, 2 back, 1 internal)		
Power supply	N+1 redundant, internal hot-swappable PSUs		
Dimensions (H x W x D)	8.6 x 16.9 x 19 inches (218 x 430 x 483 mm)		
Rack spaces	5U		
Weight	61 lbs (28 kg)		
I/O Rack	Stage 64		
Maximum I/O	64 input channels, 32 output channels @ 48/96 kHz		
I/O card slots	12		
Sample rates	48/96 kHz		
Ethernet AVB ports	2, selectable as etherCON (copper) or SFP (fiber), with redundant ring topology		
Maximum cable length	Copper: 100 meters (328 feet); Fiber: 500 meters (1,640.4 feet)		
MADI	Dual MADI output offers direct split of all 64 inputs		
Headphone confidence monitor	¼" TRS stereo headphone jack with volume control; display for channel selection		
Word Clock I/O	BNC, 75 Ohm coaxial		
Power supply	Dual redundant internal PSUs		
Dimensions (H x W x D)	17.5 x 17 x 12.2 inches (445 x 432 x 310 mm)		
Rack spaces	10U		
Weight	86 lbs (39 kg)		

Corporate Headquarters  
800 949 AVID (2843)

Asian Headquarters  
+ 65 6476 7666

European Headquarters  
+ 44 1753 655999

Preliminary info, subject to change without notice.