



### SnapRax basic dimensions

P/N	A OVERALL HEIGHT	B HEIGHT WITH FINE FLOOR CASTERS	C USEABLE HEIGHT	D USEABLE DEPTH
SR43	80.75 (2051)	81.75 (2076)	75.43 (1916)	20.00 (508)
SR37	70.25 (1784)	71.25 (1810)	64.90 (1649)	20.00 (508)
SR29	56.25 (1428)	57.25 (1429)	50.90 (1293)	20.00 (508)
SR21	42.25 (1073)	43.25 (1099)	36.90 (938)	20.00 (508)
SR14	30.00 (762)	31.00 (787)	24.70 (627)	20.00 (508)
SR8	19.50 (495)	20.50 (520)	14.20 (360)	20.00 (508)
SR43-26	80.75 (2051)	81.75 (2076)	75.43 (1916)	26.00 (660)
SR37-26	70.25 (1784)	71.25 (1810)	64.90 (1649)	26.00 (660)
SR29-26	56.25 (1428)	57.25 (1429)	50.90 (1293)	26.00 (660)
SR21-26	42.25 (1073)	43.25 (1099)	36.90 (938)	26.00 (660)
SR14-26	30.00 (762)	31.00 (787)	24.70 (627)	26.00 (660)
SR8-26	19.50 (495)	20.50 (520)	14.20 (360)	26.00 (660)

Notes: 1. All dimensions in inches unless otherwise noted (dim in brackets are in mill)  
 2. Heavy-duty casters not available for SnapRax