

AUDIO Output

SDI, HDMI: Linear PCM, 24bit, 48kHz, 2ch
USB: Linear PCM, 16bit, 48kHz, 2ch

Audio is mixed and re-embedded into the SDI, HDMI, and analog outputs as well as the USB output. Each of the outputs are assignable from the Main bus or Aux bus.

USB STREAMING Output

Uncompressed up to 1080/59.94p (USB3.0), up to 720/29.97p (USB2.0)

The resolution and frame rate of the video format can be changed thanks to the dedicated scaler for the USB output.
Output is assignable from PGM or AUX bus.

HDMI MULTI-VIEW Output

1080/59.94p with HDCP
Seven-way multi-viewer

HDMI Output

Up to 1080p
HDCP support
Each of the outputs are assignable from PGM, PVW, or AUX bus.



AUDIO Input

SDI, HDMI : Linear PCM, 24bit, 48kHz, 2ch
12 analog inputs or from audio embedded in the 4 SDI or 4 HDMI inputs. The XLR jacks are provided with selectable phantom power.

RGB/COMPONENT Input/Output

Up to 1080p

COMPOSITE Input

NTSC or PAL

HDMI Input

Up to 1080p
HDCP support

3G/HD/SD SDI Input/Output

Up to 1080p
3G SDI supports Level A and B.
Each of the outputs are assignable from PGM, PVW, or AUX bus.

*For details about supported formats, refer to the specifications on the back cover.