

RH/RHX Series














Renkus-Heinz, Inc. Headquarters, Foothill Ranch, California, USA

Working together, there's no problem we can't solve, no schedule we can't meet, no project we can't take to a higher level of excellence, from the White House to the Olympic SuperDome, from corner churches to major metropolitan concert halls. Much as we love technology, our greatest satisfaction comes through helping people communicate through music, dance, theater, or the power of a new idea brilliantly expressed. When we make those kinds of connections, there's nothing more exciting – or more powerful.

Here are some of the unique Renkus-Heinz technologies we use in our loudspeaker systems:





Complex Conic Topology, the first new approach to horn design in decades has proven its superior performance worldwide.



TRAP (TRue Array Principle) design aligns acoustic centers so loudspeaker clusters produce coherent output.



Reference Point Array engineering optimizes the entire signal chain from line level to listener for unprecedented performance.



RH/RHX Series RH/RHX Series ···-

RH/RHX62

- High Output, Small Enclosure •
- Flexible Input Configurations •
- Rotatable Complex Conic Horn
 - 150° x 60° Coverage •
- 70 Hz to 20 kHz Frequency Range
 - 130 dB Peak SPL Rating •
- High Power, High Performance •
- Premium 1" Extended Range Titanium HF Driver •

RHAON Ready •



Dimensions (H x W x D) inch: 21 3/4 x 10 1/2 x 10 1/2 cm: 55.3 x 26.7 x 26.7 Weight (lbs/kg) RH/RHX81: 37/16.8



RH/RHX81

- Compact Design
- Flexible Input Configurations
- Rotatable 120° x 60° Complex Conic Horn
- Choice of 90° x 60° or 120° x 60° Coverage

cm: 54.61 x 20.32 x 18.1

- 70 Hz to 20 kHz Frequency Range
- 131 dB Peak SPL Rating (on RHX81)
- Premium 1" Extended Range Titanium HF Driver
- Heavy-Duty 8" Woofer
- RHAON Ready

RH/RHX101





- Flexible Input Configurations •
- Rotatable 90° x 60° Complex Conic Horn •
- Choice of 90° x 60° or 120° x 60° Coverage •
- 70 Hz to 20 kHz Frequency Range •
- 133 dB Peak SPL Rating (on RHX101) •
- Premium 1" Extended Range Titanium HF Driver
 - Heavy-Duty 10" Woofer
 - RHAON Ready •





RH/RHX123

- Powerful 12" 3-Way CoEntrant •
- Flexible Input Configurations •
- Rotatable 90° x 60° Complex Conic Horn •
- Choice of 90° x 60° or 90° x 90° Coverage
 - 50 Hz to 20 kHz Frequency Range
 - 136 dB Peak SPL Rating •
- High Power, High Performance •
- Patented CDT-3 CoEntrant Mid/High Driver
 - RHAON Ready •



Dimensions (HxWxD) inch: 28 1/2 x 14 1/4 x 13 1/2 cm: 72.4 x 37 x 34.3

Weight (lbs/kg) RH/RHX123 68/30.9



RH/RHX153

- Powerful 15" 3-Way CoEntrant •
- Flexible Input Configurations •
- Choice of 60° x 40° , 90° x 60° or 60° x 60° Coverage
 - 40 Hz to 20 kHz Frequency Range
 - 135 dB Peak SPL Rating •
 - High Power, High Performance •
 - Patented CDT-3 CoEntrant Mid/High Driver
 - RHAON Ready •



Dimensions (H x W x D) inch: 30 1/4 x 17 1/2 x 16 cm: 76.8 x 44.5 x 40.6 Weight (lbs/kg) RH/RHX153: 79/35.9

Page 2