

# **AMP1SGRN1 – Three Source Plus One, 6.5” Amplified Drop Ceiling Speaker – One Speaker Package**

Three Source Plus One, 6.5” amplified ceiling speaker. It is UL Listed, Energy Verified, Energy Star audio product. This unit has 32 watts or power which can drive up to four speakers connected series parallel to have a net impedance of 8 ohms. With an included UL Listed, **Level 5** (Energy Star), 15 volt, 3.5 ampere power supply, the amplifier can output 32 watts, or 8 watts per speaker in a four speaker hook-up. Volume Control Available.

One Speaker combination consisting of the following:

- 1.) One (1) each AMP1SGRN -6.5" amplified speaker with (PS15VDC35AL5) UL Listed, Level 5 (Energy Star) 15 volts VDC, 3.5 A power supply
- 2.) One (1) each Backcan enclosures
- 3.) One (1) each 6TB tile bridge



## **Features:**

- Self-Powered "Green" Speaker
- UL and Energy Star Listed
- 2 x 16 or Total 32 Watts Max Power
- Three Audio Inputs
- Priority Override Feature
- Balanced Line Level Output
- Self Test Feature
- RS232 Controllable Supervision
- Infrared Wireless Microphone Auxiliary Input
- Speaker Combination Program Available

## **Available also in other complete install packages:**

- [AMP1SGRN1SVC](#) - Single speaker combination with tile bridge, backcan and volume control
- [AMP1SGRN2](#) - Two speaker combination with tile bridges, backcans
- [AMP1SGRN2SVC](#) - Two speaker combination with tile bridges, backcans and volume control
- [AMP1SGRN4](#) - Four speaker combination with tile bridges, backcans
- [AMP1SGRN4SVC](#) - Four speaker combination with tile bridges, backcans and volume control

