

## RoscoLED Tape Static White Kits

RoscoLED Tape Kits are engineered LED solutions designed to enable set designers for broadcast studios and television & feature film productions to easily incorporate attractive accent lighting into their sets. The RoscoLED Static White Kits include four reels of high-quality white LEDs that feature the latest SMD2835 emitters and pre-configured, plug-and-play connectors for easy installation – no soldering required. The kits also contain a balanced RoscoLED Control Box for power and flicker-free dimming via DMX. Flexible, field-cuttable and fully configurable, RoscoLED Tape Kits offer designers and filmmakers easy-to-use solutions for integrating LEDs into their next project.



### SPECIFICATIONS

Part No.	
293220100000	RoscoLED Tape Static White Kit - Tungsten
293220100015	Rosco LED Tape Static White Kit - Daylight

### RoscoLED Tape Static White Kits


#### What's In The Kit:

- (4) 5m reels of RoscoLED Static White LED Tape with pre-soldered, 2-pin connector on each reel
- (1) 300W Static White RoscoLED Control Box
- (4) 3m, 2-pin RoscoLED Static White Cables

### RoscoLED Static White LED Tape Components

Part No.	
293221100005	RoscoLED 5m Reel Static White LED Tape – Tungsten
293221150005	RoscoLED 5m Reel Static White LED Tape – Daylight
293222010001	RoscoLED 2-pin Static White Cable - 1M
293222010002	RoscoLED 2-pin Static White Cable - 2M
293222010003	RoscoLED 2-pin Static White - 3M
293222010005	RoscoLED 2-pin Static White - 5M
293222110000	RoscoLED 2-pin Static White Cable Splitter
293222500000	RoscoLED Static White Control Box (300W)
293222610000	RoscoLED DMX Decoder 4 x 6A
293222620000	RoscoLED Power Supply 24V x 350w

LED Type:	SMD2835
Number of LEDs/5m reel:	300
Color Temperature:	Tungsten: 3000K Daylight: 5600K
Lumens/Meter:	1000



Pin Configuration:	2-pin
Voltage:	24VDC
Power Consumption:	14.4W/m (72W/5m Reel)

#### Control Box Properties

Power Input:	100-240VAC via Neutrik Powercon connector
Power Output:	24VDC via 2-pin connector
Data Input:	DMX via 5PXL or RJ45
Data Output:	DMX via RJ45
Package Dimensions:	16.5" x 12" x 8" (42 cm x 30.5 cm x 20.3 cm)
Weight:	10.5 lb (4.8 kg)
Operational Temperature:	-4° - +140° F (-20° - +60° C)

Warranty:	3-years
Approvals:	UL Listed CE Certified RoHS Compliant

