

## RoscoLED Tape VariWhite Kit

RoscoLED Tape Kits are engineered LED solutions designed to enable set designers for broadcast studios and television & feature film productions to easily incorporate attractive, tunable white accent lighting into their sets. The RoscoLED VariWhite Kit includes three reels of high-quality, tunable color-temperature white LEDs that are pre-configured with plug-and-play connectors for easy installation – no soldering required. The kit also contains a balanced RoscoLED Control Box for power and flicker-free dimming via DMX. Flexible, field-cuttable and fully configurable, RoscoLED Tape Kits offer designers and filmmakers easy-to-use solutions for integrating LEDs into their next project.



### SPECIFICATIONS

Part No.  
293220100020 RoscoLED Tape VariWhite Kit

#### RoscoLED Tape VariWhite Kit


##### What's In The Kit:

- (3) 5m reels of RoscoLED VariWhite LED Tape with pre-soldered, 3-pin connector on each reel
- (1) 400W VariWhite RoscoLED Control Box
- (3) 3m, 3-pin RoscoLED VariWhite Cables

#### RoscoLED VariWhite LED Tape Components

Part No.	
293221200005	RoscoLED 5m Reel VariWhite LED Tape (24V/3000K-6000K)
293222020001	RoscoLED 3-pin VariWhite Cable - 1M
293222020002	RoscoLED 3-pin VariWhite Cable - 2M
293222020003	RoscoLED 3-pin VariWhite Cable - 3M
293222020005	RoscoLED 3-pin VariWhite Cable - 5M
293222120000	RoscoLED 3-pin VariWhite Cable Splitter
293222600000	RoscoLED VariWhite Control Box (400W)
293222610000	RoscoLED DMX Decoder 4 x 6A
293222620000	RoscoLED Power Supply 24V x 350w

LED Type:	SMD2835 Tunable White
Number of LEDs/5m reel:	300
Color Temperature Range:	3000K - 6000K
Lumens/Meter:	1500



Pin Configuration:	3-pin
Voltage:	24VDC
Power Consumption:	19W/m - 95W/5m

#### Control Box Properties

Power Input:	100-240VAC via Neutrik Powercon connector
Power Output:	24VDC via 3-pin connector
Data Input:	DMX via 5PXL or RJ45
Data Output:	DMX via RJ45
Package Dimensions:	16.5" x 12" x 8" (42 cm x 30.5 cm x 20.3 cm)
Weight:	10.5 lb (4.8 kg)
Operational Temperature:	-4° - +140° F (-20° - +60° C)
Warranty:	3-years

Approvals: UL Listed  
CE Certified  
RoHS Compliant

