

SmartBoom[®] PRO

Professional Communication Headsets

SBP-151T (Single) & SBP-152T (Double)

The **new Tempest SBP Headset** meets the standards of traditional, reliable headsets while introducing modern features and design enhancements.

The SBP Headset features SmartBoom technology, allowing the microphone boom to act as an On/Off switch for quick microphone muting. Additionally, the headset provides high ambient-noise reduction and produces high quality audio using a cardioid dynamic microphone. The headset has a flexible ambidextrous design and soft foam padding to offer superior comfort.



Features

- Outstanding Audio Quality w/Enhanced Acoustic Isolation
- Closed Back Circumaural Design Available in Single and Dual-Ear Models
- Flexible, Ambidextrous Swiveling Mic Boom
- SmartBoom[®] Flip Up Microphone Mute Operation
- Dynamic Noise-Cancelling Cardioid Microphone Optimized for Voice Communications


- Comfort Fit Adjustable Headband
- Comfortable and Replaceable Ear, Headband, and Temple Cushion Pads
- Non-Reflective Rubber Coated Matte Finish
- Collapsible for Efficient Space Saving Storage
- Detachable Cable (5 ft./1.52m, 4-pin Female XLR Supplied)
- Full One Year Parts and Labor Warranty



Wiring Diagram for Connector Inputs

PIN CONNECTIONS		
Headset Plug Pin	Cable	XLR Plug Pin
8	Blue – Speaker R+	4
7	Brown – Speaker L+	4
6	Red – Speaker R-	3
5	Orange – Speaker L-	3
2	Yellow – Mic+	2
1	Green – Mic-	1
3	Uncoated – Shield	1

MICROPHONE POLAR PATTERN



Specifications

SBP-151T & SBP-152T

Microphone

Microphone Type	
Frequency Response	
Mic Sensitivity	
Pattern	
Output Impedance	
Isolation from Headphone	

Speaker (Headphone)

Frequency Reponse Nominal Impedance Single (SBP-151T) Double (SBP-152T) Sensitivity a 1 kHz Single (SBP-151T) Double (SBP-152T) Speaker Type Max Input Power

Cables

Termination at Ear Termination at Jack Length Outside Diameter

Physical Features

Mic Boom Length Weight (without cable) Single (SBP-151T) Double (SBP-152T) Cable

Warranty

One Year Parts and Labor

Dynamic 50–10,000 Hz -58 dBV/Pa Cardioid uni-directional 200 Ω 40 dBv

20–20,000 Hz

100 Ω 200 Ω

117 dB SPL/mW 121 dB SPL/mW Dynamic 500 mW

Removable (Crossbolt) 4-pin XLR Female 5.00 ft. (1.52 m) 0.24 in. (6.00 mm)

8.50 in. (215.90 mm)

8.1 oz (229.63 g) 11.4 oz (323.18 g) 3.8 oz (107.73 g)



CoachComm, LLC Tempest®

205 Technology Parkway Auburn, AL 36830

www.tempestwireless.com 1.844.475.4268 or +1.334.321.1160 Confidential. Not for public release. COPYRIGHT © 2015 CoachComm, LLC. All rights reserved. CoachComm[®] and the Tempest[®] logos are registered trademarks of CoachComm, LLC. Any and all other trademark references within this document are property of their respective owners.

TempestMAPProgram_D0000192-A