



High Definition 3G-SDI BNC to BNC Cable



These broadcast quality cables supports SDI, HD-SDI and 3G-SDI and meet all requirements for 3 Gbps signal/ data serial interface transmission. Constructed with a specially formulated digital ready heavy duty 18 Awg RG6 cable that is 100% Shielded and terminated with True 75 Ohm nickel over brass BNC Connectors for proper impedance and minimal signal reflection. Comes in multiple lengths and covered under our famous Lifetime Warranty.

Features

- Supports SDI, HD-SDI and 3G-SDI
- Meets requirements for 3 Gbps signal / data serial interface
- True 75 Ohm BNC Connectors
- Specially formulated 18 Awg RG6 cable
- 100% Shielded
- Lifetime Warranty



Specifications

Performance Grade: Best	Temperature Rating: 75 deg C
Connector Type 1: BNC Male 75 Ohm	Voltage Rating: 30V
Connector Type 2: BNC Male 75 Ohm	Jacket Type: X-traflex mist black PVC
Connector Finish: Nickel	Weight Lbs: 0.2
Gauge: 18 AWG	RoHS Compliant: Yes
Center Conductor: Solid Oxygen Free Tinned copper	Warranty: Lifetime
Dielectric: Foam Polyethylene	
Shielding: <95% tinned copper braid and 100% Aluminum	
Mylar Wrap	
UL Rated: Yes	

BB-C-3GSDI-3	3ft.
BB-C-3GSDI-6	6ft.
BB-C-3GSDI-10	10ft.
BB-C-3GSDI-15	15ft.
BB-C-3GSDI-25	25ft.
BB-C-3GSDI-50	50ft.
BB-C-3GSDI-100	100ft.