

WXGA ultra-short-throw projector with built-in interactivity and a host of connectivity options

The D755WTi is Vivitek's new compact ultra-short-throw projector with built-in interactivity function which make possible to turn any standard screen or white surface into an interactive projection solution. The D755WTi delivers high brightness with 3,300 ANSI Lumens and an outstanding contrast ratio of 10,000:1 for a perfectly displayed image. The D755WTi is a stylish projector that is future proof with direct 3D via HDMI, powerful 20W built-in speaker and an assortment of connectivity options include HDMI v1.4 for perfect digital image transmission and RJ-45 for network connectivity, the D755WTi is the ultimate education projector for perfect presentations.

Features

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Built-in IWB functionality with interactive pens
- Dual pen support for simultaneous use
- Delivers a large 80" to 100" image from a ultra-short distance
- Helps prevent shadow obstruction and light glare in the presenter's eyes
- Bright 3300 ANSI lumens with a colorful 10,000:1 contrast ratio
- Energy efficient lamps that last up to 10,000 hours (in economy mode)
- DisplayPort connector for digital audio and video signals
- Network ready for integration and system administration via RJ45
- VGA-output for display on a secondary monitor
- Powerful 20W audio speaker
- Top-loading, cover for quick and easy lamp replacement
- Sealed optical engine, minimizing the impact of dust and smoke
- Keypad lock prevents accidental system adjustments

Product Pictures



Specifications	
Display Type	DLP
Brightness	3300 ANSI Lumens
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	UXGA (1600 x 1200)
Contrast Ratio	10,000 :1
Lamp Life and Type	6,000/10,000 Hours (Std./ Eco Mode) 230W
Image Size (Diagonal)	80"- 100"
Projection Lens	Manual Focus
Zoom Ratio	Fixed Lens
Aspect Ratio	16:10 Native
Throw Ratio	0.35:1
Offset	280mm-337mm +/-50mm
Keystone Correction	Vertical ± 40°
Horizontal Frequency	15, 30-91.4KHz
3D Ready	Direct 3D via HDMI
Vertical Scan Rate	43 - 87Hz
Speakers	20W
Lens Shift Range	N/A
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.4,VGA-In (x2), DisplayPort, S-Video, Composite, Audio-In RCA, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 3D-Sync Out, RS-232C, USB (interactivity and service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x H)	288 x 374 x 127mm
Weight	5Kg
Noise Level	29dB/33dB (Eco / Normal Mode)
Power Supply	AC 100-240V, 50/ 60Hz
Power Consumption	240W (Eco Mode), 290W (Normal Mode), <0.5W (Standby Mode)
Warranty	3 Years, 1 Year (or 1,000h) on the Lamp
Education Warranty	5-Year Warranty, 3-Year (or 2,000 hours)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Interactive Pen (x2), Documentation Kit
Optional Accessories	Replacement Lamp, Remote
UPC	814964 338594

