

PT-102V/PT-102N

1:2 Video Distribution Amplifier

| GROUP 1 |



The Kramer **PT102V** is a high performance 1:2 distribution amplifier for composite video signals. It accepts a single input and distributes it to two identical outputs using BNC connectors. Video bandwidth of 430MHz ensures that the **PT102V** remains transparent even in the most critical applications. It is the ideal companion to the model PT102A audio Pico TOOL. A 12V power supply is included. The **PT102V** is part of the Kramer Pico TOOLS family of products for applications requiring uncompromising quality and compact size at an affordable price.



TECHNICAL SPECIFICATIONS

INPUT:	1 video, 1Vpp/75 Ω on a BNC connectors.
OUTPUTS:	2 video, 1Vpp/75 Ω on BNC connectors.
VIDEO BANDWIDTH:	430MHz. -3dB, 415MHz. -0.1dB.
COUPLING:	AC.
DIFF. GAIN:	0.16%.
DIFF. PHASE:	0.11 Deg.
CONTROL:	Gain: -0.7 to +2.3dB, EQ.: 0 to 2.2dB, via trimmers accessible from front panel.
S/N RATIO:	-71.6dB.
K-FACTOR:	< 0.05%.
MAX. VIDEO OUTPUT:	2 Vpp.
POWER SOURCE:	12 VDC, 30 mA.
DIMENSIONS:	6cm x 6.5cm x 2.5cm (2.36" x 2.56" x 1", W, D, H.).
WEIGHT:	0.14 kg. (0.31 lbs.) approx.
ACCESSORIES:	Power supply.
OPTIONS:	Model VA-50P power supply with six 12VDC outlets.

TYPICAL APPLICATIONS

- Video duplication studios.
- CCTV and home theater use.
- Rental and staging applications.
- Any professional display system requiring an identical picture on several monitors.

1.19

