



GENERAL INFORMATION

Eos Programming Wing can be used as a facepanel remote for ETCnomad (either PC or Mac) or ETCnomad Puck.

It can also be used as a programming surface for the Eos and Ion Remote Processor Units (RPU) and the Remote Video Interfaces (RVI and RVI3). It cannot be used on any ETC hardware that has a dedicated facepanel and connected devices must be running at least Windows 7. The Eos Programming Wing is not compatible with Windows XP or earlier Microsoft operating systems. The wing provides power sensing and automatically turns on when both an active USB data connection and mains power is provided via the external 12V power supply.

FEATURES

- Same keypad layout as Gio
- Backlit keys
- Master Fader Pair
- Two DMX512/RDM ports
- MIDI In/Out
- Contact Closure Trigger
- Two Powered USB ports for connectivity
- One USB port to store and secure an ETCnomad Dongle
 - One Littlite connection
- VESA 100x100mm mountable
- Provides a Kensington Lock compatible locking point

INTERFACES

- AC Input (100 - 240 VAC at 50/60Hz) with external power supply
- Two DMX512/RDM ports
- Three USB ports
- MIDI In/Out
- Contact Closure Trigger

ORDERING INFORMATION

Eos Programming Wing


MODEL	DESCRIPTION
Eos PGW	Eos Programming Wing

Eos Programming Wing Accessories

MODEL	DESCRIPTION
Net3 RFR	Radio Focus Remote 903 MHz
Net3 RFR-RX	Net3 Radio Focus Remote, Receiver only
Net3 RFR - TX	Net3 Radio Focus Remote, Transmitter only
FADW 2X10	Fader Wing - 2x10
FADW 2x20	Fader Wing - 2x20
Eos PGW FC	Eos Programming Wing Flight Case

Ships with

- Power supply
- IEC power cord
- Dust cover
- USB cable



PHYSICAL

Eos Programming Wing Dimensions*

MODEL	HEIGHT		WIDTH		DEPTH	
	inches	mm	inches	mm	inches	mm
Eos PGW	4.04	103	19.55	497	14.24	362
Eos PGW with Flight Case	12.45	32	31.59	81	20.47	52

Eos Programming Wing Weights*

MODEL	WEIGHT		SHIPPING WEIGHT	
	lbs	kgs	lbs	kgs
Eos PGW	10	4.5	16	7.3

*Weights and dimensions typical

