



CANON ME20F-SH MULTI-PURPOSE CAMERA

Canon's new ME20F-SH Multi-Purpose Camera features a newly designed Canon 2.2MP high sensitivity CMOS sensor, along with Canon's DIGIC DV 4 image processor, enabling users to shoot crisp, clean, high definition, full-color video in extreme low light conditions. The camera's versatile, rugged, modular design, combined with a 35mm full frame CMOS sensor with an equivalent sensitivity in excess of ISO 4,000,000, make it ideal for a wide variety of markets.

KEY FEATURES

- 0.0005 lux (min. scene illumination)
- 12 Stop Dynamic Range
- 1080P / 720P Video to 60fps
- 3G/HD-SDI Terminals
- HDMI Terminal
- Compatible with EF-mount lenses
- Push Auto Iris
- One-Shot AF
- Auto Exposure
- Built-in Motorized ND Filters
- Motorized IR Cut Filter for Infrared Shooting
- Digital Teleconverter
- RS-422 Remote Control Terminal

APPLICATIONS

- Cinema
- Security
- Documentary
- Law Enforcement
- Reality
- Military
- Television
- Scientific
- Astronomy
- Nature and Wildlife
- Underwater

ME20F-SH MULTI-PURPOSE CAMERA

PRODUCT NAME: ME20F-SH

ITEM CODE: 1002C002

UPC CODE: 013803 271249

SPECIFICATIONS

| | | |
|------------------|-------------------------|---|
| IMAGE SENSOR | SENSOR | 35mm Full Frame CMOS (16:9 extract) |
| | TOTAL PIXELS | Approx. 2.59M (2160 x 1200) |
| | EFFECTIVE PIXELS | Approx. 2.26M (2000 x 1128) |
| | RESOLUTION | 1920 x 1080, 1280 x 720 |
| | PIXEL SIZE | 19µm x 19µm |
| | MIN. SUB. ILLUM. | 0.0005 lux or less (at 75dB, F1.2, 29.97P, 50IRE) |
| LENS SYSTEM | CANON EF MOUNT | Cinema Lock type |
| | CANON EF LENSES | EF, EF-S & Cinema (EF) (compatible lenses to be confirmed) |
| INPUT TERMINALS | GEN LOCK | Black burst or Tri-level reference |
| | MICROPHONE | φ3.5mm stereo mini jack (plug-in power mic supported) |
| | REMOTE CONTROL | Remote A: φ2.5mm stereo mini jack (Canon protocol) Remote B: Circular 8-pin for RS-422 (Canon protocol) |
| OUTPUT TERMINALS | 3G/HD-SDI | Terminal 1 (On screen display optional) Terminal 2 (Clean out only) Bit Depth: YCbCr422 10bits (effective bits: 8) Frame Rates: 1920 x 1080: 59.94P/59.94i/50P/50i/29.97P/25P/23.98P 1280 x 720: 59.94P/50P/29.97P/25P/23.98P *Cannot set framerate and output size separately by SDI and HDMI. |
| | HDMI | Terminal 1 (On screen display optional) Bit Depth: RGB444, YCbCr422, YCbCr444 (effective bits: 8 for each format) Frame Rates: 1920 x 1080: 59.94P/59.94i/50P/50i/29.97P/25P/23.98P 1280 x 720: 59.94P/50P/29.97P/25P/23.98P **640 x 480: 59.94P & 768x576: 50P will be output when connected with a monitor that support 480P and 576P inputs. Cannot be set from the menu and the on screen display will not show. |
| EXPOSURE MODES | AUTO EXPOSURE (AE) | Iris, Gain, Shutter and ND filter operating together (Cannot set auto/manual separately) AE shift/AE response selectable AGC limit can be set from 36dB to Off/75dB (3-dB intervals) |
| | MANUAL | Iris: 1/2 stops (push auto iris can be set to an assign button) Gain: 0dB to 75dB @ 3-dB intervals (approx. ISO 4,560,000 equivalent at 75dB) Shutter: 1/3 to 1/2000 (1/4 stops) |
| IMAGE CONTROL | FOCUS CONTROL | Manual focus (when used with RC-V100) ONE SHOT AF (can be set to an assign button) |
| | W/B | AWB (2,000K-15,000K), Daylight, Tungsten, Custom Set A, Custom Set B |
| | OPTICAL FILTERS | ND filters: 1/8 & 1/64 Built-in (auto or motorized manual) IR cut filter: On/Off (motorized manual) |
| | DIGITAL TELECONVERTER | 2x, 4x |
| | CUSTOM PICTURE SETTINGS | EOS Standard, Wide DR, Canon Log, Custom 1-6 |
| | OTHER FUNCTIONS | Auto black balance, color bar, test tone (interlocking with color bar), assign buttons, peripheral illumination correction, focus limit, crop for EF-S Lens, scan reverse, flicker reduction, noise reduction, time display, hour meter |
| POWER INPUT | TERMINALS | XLR 4-pin or terminal block 2-pin jack |
| | INPUT | DC +11V ~ +17V |
| | CONSUMPTION | Power consumption Approx. 12W (body only) |
| OTHER | OPERATING TEMPERATURE | Approx. 0 - 40° C (32-104° F) |
| | DIMENSIONS | 4.0 x 4.6 x 4.4 in. (102 x 116 x 113mm) |
| | WEIGHT | Approx. 2.4 lbs. (1,100g) |
| | INCLUDED IN THE BOX | ME20F-SH, 2-pin DC Power Contact |
| | RELATED ACCESSORIES | Canon RC-V100 Remote Controller, Canon EF Lenses |

EXCEPTIONAL LOW LIGHT PERFORMANCE

The ME20F-SH Multi-Purpose Camera features a newly developed Canon full frame 35mm CMOS sensor with an equivalent sensitivity in excess of 4,000,000 ISO. Able to capture full color 1080p video up to 60fps, the ME20F-SH camera is ideal when shooting in extreme low light environments.

LARGE PHOTO SITES

The 35mm full-frame CMOS image sensor was specifically developed to shoot Full-HD video in low light, by increasing the light-sensing surface area of each pixel on the sensor. Photo sites measuring 19 micrometers square allow for exceptional low light performance, with a minimum subject illumination of below 0.0005 (at maximum 75 dB gain).

FLEXIBLE MULTI-PURPOSE DESIGN

The ME20F-SH Multi-Purpose Camera was designed specifically with many mounting points along the top and bottom of the camera to allow the freedom for users to customize the rigging of the camera for almost any purpose from a minimal compact size to a fully rigged configuration.

COMPATIBLE WITH EF MOUNT LENSES

The ME20F-SH Multi-Purpose Camera is compatible with Canon's line of EF mount lenses.

The camera comes equipped with a Canon locking EF mount, allowing the lens to be attached or removed without the need to rotate the lens barrel. This facilitates changing lenses in applications where multiple accessories are attached to the lens.



REMOTE CONTROL

The ME20F-SH Multi-Purpose Camera can be controlled via either of the two remote terminals offering a mini-pin or RS-422 connection that utilize Canon's OK protocol and is compatible with the RC-V100 Remote Controller.

The front of the camera features a 12-pin lens terminal enabling power connectivity with EF mount CINE-SERVO lenses or 2/3" broadcast lenses with a third party adapter. Support for lens communication will be added in a future firmware update.



RC-V100 Remote Controller

©2015 Canon U.S.A., Inc. All rights reserved. Not responsible for typographical errors. Specifications subject to change without notice. Products not shown to scale. Certain images and effects are simulated. Canon is a registered trademark of Canon Inc. in the United States and may also be a trademark or registered trademark in other countries. All other products and brand names may be registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.



For more info:
pro.usa.canon.com
[@CanonUSApro](https://twitter.com/CanonUSApro)