

Standalone Battery Backup

Protect your investment with a comprehensive backup solution



SurgeX offers a complete UPS product line to meet your battery backup needs. Available in multiple configurations, our standalone UPS solutions provide backup power to keep equipment running and properly shut down critical systems in the event of a power outage.















For critical systems that require online battery backup, our UPS-1000-OL, UPS-2000-OL, and UPS-3000-OL solutions each deliver network grade power through double-conversion technology. They offer the perfect standalone backup solution for sensitive audio video systems, critical business servers, point of sale equipment, telephone, and data networks equipment that demand prolonged runtimes of 1.5 hours or greater. All three solutions provide extended scalable runtimes of up to 18 hours via self-charging extended battery packs and easily replaceable battery trays.

Reliable battery backup is possible. No matter what your industry, we have a premium standalone UPS solution for you.

Also available in a bundled solution with our SurgeX surge elimination technology rack mount product line to provide comprehensive protection for connected equipment.

Features:

- Online, double-conversion Uninterruptible Power Supply
- True sinewave output
- Controllable receptacles
- Configurable as tower or 19" rack
- Hot swappable-user replaceable battery trays
- Intuitive LCD screen
- UPS monitoring software
- Optional SNMP card available
- 3 Year Product Warranty
- 3 Year Battery Warranty

	Model Number	Plug Configuration		Description
		Input	Output	
	UPS-1000-OL	 NEMA 5-15P	 (3x) NEMA 5-15R Direct  (3x) NEMA 5-15R Programmable	120V/15A, 1000 VA, Online, 2U
	UPS-2000-OL	 NEMA 5-20P	 (2x) NEMA 5-20R  (1x) NEMA L5-20R Direct  (2x) NEMA 5-15R Programmable	120V/20A, 2000 VA, Online, 2U
	UPS-3000-OL	 NEMA L5-30P	 (2x) NEMA 5-20R  (1x) NEMA 5-30R (1 foot cord) Direct  (2x) NEMA 5-20R Programmable	120V/30A, 3000 VA, Online, 2U

Standalone Battery Backup

Technical Specifications	UPS-1000-OL	UPS-2000-OL	UPS-3000-OL
Power Rating	1000 VA / 900 W	2000 VA / 1800 W	3000 VA / 2700 W
Topology	On-Line Double Conversion	On-Line Double Conversion	On-Line Double Conversion
Heat Dissipation (BTU/Hour)	520 at 100% Load	1171 at 100% Load	1756 at 100% Load
Input Voltage (Nominal) Range	100-120 VAC 90-150 VAC	100-120 VAC 105-150 VAC	100-120 VAC 105-150 VAC
Input Frequency	50/60 Hz ± 4 (Auto Sense on Start-Up)	50/60 Hz ± 4 (Auto Sense on Start-Up)	50/60 Hz ± 4 (Auto Sense on Start-Up)
Input Power Factor	>0.95	>0.95	>0.95
Input Current THD	<9.0%	<9.0%	<9.0%
Efficiency	>84.0%	>84.0%	>84.0%
Output Voltage	120 VAC (Default) 100/110/115 VAC (Selectable)	120 VAC (Default) 100/110/115 VAC (Selectable)	120 VAC (Default) 100/110/115 VAC (Selectable)
Output Current	8.3 A (Default) 10.0/9.1/8.7 A (Selectable)	16.7 A (Default) 20.0/18.2/17.4 A (Selectable)	25.0 A (Default) 30.0/27.3/26.1 A (Selectable)
Voltage Regulation	$\pm 1.0\%$	$\pm 1.0\%$	$\pm 1.0\%$
Overload Online Mode	100-105%: Continuous; Warning Only 105-130%: 2 Minutes 130-200%: 10 Seconds >200%: 250 Milliseconds	100-105%: Continuous; Warning Only 105-130%: 2 Minutes 130-200%: 10 Seconds >200%: 250 Milliseconds	100-105%: Continuous; Warning Only 105-130%: 2 Minutes 130-200%: 10 Seconds >200%: 250 Milliseconds
Overload Battery Mode	100-105%: Continuous; Warning Only 105-130%: 10 Seconds >130%: 250 Milliseconds	100-105%: Continuous; Warning Only 105-130%: 10 Seconds >130%: 250 Milliseconds	100-105%: Continuous; Warning Only 105-130%: 10 Seconds >130%: 250 Milliseconds
Overload Bypass Mode	100-110%: Continuous; Warning Only 110-120%: 30 Minutes 120-130%: 10 Minutes >130%: 1 Minute	100-110%: Continuous; Warning Only 110-120%: 30 Minutes 120-130%: 10 Minutes >130%: 1 Minute	100-110%: Continuous; Warning Only 110-120%: 30 Minutes 120-130%: 10 Minutes >130%: 1 Minute
Battery Voltage (Float / Nominal)	27.4/24.0 VDC	54.7/48.0 VDC	82.1/72.0 VDC
Charger Current	1.0 A	1.0 A	1.0 A
Backup Time (Full Load)	>3.5 Minutes	>3.6 Minutes	>3.6 Minutes
Communications Interface	USB / RS-232	USB / RS-232	USB / RS-232
Shipping Weight	47.0 lbs. / 21.4 kg.	75.5 lbs. / 34.3 kg.	105.0 lbs. / 47.4 kg.
Unit Weight	38.0 lbs. / 17.3 kg.	65.0 lbs. / 29.5 kg.	81.0 lbs. / 36.8 kg.
Length	17.25 in / 438 mm	17.25 in / 438 mm	17.25 in / 438 mm
Height	3.39 in / 86 mm	3.39 in / 86 mm	3.39 in / 86 mm
Depth	16.26 in / 413 mm	20.20 in / 513 mm	24.92 in / 633 mm