

SYSTEM 21

FLUSH MOUNT

Hard Ceiling, Blind Mount
Speaker System.



GENERAL DESCRIPTION

The **SYSTEM 21** is a complete, blind mount loudspeaker system for hard ceiling applications. It consists of an 8C10PAX - 8" O.D. dual cone loudspeaker with a 10 oz. magnet and a TBLU - 5W-25/70V transformer. Loudspeaker and transformer are mounted on a BR8W - round, steel, screw mount baffle along with an ERD8U - 275 CID, round, steel back box. White powder coat finish.

INTENDED USE - Indoor Environment



Program Material	Paging and background music
Installation	Hard ceiling, blind mount

AUDIO SPECIFICATIONS

Average Sensitivity	92 dB SPL, 1W/ 1M
Loudspeaker Power Rating	20W RMS, EIA 426A Standard
Calculated Output	104 dB SPL, 5W/ 1M
Magnet Type & Weight	BeFe Ceramic, 10 oz. Nominal
Frequency Response	60Hz - 17kHz EIA 426A Standard
Nominal Coverage Angle	90° Included Angle, -6 dB / 2 kHz, Half space
Audio Connection	7" Color-Coded Pigtails, Pre-Cut
Electrical Access	1/2" Side Mounted, Flexible Conduit Clamp

SYSTEM COMPONENTS

Loudspeaker	8C10PAX
Transformer	25/70V 5W-5 tap Color Coded Leads (5W, 2.5W, 1.25W, 0.63W, 0.31W)
Baffle	BR8W
Enclosure	ERD8U



<p>Recommended construction sequences, installation instructions, and A&E Specifications are available in various formats in the QUAM Architects' and Engineers' Resources section on the web at: www.QuamSpeakers.com</p>				<p>QUAM-NICHOLS COMPANY, INC. 234 East Marquette Rd. Chicago, IL. 60637 Tel: 1-800-NEED-NOW (800-633-3669) Fax: 1-888-NEED-NOW (888-633-3669) e-mail: NeedNow@QNC.com www.QuamSpeakers.com</p>
<p>© 2013 Quam-Nichols Company reserves the right to make changes and/or improvements to its products at any time and without notice.</p>				