

## **SYSTEM 31**

### **SURFACE MOUNTED**

32W (16W X 2) Corridor Loudspeaker System, Dual Horn, (2)16W-25/70V Integrated Transformers

### **GENERAL DESCRIPTION**

The **SYSTEM 31** is a complete, surface mounted corridor loudspeaker system consisting of two (2) double re-entrant horn, compression type loudspeakers and integrated 16W-25/70V transformers with terminal block connection. White powder coat finish with a black powder coated mounting pedestal.

### **INTENDED USE - Indoor Environment**

Program Material Installation Signal tones and voice

Surface mounted to wall or ceiling with the long axis parallel to the floor plane and traffic flow.

Recommended height: 8' to 12' above finished floor.

### **AUDIO SPECIFICATIONS**


Average Sensitivity
Loudspeaker Power Rating
Maximum System Output
Magnet Type & Weight
Frequency Response
Nominal Coverage Angle

110 dB SPL, 1W/1M 16W RMS EIA 426A Standard 122 dB-SPL 16W/1M BeFe Ceramic, 4.8 oz. 300 Hz - 15 KHz EIA 426A Standard


Vertical: 90° Included Angle Horizontal: 45° Included Angle -6 dB / 2 kHz, Half space

Audio Connection | Terminal Block

# 711/16



Top View



## 311/16 23/16 of 35/16 of 35/16

Rear View

### **SYSTEM COMPONENTS**

Loudspeaker Integrated Transformer

2X - H16T

25/70V 16W: 5 tap, Color Coded Leads


(16W, 8W, 4W, 2W, 1W)

### **RECOMMENDED QUAM COMPONENTS**

Mounting Device | Drop Ceiling Installation : SSB-1900, SSB-1900DEEP

Recommended construction sequences, installation instructions, and A&E Specifications are available in various formats in the QUAM Architects' and Engineers' Resources section on the web at:

www.QuamSpeakers.com









QUAM-NICHOLS COMPANY, INC. 234 East Marquette Rd. Chicago, IL. 60637 Tel: 1-800-NEED-NOW (800-633-3669) Fax: 1-888-NEED-NOW (888-633-3669) e-mail: NeedNow@QNC.com www.QuamSpeakers.com