



Bright and Versatile Multimedia Projector with MHL and Connectivity Ports Suitable for Almost Any Presentation

FEATURES

- Bright 3,500 ANSI lumens with a high 15,000:1 contrast ratio
- Energy efficient lamp that last up to 7,000 hours (in dynamic eco. mode)
- The 1.39-2.09:1 throw ratio with 1.5x zoom ensures a flexible installation
- 6 Segment (RYGCWB) color wheel for accurate and detailed images
- Quick auto search filtering to quickly locate input signal source
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Variety of display connectivity options including: HDMI v1.4b (2x of which 1x MHL), VGA-in (2x), VGA-Out, S-Video and Composite Video
- 3D compatibility with DLP® Link™ and HDMI 1.4b Blu-Ray support for dazzling and realistic life-like images
- Internal audio speaker delivers 10W of total audio power
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Sealed optical engine, minimizing the impact of dust and smoke
- Top-loading, sliding cover for quick and easy lamp replacement
- Compatible with long VGA cables for a maximum length of up to 20 meters
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad



The DH913 is a high impact multimedia projector with a native 1080p resolution is the ideal projector for either home or office use. It delivers 3,500 ANSI lumens of brightness together with a 15,000:1 contrast ratio. The DH913 comes equipped with a range of features that makes it ideal for professional presentations. The high image resolution delivers excellent fidelity and a large screen area for simultaneous display of video conferencing, presentations, and display of charts and graphs. Whether for business, education or home use, the projector offers the essential connectivity options including VGA-In (2x), HDMI v1.4b (2x of which 1x MHL), S-Video and Composite Video. This user-friendly and versatile projector delivers a flawless performance required for today's high definition presentations.

DH913

MULTIMEDIA



SPECIFICATIONS



Display Type	Single 0.65"DLP® Technology by TI
Brightness	3,500 ANSI Lumens
Native Resolution	1080p (1920 x 1080)
Maximum Resolution	WUXGA (1920 x 1200) @60Hz
Contrast Ratio	15,000:1
Lamp Life and Type	3,000/ 4,000 Hours (Normal/Eco Mode), 280W/230W, Osram
Throw Ratio	1.39 - 2.09:1
Image Size (Diagonal)	25.9" - 324.9"
Projection Distance	1.2 - 10m
Projection Lens	F#2.418 - 2.97, f = 20.7 - 31.05mm
Zoom Ratio	1.5x
Aspect Ratio	16:9 Native
Offset (full image height)	115%
Keystone Correction	Vertical +/- 40°
Horizontal Frequency	15, 31 - 91.4Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
3D Compatibility	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
Audio	10W
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,L)
I/O Connection Ports	VGA-In (2x), HDMI v1.4b (2), S-Video, Composite Video, Audio-In (RCA), Audio-In (Mini-Jack), Audio-Out (Mini-Jack), RJ45, 12v Trigger, RS-232, USB miniB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	285 x 261 x 121.8 mm
Weight	3,15 kg
Noise Level	37dB/39dB (Eco/Normal Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 290W (Normal Mode) 240W (Eco Mode) <0.5W (Standby Mode)
Standard Warranty	3 years projector / 1 year on lamp or 1000 hours whichever comes first
Education Warranty	5 years projector / 3 years on lamp or 2000 hours whichever comes first
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Lens Cap, Carry Case, Documentation Kit
Optional Accessories	Replacement Lamp: 5811118715-SVV
UPC	813097020161

© Copyright 2015 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.

DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands
tel: +31 20 655 0960 | fax: +31 20 655 0999 | email: info@vivitek.eu