

Interlocking Dual LED Beam Fixture + Aura Effects

LOOK™ is a super-bright dual beam LED fixture with mesmerizing aura effects, plus interlocking capabilities. They come fitted with 2* high output 60W 4-in-1 RGBW LEDs with a sharp 4.5° beam angle, then 2* 4-segment circular RGB rings surround each LED to create eye-catching dynamic effects. Each individual LED (including the aura LED segments) is individually DMX controllable for pixel mapping.

These fixtures also offer built-in vertical and horizontal locking mechanisms to allow connection of multiple fixtures together in a matrix combination, and can be set up on the ground, or mounted on truss. The "LOOK Klamp" is also available (sold separately), which is a modular dual Omega bracket mounting plate that fits perfectly into the top 4-peg locking mechanism of the fixture. "LOOK Klamp" comes with the plate attachment, plus (2) 1/4 turn Omega brackets.

LOOK™ fixtures can be controlled via 13/24 or 45-channel DMX modes, which gives users total control of all the goodies including beam 1 and beam 2 individual R/G/B/W intensity levels, beam 1 and beam 2 individual linear CTO presets (2700-10000k), 67 beam color macros, beam LED strobe effects, 4 dimming curve modes, 10 auto programs, 20 built-in aura effects with speed control, aura strobe effects, plus each of the eight aura LED segment's RGB intensity levels.

Then on the back on the unit is an easy-to-use LCD control panel that allows access to a ton of features including DMX mode selection, auto modes, multiple sound active modes, master/slave settings, plus other convenient features such as menu display flip, display shut off timer, run time info, and both beam and aura testing modes.

They come with a single mounting bracket with secure locking knobs, industry standard powerCON® compatible power input and output connections, and 3 and 5-pin DMX input and output connections.

And of course, LOOK™ is backed by Blizzard's 2-year warranty!

Luminous Intensity:

Lux/m	Red	Green	Blue	White	All
1m	15,710	13,150	19,500	22,280	72,300
2m	6,750	5,590	7,850	11,070	28,240
3m	2,969	2,881	3,835	4,980	13,510
4m	1,822	1,692	2,356	2,750	7,280
5m	1,112	990	1,463	1,769	4,560

Main Features:

- 2* high output 60W RGBW 4-in-1 LEDs
- 2* 4-segment ring aura effects (16 x 0.5W RGB LEDs)
- Individually controllable beams and aura effects
- Ultra-sharp 4.5° beam angle (x2)
- 2700-10000K CTO
- User adjustable white balance settings
- Stackable and side-by-side locking linear array
- LED drive current: beam=4500mA, aura=30mA
- User selectable 32-bit dimming modes, 0-20Hz strobe effects
- 2.4 inch TFT color LCD display
- 3-pin and 5-pin male/female input and outputs
- PowerCon™ compatible AC power In/Out connectors



*Look Klamp™ (sold separately)

Power:

- 100-240VAC, 50-60 Hertz
- Power Consumption: 198W, 1.64A, PF:99

Light Source:

- 2x 60W RGBW 4-in-1 LEDs with 4.5° Beam Angle
- 2x 4-segment (16 x 0.5W RGB 3-in-1 LEDs)

Control:

- Protocol: USITT DMX-512
- 13/24 or 45-Channel DMX Modes
- Standalone, Master/Slave, Auto, Sound Active
- 3/5-pin XLR In/Out Connections
- LCD Control Panel with 4x Touch Sensitive Buttons

Weight & Dimensions:

- Dimensions: 11.8" (300 mm) x 9.4" (237 mm) x 5.1" (130 mm)
- Weight: 15.4 lbs. (7 kg)

Warranty:

- 2-year limited warranty, does not cover malfunction caused by damage to LEDs