



C2G Classroom Speakers

Rich classroom audio that meets K-12 technology budgets

C2G classroom speakers are specifically designed for use in K-12 classrooms to deliver high quality audio from multimedia presentations, video clips, movies and other curriculum throughout the classroom. This line of speakers is offered in both wall mount and ceiling mount configurations to meet the needs of different classroom designs. Available in industry standard 8 Ohm and 70 volt versions, these speakers ensure long life and quality sound. The C2G Classroom Speakers integrate seamlessly with the TruLink® Audio Amplifier to provide a complete classroom sound system. Additionally, the speakers can be combined with the TruLink® A/V controller and RapidRun® for a complete connected classroom.

Ceiling speakers mount easily for a clean, unobtrusive look while dispersing sound down to students at 125 degrees for full classroom coverage. Wall mount speakers work best in classrooms with sharp angles or room partitions (alcoves) or in rooms where ceiling mounting is not a practical option. Designed for long life, rubber surrounds and poly cone construction provide a durable solution that will not degrade over time compared with paper/foam constructed speaker components.

Features:

- Available in both wall mount and ceiling mount configurations
- Can be combined with the TruLink A/V controller and RapidRun for a complete sound system
- Rubber surrounds and poly cone construction provide a durable long life solution
- Warranty: 1 year

Part Number	Description
39903	C2G 5in Ceiling Speaker—White
39904	C2G 6in Ceiling Speaker—White
39905	C2G 5in Wall Mount Speaker—Black
39906	C2G 4in Wall Mount Speaker—Black
39907	C2G 5in Ceiling Speaker 70v—White
39908	C2G 5in Wall Mount Speaker 70v—Black



39903 – Cables To Go® 5in Ceiling Speaker-White

Impedance:	8Ω
Wattage:	20W
Efficiency:	88dB/W
Frequency response:	100Hz - 20kHz
Type of speaker:	2-way
Woofers:	5in PP
Tweeter:	½in Mylar
Dispersion:	120°
Grill material:	Iron
Enclosure material:	ABS plastic
Operating temperature:	-10° - 50°C
Dimensions (diameter x depth):	203x80mm
Weight:	685g
Color:	White
Packaging:	Brown box
Mounting:	Pivoting mounting arms

39904 – Cables To Go® 6in Ceiling Speaker-White

Impedance:	8Ω
Wattage:	30W
Efficiency:	88dB/W
Frequency response:	90Hz - 20kHz
Type of speaker:	2-way
Woofers:	6in PP
Tweeter:	½in Mylar
Dispersion:	120°
Grill material:	Iron
Enclosure material:	ABS plastic
Operating temperature:	-10° - 50°C
Dimensions (diameter x depth):	230x90mm
Weight:	980g
Color:	White
Packaging:	Brown box
Mounting:	Pivoting mounting arms

39907 – Cables To Go® 5in Ceiling Speaker 70v-White

8Ω Wattage Tap:	20W
Wattage Taps:	20W/10W/ 5W/2.5W
Efficiency:	88dB/W
Frequency response:	100Hz - 20kHz
Type of speaker:	2-way
Woofers:	5in PP
Tweeter:	½in Mylar
Dispersion:	120°
Grill material:	Iron
Enclosure material:	ABS plastic
Operating temperature:	-10° - 50°C
Dimensions (diameter x depth):	203x80mm
Weight:	685g
Color:	White
Packaging:	Brown box
Mounting:	Pivoting mounting arms

39905 – Cables To Go® 5in Wallmount Speaker-Black

Impedance:	8Ω
Wattage:	30W
Efficiency:	89dB/W
Frequency response:	100Hz - 20kHz
Type of speaker:	2-way
Woofers:	5in PP
Tweeter:	1in SILK
Dispersion:	120°
Grill material:	Iron
Enclosure material:	ABS plastic
Operating temperature:	-10° - 50°C
Dimensions (diameter x depth):	242x182x162mm
Weight:	820g
Color:	Black
Packaging:	Brown box
Mounting:	Metal "C" bracket

39906 – Cables To Go® 4in Wallmount Speaker-Black

Impedance:	8Ω
Wattage:	20W
Efficiency:	89dB/W
Frequency response:	100Hz - 20kHz
Type of speaker:	2-way
Woofers:	4in PP
Tweeter:	1in PEI
Dispersion:	120°
Grill material:	Iron
Enclosure material:	ABS plastic
Operating temperature:	-10° - 50°C
Dimensions (diameter x depth):	215x170x150mm
Weight:	685g
Color:	Black
Packaging:	Brown box
Mounting:	Metal "C" bracket

39908 – Cables To Go® 5in Wallmount Speaker 70v-Black

8Ω Wattage Tap:	20W
Wattage:	30W/15W/ 7.5W/3.75W
Efficiency:	89dB/W
Frequency response:	100Hz - 20kHz
Type of speaker:	2-way
Woofers:	5in PP
Tweeter:	1in SILK
Dispersion:	120°
Grill material:	Iron
Enclosure material:	ABS plastic
Operating temperature:	-10° - 50°C
Dimensions (diameter x depth):	242x182x162mm
Weight:	685g
Color:	Black
Packaging:	Brown box
Mounting:	Metal "C" bracket

