

## Specifications

Type	
Type	Digital AF/AE single-lens reflex camera with built-in flash
Recording Media	SD/SDHC/SDXC memory cards <ul style="list-style-type: none"> <li>• SD speed class-compatible</li> <li>• UHS-I compatible</li> <li>• High-speed writing is supported when a UHS-I compatible SD card is used.</li> <li>• Compatible with Eye-Fi Cards.</li> <li>• Multimedia cards (MMC) cannot be used (card error will be displayed).</li> </ul>
Image Format	Approx. 22.3 x 14.9mm (APS-C Size)
Compatible Lenses	Canon EF lenses (including EF-S lenses, excluding EF-M lenses)
Lens Mount	Canon EF mount
Image Sensor	
Type	CMOS sensor (supporting Dual Pixel CMOS AF)
Pixels	Effective pixels: Approx. 24.2 Megapixels Total pixels: Approx. 25.8 Megapixels
Pixel Unit	Approx. 3.72 μm square
Aspect Ratio	3:2 (Horizontal:Vertical)
Color Filter System	RGB primary color filters
Low Pass Filter	Installed in front of the image sensor, non-detachable
Dust Deletion Feature	(1) Self Cleaning Sensor Unit <ul style="list-style-type: none"> <li>• Removes dust adhering to the low-pass filter.</li> <li>• Self-cleaning executed automatically (taking approx. 2 sec.) when power is turned on or off. Manual execution also possible (taking approx. 7 sec.).</li> <li>• After the cleaning is performed, the camera will automatically restart (power OFF to ON).</li> </ul> (2) Dust Delete Data acquisition and appending <ul style="list-style-type: none"> <li>• The coordinates of the dust adhering to the low-pass filter are detected by a test shot and appended to subsequent images.</li> <li>• The dust coordinate data appended to the image is used by the provided software to automatically erase the dust spots.</li> </ul> (3) Manual cleaning
Recording System	
Recording Format	Compliant to Design rule for Camera File system 2.0 and EXIF 2.3
Image Format	Still Image: JPEG, RAW (14 bit Canon Original) Video: MOV (Full HD Movie: MPEG4 AVC/H.264*; Audio: Linear PCM), MP4 (Movie: MPEG4 AVC/H.264*; Audio: AAC) * Variable (averaged) bit rate

<p><b>File Size</b></p>	<p>3:2 Aspect Ratio  Large: 6000 x 4000  Medium: 3984 x 2656  Small 1: 2976 x 1984  Small 2: 2400 x 1600  RAW: 6000 x 4000</p> <p>4:3 Aspect Ratio  Large: 5328 x 4000*  Medium: 3552 x 2664  Small 1: 2656 x 1992  Small 2: 2112 x 1600*  RAW: 6000 x 4000</p> <p>16:9 Aspect Ratio  Large: 6000 x 3368*  Medium: 3984 x 2240*  Small 1: 2976 x 1680*  Small 2: 2400 x 1344  RAW: 6000 x 4000</p> <p>1:1 Aspect Ratio  Large: 4000 x 4000  Medium: 2656 x 2656  Small 1: 1984 x 1984  Small 2: 1600 x 1600  RAW: 6000 x 4000</p> <ul style="list-style-type: none"> <li>• Values for recording pixels are rounded to the nearest 100,000.</li> <li>• JPEG images are generated in the set aspect ratio.</li> <li>• RAW images are generated in [3:2], and the set aspect ratio is appended.</li> </ul> <p>* Indicate an inexact proportion.</p>
<p><b>File Numbering</b></p>	<p>The following three types of file numbering method can be set:</p> <p>(1) File numbering method</p> <p>Continuous numbering</p> <ul style="list-style-type: none"> <li>• The numbering of captured images will continue even after you replace the camera's card.</li> </ul> <p>Auto reset</p> <ul style="list-style-type: none"> <li>• When you replace the camera's card, the numbering will be reset to start from 0001.  If the new card already contains images, the numbering will continue from the last recorded image in the card.</li> </ul> <p>(2) Manual reset</p> <ul style="list-style-type: none"> <li>• Resets the file number to 0001, and creates a new folder automatically.</li> </ul>
<p><b>RAW + JPEG Simultaneous Recording</b></p>	<p>Simultaneous recording is possible using a combination of RAW and JPEG (Large).</p>
<p><b>Color Space</b></p>	<p>sRGB/Adobe RGB</p>
<p><b>Picture Style</b></p>	<p>(1) Auto  (2) Standard  (3) Portrait  (4) Landscape  (5) Fine Detail  (6) Neutral  (7) Faithful  (8) Monochrome  (9) User Def. 1-3</p> <ul style="list-style-type: none"> <li>• In Basic Zone modes, [Auto] will be set for &lt;Fish-eye effect&gt; and &lt;HDR art standard&gt; of the &lt;Creative filters&gt; mode, and [Standard] will be set for other modes.</li> <li>• In Creative Zone modes, you can select or set the Picture Style.</li> <li>• [Auto] is the default setting for [User Def. 1-3].</li> </ul>

White Balance										
<b>Settings</b>	(1) Auto (Ambience priority/White priority) (2) Daylight (3) Shade (4) Cloudy* (5) Tungsten light (6) White fluorescent light (7) Flash (8) Custom (Custom WB) * Effective also in twilight and sunset.									
<b>Auto White Balance</b>	Option between ambience priority and white priority settings									
<b>Color Temperature Compensation</b>	Blue/amber bias: ±9 levels Magenta/green bias: ±9 levels • Corrected in reference to the current WB mode's color temperature.									
Viewfinder										
<b>Type</b>	Eye-level SLR (with fixed pentamirror)									
<b>Coverage</b>	At approx. 19mm eyepoint <table border="1" data-bbox="453 768 1485 995"> <tbody> <tr> <td rowspan="4">Aspect ratio</td> <td>3.2</td> <td>Approx. 95% vertically/horizontally</td> </tr> <tr> <td>4:3</td> <td>Approx. 95% vertically/horizontally</td> </tr> <tr> <td>16:9</td> <td>Approx. 93% vertically Approx. 95% horizontally</td> </tr> <tr> <td>1:1</td> <td>Approx. 95% vertically/horizontally</td> </tr> </tbody> </table>	Aspect ratio	3.2	Approx. 95% vertically/horizontally	4:3	Approx. 95% vertically/horizontally	16:9	Approx. 93% vertically Approx. 95% horizontally	1:1	Approx. 95% vertically/horizontally
Aspect ratio	3.2		Approx. 95% vertically/horizontally							
	4:3		Approx. 95% vertically/horizontally							
	16:9		Approx. 93% vertically Approx. 95% horizontally							
	1:1	Approx. 95% vertically/horizontally								
<b>Magnification</b>	Approx. 0.82x/23.2° (with 50mm lens at infinity, -1m <sup>-1</sup> )									
<b>Eye Point</b>	Approx. 19mm (at -1m <sup>-1</sup> from the eyepiece lens center)									
<b>Dioptric Adjustment Correction</b>	Adjustable from approx. -3.0 to +1.0m <sup>+1</sup> (dpt)									
<b>Focusing Screen</b>	Fixed									
<b>Mirror</b>	Quick-return all-surface half mirror									
<b>Viewfinder Information</b>	Displayed with transparent liquid crystal (1) AF point information • Including Area AF frame (2) Spot metering circle (3) Electronic level (4) Grid (5) Aspect line (6) Flicker detection									
<b>Depth of Field Preview</b>	Provided with depth of field preview button									
Autofocus										
<b>Type</b>	TTL secondary image-forming phase-difference detection system with AF-dedicated sensor									

<b>AF Points</b>	<p>Up to 45 points (cross-type AF points: max. 45)</p> <table border="1" data-bbox="456 163 1224 394"> <thead> <tr> <th>AF Points and AF Patterns</th> <th>AF Points (max.)</th> </tr> </thead> <tbody> <tr> <td>Dual cross-type AF points supporting f/2.8 and f/5.6</td> <td>1</td> </tr> <tr> <td>Cross-type AF points supporting f/5.6</td> <td>45</td> </tr> <tr> <td>AF points supporting f/8</td> <td>27 (Cross-type AF point 9)</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>• The number of AF points, Cross-type AF points and dual cross-type AF points varies depending on the lens used.</li> <li>• Note that, with aspect ratio of 1:1, the maximum number of AF points becomes 35. (Each left and right end line of AF points in total of ten are not usable.)</li> </ul>	AF Points and AF Patterns	AF Points (max.)	Dual cross-type AF points supporting f/2.8 and f/5.6	1	Cross-type AF points supporting f/5.6	45	AF points supporting f/8	27 (Cross-type AF point 9)
AF Points and AF Patterns	AF Points (max.)								
Dual cross-type AF points supporting f/2.8 and f/5.6	1								
Cross-type AF points supporting f/5.6	45								
AF points supporting f/8	27 (Cross-type AF point 9)								
<b>AF Working Range</b>	<p>Conditions: One-Shot AF, at 73°F/23°C, ISO 100 (based on Canon's testing standards and environment)</p> <table border="1" data-bbox="456 594 1224 825"> <thead> <tr> <th>AF Point</th> <th>Brightness</th> </tr> </thead> <tbody> <tr> <td>One center AF point focusing supporting f/2.8</td> <td>EV -3 to 18</td> </tr> <tr> <td>One center AF point focusing supporting f/5.6</td> <td>EV -1 to 18</td> </tr> <tr> <td>Peripheral AF points focusing supporting f/5.6</td> <td>EV -0.5 to 18</td> </tr> </tbody> </table>	AF Point	Brightness	One center AF point focusing supporting f/2.8	EV -3 to 18	One center AF point focusing supporting f/5.6	EV -1 to 18	Peripheral AF points focusing supporting f/5.6	EV -0.5 to 18
AF Point	Brightness								
One center AF point focusing supporting f/2.8	EV -3 to 18								
One center AF point focusing supporting f/5.6	EV -1 to 18								
Peripheral AF points focusing supporting f/5.6	EV -0.5 to 18								
<b>Focusing Modes</b>	<p>(1) Autofocus</p> <ol style="list-style-type: none"> <li>One-Shot AF</li> <li>Predictive AI Servo AF (AI Servo AF II)</li> <li>AI Focus AF <ul style="list-style-type: none"> <li>• Switches between One-Shot AF and AI Servo AF automatically.</li> </ul> </li> </ol> <p>(2) Manual focus</p>								
<b>AF Point Selection</b>	<p>(1) Single-point AF (Manual selection)</p> <ul style="list-style-type: none"> <li>• The checkmark cannot be removed from this option.</li> </ul> <p>(2) Zone AF (Manual selection of zone)</p> <ul style="list-style-type: none"> <li>• All the AF points are divided into nine focusing zones.</li> </ul> <p>(3) Large Zone AF (Manual selection of zone)</p> <ul style="list-style-type: none"> <li>• All the AF points are divided into three focusing zones.</li> </ul> <p>(4) Automatic selection AF (45 points)</p>								
<b>AF Assist Beam</b>	<p>Intermittent firing of built-in flash Effective range</p> <table border="1" data-bbox="456 1352 1224 1451"> <tbody> <tr> <td>Center</td> <td>Approx. 13.1 ft. / 4.0m</td> </tr> <tr> <td>Periphery</td> <td>Approx. 11.5 ft. / 3.5m</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>• With an EOS-dedicated Speedlite attached, the Speedlite's AF-assist beam is emitted instead.</li> </ul>	Center	Approx. 13.1 ft. / 4.0m	Periphery	Approx. 11.5 ft. / 3.5m				
Center	Approx. 13.1 ft. / 4.0m								
Periphery	Approx. 11.5 ft. / 3.5m								
<b>Exposure Control</b>									
<b>Metering Mode</b>	<p>7560-pixel RGB+IR metering sensor 63-zone (9 x 7) metering</p> <ol style="list-style-type: none"> <li>Evaluative metering (linked to all AF points)</li> <li>Partial metering (center, approx. 6.0% of viewfinder)</li> <li>Spot metering (center, approx. 3.5% of viewfinder)</li> <li>Center-weighted average metering</li> </ol>								
<b>Metering Range</b>	<p>EV 1-20 (room temperature, ISO 100, evaluative metering)</p>								

**Exposure Control Systems**

- (1) Creative Zone
  - 1) Program AE (Shiftable)
  - 2) Shutter-priority AE
  - 3) Aperture-priority AE
  - 4) Manual exposure (including bulb)
- (2) Basic Zone
  - 1) Scene Intelligent Auto (Program AE /non-shiftable)
  - 2) Flash Off
  - 3) Creative Auto
  - 4) Portrait
  - 5) Landscape
  - 6) Close-up
  - 7) Sports
  - 8) Special Scene
    - i. Group Photo
    - ii. Kids
    - iii. Food
    - iv. Candlelight
    - v. Night Portrait
    - vi. Handheld Night Scene
    - vii. HDR Backlight Control
- 9) Creative Filters
  - i. Grainy B/W
  - ii. Soft Focus
  - iii. Fish-eye Effect
  - iv. Water Painting Effect
  - v. Toy Camera Effect
  - vi. Miniature Effect
  - vii. HDR Art Standard
  - viii. HDR Art Vivid
  - ix. HDR Art Bold
  - x. HDR Art Embossed

**ISO Speed Range**

**Manual Setting**

Normal ISO Speed	ISO 100-25600 (in whole-stop increments)
Expanded ISO Speed	ISO 51200

• For [Highlight tone priority], the settable ISO speed range will be ISO 200-25600.

**Auto ISO Speed Settings**

Shooting Mode		ISO Settings		
		No Flash	Flash (built-in) <sup>2</sup>	Flash (external) <sup>2</sup>
Scene Intelligent Auto, Creative Auto		ISO 100-6400	ISO 400-3200	ISO 400-1600
Flash Off		ISO 100-6400	-	-
Portrait, Close-up		ISO 100-6400	ISO 400-1600	ISO 400-1600
Landscape		ISO 100-6400	-	ISO 400-1600
Sports		ISO 100-6400	-	ISO 400-1600
SCN	Group Photo	ISO 100-6400	ISO 400-3200	ISO 400-1600
	Kids, Food, Night Portrait	ISO 100-6400	ISO 400-1600	ISO 400-1600
	Candlelight, HDR Backlight Control	ISO 100-6400	-	AF-assist beam only
	Handheld Night Scene	ISO 100-12800	ISO 400-6400	ISO 400-6400
Creative Filters	Grainy B/W, Soft Focus, Fish-eye Effect, Water Painting Effect, Toy Camera Effect, Miniature Effect	ISO 100-6400	ISO 400-3200	ISO 400-1600
	HDR Art Standard, HDR Art Vivid, HDR Art Bold, HDR Art Embossed	ISO 100-6400	-	AF-assist beam only
P, Tv, Av, M		ISO 100-25600 <sup>1</sup>	ISO 400-1600 <sup>1</sup>	ISO 400-1600 <sup>1</sup>
With bulb exposures		ISO 400	ISO 400	ISO 400

<sup>\*1</sup> It depends on [Maximum] of [ISO Auto].

<sup>\*2</sup> If fill-in flash will cause overexposure, ISO 100 or a higher ISO will be set.

<b>Exposure Compensation</b>	Manual	±5 stops in 1/3- or 1/2-stop increments*
	AEB	±3 stops in 1/3- or 1/2-stop increments
	<p>* Up to ±2 stops, indicated in the viewfinder.          * Up to ±3 stops when [Shooting screen: Guided] is set.</p>	
<b>AE Lock</b>	<p>(1) Auto AE lock</p> <ul style="list-style-type: none"> <li>In the One-Shot AF mode with evaluative metering, AE lock takes effect when focus is achieved.</li> </ul> <p>(2) Manual AE lock</p> <ul style="list-style-type: none"> <li>In the P, Tv, Av and M modes, enabled with the AE lock button. (Press again to update.)</li> <li>Possible with all metering modes.</li> </ul>	
<b>Shutter</b>		
<b>Type</b>	Vertical-travel, mechanical, focal-plane shutter with all speeds electronically-controlled	
<b>Shutter Speed</b>	1/4000 to 30 sec., bulb (total shutter speed range. Available range varies by shooting mode.) X-sync at 1/200 sec.	
<b>Shutter Release</b>	Soft-touch electromagnetic release	
<b>Self Timer</b>	10-sec. delay, 2-sec. delay	
<b>Shutter Lag Time</b>	<p>(1) With SW-1 ON, time lag between SW-2 ON and start of exposure: approx. 0.070 sec.          (2) Time lag between simultaneous SW-1/SW-2 ON and start of exposure:</p> <ul style="list-style-type: none"> <li>Time lag with the aperture stopped down by 3 stops or less from the open aperture. Excludes AF operation time.</li> </ul>	
<b>Built-in Flash</b>		
<b>Type</b>	Auto pop-up, retractable built-in flash at the pentamirror	
<b>Flash Metering System</b>	E-TTL II autoflash with all EX Series Speedlites	
<b>Guide Number</b>	Approx. 39.4 / 12 (at ISO 100 in feet / meters)	
<b>Flash Coverage</b>	Up to approx. 17mm focal length (equivalent to approx. 28mm in 135 format)	
<b>FE Lock</b>	Provided	
<b>Flash Exposure Compensation</b>	<p>±2 stops in 1/3- or 1/2-stop increments</p> <ul style="list-style-type: none"> <li>Flash exposure compensation for built-in flash and external Speedlite can be set from the camera.</li> </ul>	
<b>External Speedlite</b>		
<b>Flash Metering</b>	E-TTL II autoflash (Evaluative, Average), FE Lock	
<b>Flash Exposure Compensation</b>	±2 stops in 1/3- or 1/2-stop increments	
<b>FE Lock</b>	Provided	
<b>External Flash Settings</b>	<p>(1) External flash control</p> <ul style="list-style-type: none"> <li>Flash firing, E-TTL II metering, Flash mode, Wireless functions, Flash zoom, Shutter synchronization, Flash exposure compensation, Flash exposure bracketing and Clear settings.</li> <li>The radio wireless flash functions can be set from the camera.</li> </ul> <p>(2) External flash Custom Function setting</p> <ul style="list-style-type: none"> <li>The setting options for both (1) and (2) will differ depending on the Speedlite used.</li> </ul>	

Drive System																																																								
<b>Drive Modes and Continuous Shooting Speed during Viewfinder Shooting</b>	<p>(1) Single shooting</p> <p>(2) High-speed continuous shooting</p> <ul style="list-style-type: none"> <li>• Max. approx. 6.0 fps.</li> <li>• Maximum continuous shooting speed with 1/500 sec. or faster shutter speed, maximum aperture (varies depending on the lens), Anti-flicker shooting set to Disable, with a fully-charged Battery Pack LP-E17 and at room temperature (73°F/23°C).</li> <li>• With the AF mode set to One-Shot AF and the Image Stabilizer turned off when using the following lenses: EF 300mm f/4L IS USM, EF 28-135mm f/3.5-5.6 IS USM, EF 75-300mm f/4-5.6 IS USM, EF 100-400mm f/4.5-5.6L IS USM.</li> </ul> <p>(3) Low-speed continuous shooting</p> <ul style="list-style-type: none"> <li>• Max. approx. 3.0 fps</li> </ul> <p>(4) Self-timer: 10 sec./remote control</p> <p>(5) 2 sec. self-timer</p> <p>(6) Continuous shooting after 10-sec. self-timer (2 to 10 shots)</p>																																																							
<b>Maximum Burst</b>	<table border="1"> <thead> <tr> <th rowspan="2">Image-recording Quality</th> <th rowspan="2">Image File Size (approx. MB)</th> <th rowspan="2">Possible Shots (approx.)</th> <th colspan="2">Maximum Burst (approx.)</th> </tr> <tr> <th>Standard</th> <th>High-speed (UHS-I)</th> </tr> </thead> <tbody> <tr> <td>Large (Fine)</td> <td>7.6</td> <td>950</td> <td>190</td> <td>Full</td> </tr> <tr> <td>Large (Normal)</td> <td>3.9</td> <td>1840</td> <td>Full</td> <td>Full</td> </tr> <tr> <td>Medium (Fine)</td> <td>4.1</td> <td>1790</td> <td>Full</td> <td>Full</td> </tr> <tr> <td>Medium (Normal)</td> <td>2.0</td> <td>3480</td> <td>Full</td> <td>Full</td> </tr> <tr> <td>Small 1 (Fine)</td> <td>2.6</td> <td>2730</td> <td>Full</td> <td>Full</td> </tr> <tr> <td>Small 1 (Normal)</td> <td>1.3</td> <td>5260</td> <td>Full</td> <td>Full</td> </tr> <tr> <td>Small 2</td> <td>1.8</td> <td>3810</td> <td>Full</td> <td>Full</td> </tr> <tr> <td>RAW</td> <td>29.4</td> <td>210</td> <td>21</td> <td>27</td> </tr> <tr> <td>RAW + Large (Fine)</td> <td>29.4 + 7.6</td> <td>170</td> <td>19</td> <td>23</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>• The number of possible shots and maximum burst (standard) are with a Canon's standard testing 8GB card. The maximum burst (High-speed) is with a Canon's standard testing 16GB card.</li> <li>• The file size, number of possible shots and maximum burst vary depending on shooting conditions (aspect ratio of 3:2, subject, memory card brand, ISO speed, Picture Style, etc.)</li> <li>• "Full" indicates that shooting is possible until the card becomes full.</li> </ul>				Image-recording Quality	Image File Size (approx. MB)	Possible Shots (approx.)	Maximum Burst (approx.)		Standard	High-speed (UHS-I)	Large (Fine)	7.6	950	190	Full	Large (Normal)	3.9	1840	Full	Full	Medium (Fine)	4.1	1790	Full	Full	Medium (Normal)	2.0	3480	Full	Full	Small 1 (Fine)	2.6	2730	Full	Full	Small 1 (Normal)	1.3	5260	Full	Full	Small 2	1.8	3810	Full	Full	RAW	29.4	210	21	27	RAW + Large (Fine)	29.4 + 7.6	170	19	23
Image-recording Quality	Image File Size (approx. MB)	Possible Shots (approx.)	Maximum Burst (approx.)																																																					
			Standard	High-speed (UHS-I)																																																				
Large (Fine)	7.6	950	190	Full																																																				
Large (Normal)	3.9	1840	Full	Full																																																				
Medium (Fine)	4.1	1790	Full	Full																																																				
Medium (Normal)	2.0	3480	Full	Full																																																				
Small 1 (Fine)	2.6	2730	Full	Full																																																				
Small 1 (Normal)	1.3	5260	Full	Full																																																				
Small 2	1.8	3810	Full	Full																																																				
RAW	29.4	210	21	27																																																				
RAW + Large (Fine)	29.4 + 7.6	170	19	23																																																				
Live View Functions																																																								
<b>Shooting Modes</b>	Still photo shooting and video shooting																																																							
<b>Focusing</b>	<p>(1) Dual Pixel CMOS AF</p> <ul style="list-style-type: none"> <li>• Dual Pixel CMOS AF is possible with all EF and EF-S lenses.</li> <li>• Contrast AF is not provided.</li> </ul> <p>(2) Manual focus</p> <ul style="list-style-type: none"> <li>• Magnifying the image by 5x or 10x for manual focus possible.</li> </ul>																																																							
<b>Metering Modes</b>	<p>Real-time metering with image sensor</p> <ul style="list-style-type: none"> <li>• AE lock possible. The metering timer can be changed.</li> </ul> <p>(1) Evaluative metering (315-zone)</p> <p>(2) Partial metering (center, approx. 6.0% of viewfinder)</p> <p>(3) Spot metering (center, approx. 2.6% of viewfinder)</p> <p>(4) Center-weighted average metering</p> <ul style="list-style-type: none"> <li>• AE lock possible. The active metering timer can be changed.</li> </ul>																																																							
<b>Metering Range</b>	EV 0–20 (room temperature, ISO 100, evaluative metering)																																																							

<b>Grid Display</b>	(1)Off (2)3x3 (3)6x4 (4)3x3+diag
<b>Exposure Simulation</b>	±3 stop increments
<b>Video Shooting</b>	
<b>File Format</b>	MP4 Video: MPEG-4 AVC / H.264 • Variable (averaged) bit rate Audio: AAC MOV: ALL-I (FHD 29.97, time-lapse movies only)

### Video Recording Size and Frame Rates

NTSC		
1920 x 1080	59.94 fps	IPB (Standard)
	29.97 fps	IPB (Standard)
		IPB (Light)
1280 x 720	23.98 fps	IPB (Standard)
	59.94 fps	IPB (Standard)
	29.97 fps	IPB (Light)
640 x 480	29.97 fps	IPB (Standard)
	29.97 fps	IPB (Light)

### Continuous Shooting Time

Video Recording Size			Total Recording Time on Card (approx.)			File Size (approx.)	Bit Rate (approx.)
			4GB	16GB	64GB		
1920 x 1080	59.94 fps	IPB (Standard)	8 min.	35 min.	2 hrs. 21 min.	431 MB/min.	60 Mbps
	29.97 fps	IPB (Standard)	17 min.	1 hr. 10 min.	4 hrs. 41 min.	216 MB/min.	30 Mbps
	23.98 fps						
1280 x 720	29.97 fps	IPB (Light)	43 min.	2 hrs. 53 min.	11 hrs. 35 min.	87 MB/min.	12 Mbps
	59.94 fps	IPB (Standard)	20 min.	1 hr. 21 min.	5 hr. 24 min.	184 MB/min.	26 Mbps
	29.97 fps	IPB (Light)	2 hr. 5 min.	8 hrs. 20 min.	33 hrs. 22 min.	30 MB/min.	4 Mbps
640 x 480	29.97 fps	IPB (Standard)	57 min.	3 hrs. 50 min.	15 hrs. 20 min.	66 MB/min.	9 Mbps
	29.97 fps	IPB (Light)	2 hrs. 43 min.	10 hrs. 53 min.	43 hrs. 32 min.	23 MB/min.	3 Mbps
HDR Movie 1920 x 1080	29.97 fps	IPB (Standard)	17 min.	1 hr. 10 min.	4 hrs. 41 min.	216 MB/min.	30 Mbps
Time-Lapse Movie 1920 x 1080	29.97 fps	ALL-I	5 min.	23 min.	1 hr. 33 min.	654 MB/min.	90 Mbps

- If the recording time reaches 29 min. 59 sec., the movie shooting stops automatically.
- Movie shooting does not stop automatically even if the file size reaches 4GB.  
(When an SDXC card is formatted in exFAT, a movie will be recorded in a single movie file even if it exceeds 4GB.)

<b>Focusing</b>	(1) Dual Pixel CMOS AF • Contrast AF is not provided. (2) Manual focus • Magnifying the image by 5x or 10x for manual focus possible (not possible during movie shooting).
<b>Range</b>	Full range (0-255)



## Exposure Control

Shooting Mode	Frame Rate	Shutter Speed (sec.)		Aperture Value		ISO Speed (recommended exposure index)	
		Auto Setting	Manual Setting	Auto Setting	Manual Setting	Auto Setting	Manual Setting
Program AE for movie shooting in Basic Zone modes*	29.97, 23.98	1/4000-1/30		Yes		ISO 100-12800	
	59.94	1/4000-1/60		Yes		ISO 100-6400 or ISO 100-12800 (H: 25600)	
Program AE for movie shooting in Creative Zone modes	29.97, 23.98	1/4000-1/30					
	59.94	1/4000-1/60					
Manual exposure for movie shooting	23.98		1/4000-1/25			ISO 100-6400 or ISO 100-12800 (H: 25600)	ISO 100-12800 (H: 25600)
	29.97		1/4000-1/30		Yes		
	59.94		1/4000-1/60				

\* In Basic Zone modes, exposure control is exerted as appropriate for the detected scene.

<b>Exposure Compensation</b>	Up to ±3 stops in 1/3- or 1/2-stop increments
<b>LCD Monitor</b>	
<b>Type</b>	TFT color, liquid-crystal monitor
<b>Monitor Size</b>	3.0-inch (screen aspect ratio of 3:2) Approx. 3.03 in./7.70cm diagonal (approx. 2.51 in./6.37cm width, approx. 1.67 in./4.25cm height)
<b>Dots</b>	Approx. 1.04 million dots
<b>Coverage</b>	Approx. 95%* *When the aspect ratio is 16:9, vertical viewfinder coverage is approx. 93%.
<b>Brightness Control</b>	Adjustable to one of seven brightness levels
<b>Coating</b>	Clear View LCD II <ul style="list-style-type: none"> <li>• Anti-smudge coating applied.</li> <li>• Anti-reflection coating not applied.</li> </ul>
<b>Interface Languages</b>	25 (English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Romanian, Ukraine, Turkish, Arabic, Thai, Simplified/Traditional Chinese, Korean, Japanese)
<b>Playback</b>	
<b>Display Format</b>	<p>(1) Single-image display</p> <ul style="list-style-type: none"> <li>• No information display</li> <li>• Basic information display</li> <li>• Detailed shooting information display <ul style="list-style-type: none"> <li>○ Basic shooting information</li> <li>○ Lens information and RGB histogram</li> <li>○ White balance</li> <li>○ Picture Style and sharpness</li> <li>○ Contrast, color saturation and color tone</li> <li>○ Color space and noise reduction</li> <li>○ Lens aberration correction</li> <li>○ GPS information (when GPS Receiver is used)</li> </ul> </li> </ul> <p>(2) Index display</p> <ul style="list-style-type: none"> <li>• 4-image</li> <li>• 9-image</li> <li>• 36-image</li> <li>• 100-image</li> </ul>

<b>Highlight Alert</b>	With detailed information display, overexposed highlight areas with no image data will blink				
<b>Histogram</b>	Brightness and RGB				
<b>Quick Control Function</b>					
<b>Items</b>	Pressing the Quick Control button displays the Quick Control screen during viewfinder shooting, Live View shooting, movie shooting and playback. After selecting an item, you can select contents by operating the Main Dial.				
<b>Image Protection and Erase</b>					
<b>Protection</b>	(1)Single image (select image) (2)Select range (3)All images in a folder (4)All images in a card (5)All found images (only during image search)				
<b>Erase</b>	Except protected images (1) Select image to erase (2)Select range (3)All images in a folder (4)All images in a card (5)All found images (only during image search)				
<b>Direct Printing</b>					
<b>Compatible Printers</b>	PictBridge-compatible printers (wireless LAN only)				
<b>Printable Images</b>	JPEG images compliant to Design rule for Camera File System <ul style="list-style-type: none"> <li>• RAW images can be printed.</li> <li>• Movies cannot be printed.</li> </ul>				
<b>Digital Print Order Format</b>					
<b>DPOF</b>	Compliant to DPOF Version 1.1				
<b>Customization</b>					
<b>Custom Functions</b>	14 Custom Functions with 34 settings settable with the camera				
<b>Custom Controls</b>	Functions can be assigned to the following control parts: <ul style="list-style-type: none"> <li>• Shutter button (halfway pressing)</li> <li>• AE start button</li> <li>• AE lock button</li> <li>• SET button</li> </ul>				
<b>My Menu Registration</b>	<ul style="list-style-type: none"> <li>• Up to six top-tier menu options and Custom Function settings can be registered.</li> <li>• Up to five My Menu tabs can be added.</li> </ul> <table border="1" data-bbox="453 1461 1255 1780"> <tr> <td data-bbox="453 1461 837 1600">My Menu tab overall operations</td> <td data-bbox="837 1461 1255 1600"> <ul style="list-style-type: none"> <li>• Adding a tab</li> <li>• Deleting tabs in a batch</li> <li>• Deleting all tab items</li> <li>• Setting the menu display</li> </ul> </td> </tr> <tr> <td data-bbox="453 1600 837 1780">My Menu tab detailed operations</td> <td data-bbox="837 1600 1255 1780"> <ul style="list-style-type: none"> <li>• Selecting item to register</li> <li>• Sorting registered items</li> <li>• Deleting selected registered items</li> <li>• Deleting registered items in a batch</li> <li>• Deleting tabs</li> <li>• Changing a tab name (16 ASCII characters)</li> </ul> </td> </tr> </table>	My Menu tab overall operations	<ul style="list-style-type: none"> <li>• Adding a tab</li> <li>• Deleting tabs in a batch</li> <li>• Deleting all tab items</li> <li>• Setting the menu display</li> </ul>	My Menu tab detailed operations	<ul style="list-style-type: none"> <li>• Selecting item to register</li> <li>• Sorting registered items</li> <li>• Deleting selected registered items</li> <li>• Deleting registered items in a batch</li> <li>• Deleting tabs</li> <li>• Changing a tab name (16 ASCII characters)</li> </ul>
My Menu tab overall operations	<ul style="list-style-type: none"> <li>• Adding a tab</li> <li>• Deleting tabs in a batch</li> <li>• Deleting all tab items</li> <li>• Setting the menu display</li> </ul>				
My Menu tab detailed operations	<ul style="list-style-type: none"> <li>• Selecting item to register</li> <li>• Sorting registered items</li> <li>• Deleting selected registered items</li> <li>• Deleting registered items in a batch</li> <li>• Deleting tabs</li> <li>• Changing a tab name (16 ASCII characters)</li> </ul>				

Interface																										
<b>USB Terminal</b>	Hi-Speed USB (USB 2.0) <ul style="list-style-type: none"> <li>• For PC communication</li> <li>• For GP-E2 connection</li> <li>• For Connect Station connection</li> </ul>																									
<b>Video Out Terminal</b>	Type C (resolution switches automatically) <ul style="list-style-type: none"> <li>• Video is not displayed unless the video format appropriate for the connected TV set, [NTSC] or [PAL], is set.</li> </ul>																									
<b>Extension System Terminal</b>	3.5mm diameter stereo mini jack <ul style="list-style-type: none"> <li>• Directional Stereo Microphone DM-E1 connection</li> </ul>																									
Power Source																										
<b>Battery</b>	Battery Pack LP-E17 x 1 <ul style="list-style-type: none"> <li>• With the AC Adapter AC-E6N and DC Coupler DR-E18, AC power operation is possible.</li> </ul>																									
<b>Battery Life</b>	<table border="1"> <thead> <tr> <th rowspan="2">Mode</th> <th rowspan="2">Shooting Method</th> <th rowspan="2">Battery</th> <th rowspan="2">Temperature</th> <th colspan="2">Shooting Condition</th> </tr> <tr> <th>AE 100%</th> <th>AE 50% / FA 50%</th> </tr> </thead> <tbody> <tr> <td rowspan="4">Camera body only</td> <td rowspan="2">Viewfinder shooting</td> <td rowspan="2">LP-E17</td> <td>At 73°F/23°C</td> <td>Approx. 820</td> <td>Approx. 600</td> </tr> <tr> <td>At 32°F/0°C</td> <td>Approx. 770</td> <td>Approx. 550</td> </tr> <tr> <td rowspan="2">Live View shooting</td> <td rowspan="2">LP-E17</td> <td>At 73°F/23°C</td> <td>Approx. 310</td> <td>Approx. 270</td> </tr> <tr> <td>At 32°F/0°C</td> <td>Approx. 270</td> <td>Approx. 230</td> </tr> </tbody> </table>	Mode	Shooting Method	Battery	Temperature	Shooting Condition		AE 100%	AE 50% / FA 50%	Camera body only	Viewfinder shooting	LP-E17	At 73°F/23°C	Approx. 820	Approx. 600	At 32°F/0°C	Approx. 770	Approx. 550	Live View shooting	LP-E17	At 73°F/23°C	Approx. 310	Approx. 270	At 32°F/0°C	Approx. 270	Approx. 230
Mode	Shooting Method					Battery	Temperature	Shooting Condition																		
		AE 100%	AE 50% / FA 50%																							
Camera body only	Viewfinder shooting	LP-E17	At 73°F/23°C	Approx. 820	Approx. 600																					
			At 32°F/0°C	Approx. 770	Approx. 550																					
	Live View shooting	LP-E17	At 73°F/23°C	Approx. 310	Approx. 270																					
			At 32°F/0°C	Approx. 270	Approx. 230																					
<b>Battery Check</b>	Automatic battery check when the power switch is turned ON. Displayed in 4 levels.																									
<b>Power Saving</b>	Power turns off after the set time (10/30* or 30 sec., 1, 2, 4, 8 or 15 min.) of non-operation elapses *Normally 10 sec. is set. 30 sec. will be set for function setting, Live View shooting, image playback, etc.																									
<b>Date/Time Battery</b>	Built-in secondary battery When fully-charged, the date/time can be maintained for approx. 3 months <ul style="list-style-type: none"> <li>• Recharge time: approx. 8 hrs. <ul style="list-style-type: none"> <li>◦ To become capable to maintain the right date/time for 3 months after main battery power depletion.</li> </ul> </li> </ul>																									
<b>Start-up Time</b>	Approx. 0.2 sec. (based on CIPA testing standards)																									
Dimensions and Weight																										
<b>Dimensions (W x H x D)</b>	Approx. 5.16 x 3.93 x 3.00 in. (131.0 x 99.9 x 76.2mm) <ul style="list-style-type: none"> <li>• CIPA compliant.</li> </ul>																									
<b>Weight</b>	Approx. 19.05 oz. / 540g (including battery pack and SD memory card) Approx. 17.39 oz. / 493g (body only)																									
Operating Environment																										
<b>Working Temperature Range</b>	32–104°F / 0–40°C																									
<b>Working Humidity Range</b>	85% or less																									