


Intensifier® K 1000 TVL Indoor/Outdoor Vandal Resistant Dome with True WDR

HTINT59K 2.8-12mm auto iris varifocal lens, dark grey housing



Shown with included paintable, snap-on Chameleon Cover™

Features

- 1/3" 1.3MP Sony Sensor
- 1000 TV lines highest resolution in analog
- True WDR functionality
- Superior low-light performance
- Amplify existing light with no distance limitation
- Heater circuitry eliminates fog or condensation under any weather condition
- Presets: Indoor, Outdoor, Low Light, Hallway, Lobby (WDR), Elevator
- Chameleon Cover™: snaps on and can be painted to match any décor!*
- 12VDC & 24VAC dual voltage operation
- Relay output for motion detection
- 3-axis wall and ceiling mount
- Vandal / tamper resistant operation
- IP67 compliant
- 5 year warranty

Specifications

Image Sensor	1/3" 1.3MP Sony Sensor	AGC.....	0 - 20 (level adjustable)
Resolution.....	1000 TV lines	Sense-Up.....	(x2 – x32)
Minimum Illumination.....	0.0001 lux	Motion Tracking	On / Off
Effective Pixels	1305 (H) x 1049 (V)	Motion Detection.....	On / Off (4 zones)
Total Pixels	1312 (H) x 1069 (V)	Privacy.....	On / Off (16 zones)
TV System.....	NTSC	Mirror / V-Flip	On / Off
Scanning System.....	Progressive	Sharpness	0 - 15 (level adjustable)
S/N Ratio	More than 50dB	Lens Shading Compensation	On / Off
Frame rate.....	Max 50P/60P	3DNR.....	Off / Low / Middle / High
Video Output	1.0Vp-p / 75 ohms	Defog.....	On (Auto / Manual) / Off
Lens.....	DC / Manual	DIS.....	On / Off
Electronic Shutter Speed.....	Auto / Manual	Power Supply	12VDC / 24VAC dual voltage operation
	(1/60 sec. - 1/60,000 sec.) / Flicker		(power supply not included)
WDR.....	On (Low / Middle / High) / Off	Power Consumption	12VDC, 590mA / 24VAC, 230mA
Digital WDR.....	On (Low / Middle / High) / Off	Operating Temperature.....	-4° F – 140° F
Day/Night.....	Color / BW / Auto / Ext	Dimensions.....	4.72" (Dia.) x 3.35" (H)
White Balance	Auto / Auto Ext / AWC – SET / Manual	Weight	2.2 lbs.
Brightness.....	0 - 20 (level adjustable)		

Optional Accessories



INTPM
Pendant Mount
(use with 59PLATE and CVCJBD)



INTCM
Corner/Pole Adaptor
(use with INTWM only)



INTWM
Wall Mount
(use with 59PLATE and CVCJBD)



CVCJBD
Dome Camera Junction Box
(use with 59PLATE)



59PLATE
Adaptor Plate



PSW4
24VAC Power Supply



PSW5
12VDC Power Supply

*Chameleon Cover™ - for best results when used outdoors, waterproof paint is recommended. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/20/16