



## LED-1906HDMTLX

High-definition, flush-mount monitor with digital TV tuner and no front controls is ideal for use in any public or controlled environment that requires a quality and durable video display.

### Benefits

- LED backlight: brighter picture using less power
- Displays HD signals (1080i/p and 720p)
- 3D + 3D image processing with digital noise reduction
- Built-in ATSC / Clear QAM Tuner
- Built-in speakers
- IR remote control

### Related Products

- LED-1906HDMTR: Rack-mount version
- LED-1906HDMTL: Flush-mount version
- LED-1906HDMT: Wall-mount version with removable deskstand
- LED-1906HDMTX: Wall-mount version with removable deskstand and no front controls

Specifications	
<b>Mount</b>	Flush Mount
<b>HD Compatible</b>	Yes
<b>Anti Glare Coating</b>	Yes
<b>Screen Panel</b>	18.5" TFT Active Matrix
<b>Case</b>	Durable Metal
<b>IR Remote Control</b>	Yes
<b>Native Aspect Ratio</b>	16:9
<b>Visible Screen Size (WH)</b>	16.1" x 9.1" / 409.8 x 230.4mm
<b>Resolution</b>	1366(H) x 768(V)
<b>Brightness Rating</b>	230 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	1000:1
<b>Back Light</b>	LED (30K)
<b>Dot Pitch</b>	0.30(H) x 0.30(V)mm
<b>Color Depth</b>	16.7M
<b>Number of Pixels</b>	1,049,088
<b>Response Time</b>	5ms (Rising/Falling)
<b>Audio Power / Speakers</b>	8 Ohm, 2 Speakers x 2 Watts
<b>Viewing Angle (L/R/T/B)</b>	85/85/80/80 degrees
<b>3D Comb Filter</b>	Yes
<b>Dimensions</b>	20" x 14.5" x 1.93" / 508.5 x 369 x 49mm
<b>Operating Temp</b>	6 ~ 104°F / -14 ~ 40°C
<b>Humidity</b>	10% ~ 90%
<b>Power Requirements</b>	100 ~ 240 VAC; 50/60 Hz
<b>Power Consumption</b>	< 25 Watts (Active); < 0.5 Watts (Stand-by)
<b>Component</b>	x1 RCA YPbPr Input
<b>Composite</b>	x2 RCA Inputs; x1 RCA Output
<b>VGA</b>	x1 15-pin D-sub Input
<b>HDMI</b>	x3 Inputs
<b>TV (RF)</b>	x1 F (Coax) Input
<b>Audio</b>	x1 RCA L/R Output; x1 3.5mm PC Input
<b>Power</b>	x1 AC Input
<b>Weight</b>	Net: 8 lbs / 3.6 kg; Gross: 11.2 lbs / 5.1 kg

Specifications subject to change.