


## 1855P Coax - Sub-Miniature Plenum



For more Information  
please call

1-800-Belden1

**General Description:**

23 AWG solid .023" bare copper conductor, gas-injected foam FEP insulation, Duofoil® (100% coverage) plus a tinned copper braid shield (95% coverage), flexible Flamarrest® jacket.

**Usage (Overall)****Suitable Applications:**

SMPTE 2081-1 6 Gb/s UHDTV, SMPTE 424M 3 Gb/s HD-SDI 1080p, SDI/HDTV Digital Video, High Definition (HD), Standard Definition (SDI) and Digital Audio Equipment in Professional & Commercial Applications such as TV Stations, Stadiums & Arenas, Convention Center, and other large facilities requiring high quality digital video transmissions, Plenum Applications

**Physical Characteristics (Overall)****Conductor****AWG:**

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	23	Solid	BC - Bare Copper	0.023

Total Number of Conductors:

1

**Insulation****Insulation Material:**

Insulation Material	Dia. (in.)
Gas-injected FEP - Foam Fluorinated Ethylene Propylene	0.102

**Outer Shield****Outer Shield Material:**

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

**Outer Jacket****Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

**Overall Cable**

Overall Nominal Diameter: 0.159 in.

**Mechanical Characteristics (Overall)**

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 21 lbs/1000 ft.

Max. Recommended Pulling Tension: 40 lbs.

Min. Bend Radius/Minor Axis: 1.500 in.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (RoHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	03/28/2008
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes

CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
RG Type:	Sub-miniature 59/U
<b>Flame Test</b>	
UL Flame Test:	UL910 Steiner Tunnel
CSA Flame Test:	FT6
<b>Suitability</b>	
Suitability - Indoor:	Yes
Suitability - Aerial:	Yes - Black only.
Sunlight Resistance:	No
<b>Plenum/Non-Plenum</b>	
Plenum (Y/N):	Yes
Non-Plenum Number:	1855A

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

75

Nom. Inductance:

Inductance (µH/ft)

0.300

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

16.300

Nominal Velocity of Propagation:

VP (%)

80.000

Nominal Delay:

Delay (ns/ft)

1.22

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

20.100

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

3.700

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.380
3.600	0.760
10.000	1.300
71.500	3.100
135.000	4.100
270.000	5.800
360.000	6.900
540.000	8.700
720.000	10.300
750.000	10.500
1000.000	12.400
1500.000	15.700
2250.000	19.900
3000.000	23.800
4500.000	30.300
6000.000	36.400

Max. Operating Voltage - UL:

Voltage

300 V RMS

Other Electrical Characteristic 1:	TDR Impedance: 75 +/- 3 Ohms
Other Electrical Characteristic 2:	Return Loss: Fixed bridge and termination.

## 1855P Coax - Sub-Miniature Plenum

## Minimum Return Loss:

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
5.000	1600.000	23.000
1600.000	4500.000	21.000
4500.000	6000.000	15.000

## Sweep Test

**Sweep Testing:** 100&#37; Sweep tested 5 MHz to 6 GHz.

## Notes (Overall)

**Notes:** Print legend includes sequential footage marks.

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1855P N3U1000	1,000 FT	22.000 LB	GREEN, MIL		#23 FFEP SH FLRST
1855P 0011000	1,000 FT	22.000 LB	BROWN		#23 FFEP SH FLRST
1855P 0021000	1,000 FT	22.000 LB	RED		#23 FFEP SH FLRST
1855P 0031000	1,000 FT	22.000 LB	ORANGE		#23 FFEP SH FLRST
1855P 0041000	1,000 FT	22.000 LB	YELLOW		#23 FFEP SH FLRST
1855P 0061000	1,000 FT	22.000 LB	BLUE, LIGHT		#23 FFEP SH FLRST
1855P 0071000	1,000 FT	22.000 LB	VIOLET		#23 FFEP SH FLRST
1855P 0081000	1,000 FT	22.000 LB	GRAY		#23 FFEP SH FLRST
1855P 0101000	1,000 EA	22.000 LB	BLACK		#23 FFEP SH FLRST
1855P 8771000	1,000 FT	22.000 LB	NATURAL		#23 FFEP SH FLRST

Revision Number: 4 Revision Date: 04-14-2017

© 2017 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).