
## **Specifications**



## RF EXPLORER® RACKPRO

Spectrum Analyzer + RF Coordination Software



The RF Explorer® RackPRO is a hardware spectrum analysis platform for managing and monitoring any wireless audio system from a laptop or equipment rack. Powerful frequency coordination and interference monitoring is now easy to master and within budget for venues large and small. While most spectrum analyzers offer laboratory precision across wide frequency ranges, the RackPRO is designed with essential features that operate only in the range required for wireless mics and IEMs.

Neverfly blind again with real time, scalable visualizations that illuminate local spectrum at the click of a mouse or push of a button. The RackPRO delivers a real time view of RF activity so you can stay ahead of interference and have confidence in your wireless systems.

Software for the RF Explorer is sold separately to acommodate user preference and different operating systems. For Mac users, Vantage, by RF Venue offers a suite of simple yet powerful tools for spectrum analysis. For Windows users, Clear Waves, from Nuts About Nets, offers clear visualizations as well as useful tools. Both Vantage and Clear Waves edit and export frequency sets compatible with Professional Wireless Systems® IAS, or Shure® Wireless Workbench.

| Electrical                      |                |
|---------------------------------|----------------|
| Operating frequeny              | 240-960 MHz    |
| Impedance (nom)                 | 50Ω            |
| Max input power                 | +5 dBm / 3mW   |
| Modes                           | Peak Max, Max  |
| Hold, Normal Overwrite, Average |                |
| Display                         | LCD            |
| Resolution Bandwidth            | Auto; Max .025 |
| MHz                             |                |
| Dynamic range                   | 115 dBm-0 dBm  |
| Average noise                   | 115 dBm        |
| Supplied antenna                | 1X dipole      |
|                                 |                |

| Physical                                |   |
|---|---|
| Dimensions                              |   |
| Input AC voltage                        | , |
| RF input connector                      | 0                                       |
| Weight                                  | 2.15 kg                                 |
| Mount location                          | 19" rack                                |
| Power connection                        |   |
| PC cable                                |   |
| type B male                             |   |
| Connector(s)                            | BNC female                              |
| System Requirements                     |   |
| OS                                      |   |
| sional, Vista, 7, 8 (32 or 64-bit). Mic | rosoft.NET framework v4.5 or            |
| later: MAC: OS 10.10 or later           |   |
| Min hard disk                           | 300 MB                                  |