

Blade RGBW™

Knife-Edge Optics Make This Blade A Cut Above!

Blizzard Lighting's Blade™ RGBW Moving Head Beam combines blinding output, surgical precision and a razor-sharp 1.1 degree beam to dazzle your audience as it slices through the air!

Packed with 36 5-Watt CREE® Red/Green/Blue/White LEDs and coupled to an all-new, incredible 1.1 degree beam angle optic system, the Blade™ RGBW is an incredible aerial performer packed in a tiny, lightweight package. Plus, thanks to advanced motor technology and innovative design, the Blade™ is the fastest, most accurate moving head we've ever offered... by far!

The Blade™ is a snap to program and easy on the eyes, too, thanks to its full-color LCD-TFT display with icon-based navigation. Plus, the fixture has plenty of extras usually only found on fixtures with a much higher price tag. PowerCON™ compatible power in and out connectors make for secure power connections, user selectable 16-bit dimming, defeatable pan/tilt correction with trim adjustment, auto standby after DMX signal loss and fixture ID addressing are all included!

Finally the Blade™ RGBW easily converts from a dazzling beam fixture to a versatile 8.8-degree soft-edged wash fixture by attaching the included diffuser lens. It's like having two fixtures in one!

So get ready to slice and dice, and pick up your Blade™ RGBW's today!

Control Features

- 36x 5-watt R/G/B/W CREE® LED's
- User selectable 11 or 15 DMX channels
- Razor-sharp 1.1° beam angle + attachable 8° diffuser lens
- 4-button menu with LCD-TFT icon-based display
- Full color mixing in standalone, master/slave and DMX modes
- Built-in automated and sound active programs via master/slave
- User selectable 16-bit dimming
- Defeatable pan/tilt correction with trim adjustment
- Auto standby after DMX signal loss
- Fixture ID addressing
- 3-pin male input and 3-pin female output
- PowerCon™ compatible AC power In/Out connectors

BLADE RGBW™



DISCLAIMER:

The power connector fitted to the fixture and fixture cord are designed for compatibility with products manufactured by Neutrik AG, Neutrik USA and their related entities, however they are not manufactured by, affiliated with or endorsed by Neutrik AG, Neutrik USA, or any related entity. Neutrik® and powerCON® are registered trademarks of Neutrik AG.

Additional Features

- Beam Angle: 1.1° no diffusion filter 8° with diffusion filter
- Lux: 5,400 @ 2.5m
- Light source: 36x 5-watt R/G/B/W CREE® LED's
- powerCON® compatible In and Out power connectors
- Power Consumption: 148W, 1.84A (full white)
- Compact and lightweight
- Input Voltage: AC power: Auto-ranging 90 V ~ 240 V 50/60 Hz
- AC power: AC 120VAC, 60 Hertz

Weight & Dimensions

- Length: 13.4 inches (34 cm)
- Width: 9.5 inches (24 cm)
- Height: 14.8 inches (37.5 cm)
- Weight: 11.5 lbs (5.2 kg)

Warranty

- 2-year limited warranty, does not cover malfunction caused by damage to LED's.

Blade RGBW LUMINOUS INTENSITY

LUX/METER	1 METER WITH DIFFUSER	1 METER WITH-OUT DIFFUSER	2 METERS WITH DIFFUSER	2 METER WITH-OUT DIFFUSER
RED	1,600	9,700	530	6,600
GREEN	2,400	13,900	740	8,070
BLUE	3,400	21,000	1,030	13,520
WHITE	2,680	23,800	1,000	12,870
ALL	10,200	69,000	2,920	41,000

BLADETM RGBW

