

# HP-SWHD-3X1/HP-SWHD-5X1 User manual

V1.1

## I. Introduction

This is a high performance 3 or 5 HDMI input and 1 HDMI output switch. It supports HDCP repeater functions and fast switching between any of the HDMI input ports. The system supports all 3D TV formats in addition to all HDTV formats up to 4Kx2K at 30 Hz. Furthermore, the remote control gives users complete control over the selection of sources and makes the device incredibly user friendly.

## II. Features

1. Compliant with HDMI 1.4a, CTS 1.4a, DVI 1.0 standards.
2. HDMI 1.4 support: 3D TV support.
3. Support 3D Video & 4Kx2K (30 Hz), 8, 10, 12 & 16 bits per color depth.
4. Audio support:
5. Dolby TrueHD
6. DTS-HD Master Audio 7.1CH
7. Low power consumption, does not require an external power supply

## III. Package

1. HDMI 1.4 3 by 1 or 5 by 1 Switcher
2. 5V USB to DC Power Supply cable
3. Remote control
4. IR Receive Extend cable
5. Operation Manual


## IV. Specifications

Frequency Bandwidth	2.97 Gbps
Input Ports	3 or 5 HDMI Female ports, IR Receive port
Output port	1 HDMI Female port
HDMI Audio Output	PCM2, 5.1, 7.1CH, Dolby 5.1, DTS5.1, Dolby TrueHD, DTS-HD
ESD Protection (Human Body Model)	± 8kV (air-gap discharge) ± 4kV (contact discharge)
Dimensions (mm)	87(D) x59.5 (W) x 19(H)
Weight (g)	60
Power Consumption	0.2W
Operating Temperature	0°C ~ 40°C / 32°F ~ 104°F
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Power Consumption	0.5 watts (max)


## V. 3×1 Switch Operation controls and Functions

Face Panel: ① Switch button, press the button will switch the input source;


②③④ Led indicate , Indicates the HDMI input port selected corresponding to the light.



Front Panel: HDMI output port, connect with HDTV or monitor with HDMI cable




Rear Panel: HDMI input port, connect with DVD, PS3, Set-top Box and Note Book with HDMI cable



Right Panel: ① DC 5V input port;


② IR receiver port: connect a IR extend cable and receiver the Remote signal.



## VI. 5×1 Switch Operation controls and Functions


Face Panel: ① Switch button, press the button will switch the input source;

②③④⑤⑥ Led indicate , Indicates the HDMI input port selected corresponding to the light.




Front Panel: ①③ HDMI input port, connect with DVD, PS3, Set-top Box and Note Book with HDMI cable

② HDMI output port, connect with HDTV or monitor with HDMI cable




Rear Panel: HDMI input port, connect with DVD, PS3, Set-top Box and Note Book with HDMI cable




Right Panel: ① DC 5V input port;


② IR receiver port: connect a IR extend cable and receiver the Remote signal.



VII. Application Example (3x1 Switch)



Application Example (5x1 Switch)




## VIII. Remote control

### 3×1 Switch Remote




IN1、IN2、IN3: Press these buttons will force switch the input port and the LED will indicate the corresponding input source.

: Press this button will cycle switch the input source and the LED will indicate the corresponding input source.

### 5×1 Switch Remote



IN1、IN2、IN3、IN4、IN5: Press these buttons will force switch the input port and the LED will indicate the corresponding input source.

: Press this button will cycle switch the input source and the LED will indicate the corresponding input source.