

Model Name	SE-650
Product Name	HD 4-Channel Digital Video Switcher
Video Inputs	2x HDMI, 2x HD-SDI
Video Outputs	2x HDMI (1 is MV, 1 is Assignable) 1x HD-SDI (Assignable)
Audio Inputs	2x RCA Analogue (L/R) 2x Mono Microphone, De-embedded Digital Audio (2 CH)
Audio Outputs	2x RCA Analogue (L/R) 1x Stereo headphone (Mini Jack with volume control) Embedded Digital Audio (2 CH / Channel 1 & 2)
Tally	Yes, D-Sub -15 Male connector
Software Update	USB Port
Audio Mixer	
Audio Fader	5 VR, 6 CH (3 Pair) Audio Mixer
Audio LED Meter	2 Rows (Left / Right)
Standards	
Supported Resolution	1080i/50, 1080i/59.94, 1080i/60, 720p/50, 720p/59.94, 720p/60
Internal Processing	YUV 4:2:2, 10-bit
Extras	
Keyers	2 Keyers (2 Chroma Keyers), Linear as well as Luma Keying is supported
Upstream Keyers	2 (M/E Keyer & PIP)
Chroma Keyers	2 High Quality ChromaKeyers, available on Keyer & PIP
PIP	1x Full PIP, full size, position, crop control. Border with variable size & color
Wipe	32 Wipe Patterns including Circle, Heart. Full Softness control. Variable width Border with softness
Stills	Any unused channel can also be used as a still buffer, can store stills internally.
Stinger Transitions	Yes

Logo	1
Operating Temperature	0°C to 50°C (32°F to 122°F)
Humidity	10% to 80%
Power Consumption	12V / 29W
Dimension (mm)	400 x 264 x 72
Weight	1.72 Kg