



LED-1562HD

15" LED-backlit LCD monitor has optimal picture quality with native Full HD resolution (1920 x 1080). This latest generation model is ideal for any small screen, high quality video installations.

Benefits

- Displays native Full HD signals (1080i/p) with no downscaling
- LED backlight: brighter picture using less power
- Widescreen (16:9) native aspect ratio
- Multiple connections including HDMI, Composite and VGA
- Built-in removable desk stand
- Built-in speakers

Related Products

- LED-1562HDL: Flush-mount version of LED-1562HD
- LED-1562HDR: Rack-mount version of LED-1562HD
- LED-1562HDLX: Flush-mount version of LED-1562HD with no front controls

| Specifications | |
|--------------------------|---|
| Mount | VESA 75 x 75mm; Removable Deskstand |
| HD Compatible | Yes |
| Anti Glare Coating | Yes |
| Case | Durable Metal |
| IR Remote Control | Yes |
| Native Aspect Ratio | 16:9 |
| Visible Screen Size (WH) | 13.6" x 7.6" / 345 x 195mm |
| Resolution | 1920(H) x 1080(V) (Full HD) |
| Brightness Rating | 300 cd/m ² (Nit) |
| Contrast Ratio | 600:1 |
| Back Light | LED (30K) |
| PC Compatibility | Yes |
| Dot Pitch | 0.17925(H) x 0.17925(V)mm |
| Color Depth | 6-bit, 262K |
| Number of Pixels | 2,073,600 |
| Response Time | 8ms (Rising/Falling) |
| Audio Power / Speakers | 8 Ohm, 2 Speakers x 5 Watts |
| Viewing Angle (L/R/T/B) | 70/70/60/60 degrees |
| Digital Signal Processor | 3D Comb Filter |
| HDMI | x2 Inputs |
| Composite | x1 BNC Input; x1 BNC Output |
| VGA | x1 15-pin mini D-sub Input |
| RS-232 | x1 Input |
| Audio | x1 RCA L/R Input; x1 3.5mm PC Input |
| Power | x1 2.1mm DC Input |
| Power Requirements | Regulated 12VDC; 3A; Negative Ground |
| Power Consumption | 8 Watts (Max) |
| Operating Temp | 32 ~ 104°F / 0 ~ 40°C |
| Humidity | 10% ~ 90% |
| Dimensions w/ Deskstand | 14.25" x 10.78" x 5.5"; 362 x 275 x 140mm |
| Dimensions | 14.25" x 10.5" x 1.85"; 362 x 267 x 47mm |
| Weight | Net: 4.85 lbs / 2.2 kg |

Specifications subject to change.