
# **Bright XGA projection**

X365




# Wireless presentation and multimedia














Minimal maintenance with an amazing 10,000 hour

















Project bright 3,600 lumens images in small-to-medium classrooms, training rooms and multi-purpose offices with the Optoma X365 XGA (1024x768) projector. Its small footprint, 22,000:1 contrast ratio and sRGB color profile support produces sharp and vivid images with accurate color reproduction perfect for sharing presentations in illuminated rooms.

The integrated PC-free file and image viewer provides direct viewing of office documents, PDFs, images and presentations from any USB storage device - simply plug it into the Optoma X365. USB display mode makes mirroring Android and iOS devices by connecting a USB cable while network display enables up to four PCs to connect simultaneously to the projector via wired networking for greater screen sharing flexibility.

A 15 watt internal speaker fills the room with immersive audio that elevates media content and presentations projected with the Optoma X365. A robust arsenal of inputs including 2 HDMI (one with MHL), VGA-in, VGAout, composite video and RJ-45 enables connectivity to a wide range of devices including PC, Mac, Blu-ray players and various set-top box media players. A 10,000-hour lamp life enables many years of use with minimal maintenance.

# **CONNECTIVITY** (May require optional accessories)



Computers **Phones** 



\_ \_ \_ \_ \_ \_ \_ \_ \_ 3 99-49 3D Blu-ray/DVD Players







Camcorders

Apple TV®

Chromecast™

## **Bright XGA projection - X365**

## **OPTICAL/TECHNICAL SPECIFICATIONS**

Display Technology	Single 0.55" DMD S450, DC3 chip, DLP® Technology Texas Instruments
Color Wheel	RYGCWB
Native Resolution	XGA (1024x768)
Maximum Resolution	UXGA (1600x1200)
Brightness	3600 ANSI lumens
Contrast Ratio	22,000:1
Displayable Colors	1.07 billion
Lamp Life and Type*	10,000/6000/5000 (Dynamic/ECO/Bright) - 195W
Projection Method	Front, rear, ceiling mount, table top
Keystone Correction	$\pm20^{\circ}$ vertical / $\pm20^{\circ}$ horizontal with four corner and auto keystone
Keystone Distortion	±0.5% max
Uniformity	80%
Offset	115% (%±5%)
Aspect Ratio	4:3 (native), 16:9 compatible
Throw Ratio	1.95 - 2.15 (±5%)
Projection Distance	3.93' - 43.35' (no zoom)
Image Size	27.34" - 304.5"
Projection Lens	F=2.41 ~2.53, f=21.85 ~ 24.01mm manual
Optical Zoom	1.1x
Digital Zoom	0.8 - 2.0
Audio	15W
Noise Level	29dB/31dB (ECO/Bright)
Remote Control	Full size remote
Operating Temperature	41–104°F (5–40°C), 85% max humidity
Power Supply	AC input 100 - 240V, 50 - 60 Hz, auto-switching
Power Consumption	267W typical (Bright mode), 294W max (Bright mode), 207W typical (Eco+ mode), 228W max (Eco+ mode)
High Altitude	Operating temp @ sea level up to 10000 feet = 23F (max); must manually switch to high altitude mode @ 3600 feet & above (using OSD)

#### COMPATIBILITY SPECIFICATIONS

COMPATIBILITY SPECIFICATIONS		
Wireless Screen Mirror	Screen mirroring for PC, Mac, and Android using HDCast Pro app (requires optional Wi-Fi adapter)	
USB Display	Screen mirroring of Android and iOS device using Lightning or USB cable	
PC Free USB Media Player and Office Document Viewer	Supports viewing of office documents, PDFs and images via USB storage devices	
PC Free USB Media Player Image formats	JPEG, GIF, BMP	
PC Free Office Document and PDF Viewer formats	Word documents (.doc, .docx), Excel spreadsheets (.xls, .xlsx), PowerPoint presentations (.ppt, .pptx), Adobe Acrobat files (.pdf)	
Computer Compatibility	FHD, HD, XGA, UXGA, SXGA, XGA, SVGA, VGA, Mac	
Video Input Compatibility	PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p)	
3D Compatibility <sup>†</sup>	Side-by-side:1080i50 / 60, 720p50 / 60 Frame-pack: XGA24, 720p50 / 60 Over-under: XGA24, 720p50 / 60	
Vertical Scan Rate	15 - 91kHz	
Horizontal Scan Rate	25 - 85Hz (120Hz for 3D)	
User Controls	Complete on-screen menu adjustment in 26 languages	
I/O Connection Ports	2xHDMI (with MHL), VGA-in, VGA-out, composite video, audio-in (3.5mm), audio-out (3.5mm), RJ-45, 1x USB (for optional Wi-Fi adapter), 1x USB (USB reader and USB power), USB-B mini (service), 12V trigger (3.5mm), RS-232C	
Loop Through (Audio)	Yes	

## PHYSICAL SPECIFICATIONS

Security	Security bar, Kensington lock, password protection
Weight	5.51 lbs.
Dimensions (W x H x D)	11.73" x 9.05" x 3.79"

#### Warranty

3-year Optoma Express Service, 1-year on lamp

#### What's in the Box

X365 projector, AC power cord, remote control, carrying case, batteries for remote, multilingual CD-ROM user's manual, quick start card, and warranty card

## **Optional Accessories**

Universal ceiling mount, DLP®Link™ 3D glasses, WUSB (Wi-Fi adapter for HDCast Profeatures), lamp, remote

#### **Accessory Part Numbers**

Lamp: BL-FP195C Remote: BR5011L

DLP® Link™ 3D glasses: ZD302

Wireless 802.11: WUSB (required for HDCast Pro features)

Universal ceiling mount: OCM818W-RU

Universal ceiling mount: BM-5001U

Universal ceiling mount (with extensional pole): OCM815W Single-Cat6 HDBaseT kit: EVBMN-M110

Single-Cat6 HDBaseT kit: EVBMN-M11 Carrying case: SP.8VH03GC01

UPC 796435 44 191 3





Full 3D Hann DLP 1. HDMI1-In 5. VGA-Out/YPbPr 9. RS-232C 2. HDMI2-In (MHL) 6. RJ-45 10. Audio-Out 3. Video 7. Audio-In 11. AC Power 4.VGA-In/YPbPr 8.USB 12. Kensington™ Lock Power On Switch Freeze 🔯 Mute Freeze **Four Directional ■** Enter Select Keys Enter Laser Page + Page -Keystone Volume Menu 3D VGA ( Video HDMI User 3 User 1 • Resync Source • User 2 **Brightness** 

<sup>\*</sup>Light source life is dependent upon many factors, including brightness mode, display mode, usage, environmental conditions and more. Light source brightness can decrease over time.