

**ASSEMBLY INSTRUCTIONS
FOR LS7805B
CRANK-UP LIGHTING STAND**

PREPARATION

Remove the following components from the box and packaging. Identify all of the parts and quantities listed below:

- 1 Top horizontal bar w/plastic T in center
- 2 Complete Side Bar Assemblies
- 1 Assembled Crank-Up Lighting Stand

ASSEMBLING

1. Loosen the leg housing knob and push down on the leg housing allowing the legs to spread open to approx. 4' and tighten leg housing knob.
2. Loosen the upper clutch knob and raise the top vertical shaft up to the 1st or 2nd security pin location, insert security pin attached to upper clutch, let pin rest on clutch, and tighten upper clutch knob.

Loosen all thumb knobs on the side bars and top bar before proceeding.

3. Slide the small plastic collar of one of the side bars down the top vertical shaft making sure the pin at the top of the vertical shaft is lined up with the gap in the plastic collar to allow the collar to pass the pin. NOTE: This will need to be done with the rest of the plastic collars and T-clamps.
4. Slide the small plastic collar of the other side bar down the top vertical shaft.
5. Slide the T-clamp from the 1st side bar down the top vertical shaft.
6. Slide the T-clamp from the 2nd side bar down the top vertical shaft.
7. Slide the T-clamp of the top horizontal bar on top of the top vertical shaft.
8. Position and secure the side bars and top T bar before mounting ANY lighting.

DO NOT raise any vertical shaft of this stand pass its maximum or this may cause damage to the stand, equipment or cause serious injury.

Make sure you check that all knobs are tightened, safety pins are in place, and all lighting are equally placed and securely mounted on the stand or this may cause damage to the stand, equipment or cause serious injury.