

## Technical Specifications TL-10GSFPP-SM10K

### Features at a Glance

- Hot-pluggable SFP+ footprint
- Supports 9.95 to 10.5Gb/s bit rates
- Power dissipation < 1W
- RoHS-6 compliant (lead-free)
- Commercial temperature range 0 to 70°C
- Single 3.3V power supply
- Maximum link length of 10km
- Uncooled 1310nm DFB laser Receiver limiting electrical interface
- Duplex LC connector
- Built-in digital diagnostic functions



The TL-10GSFPP-SM10K transceivers are designed for use in 10-Gigabit Ethernet links up to 10km over Single Mode fiber. They are compliant with SFF-8431, SFF-8432 and IEEE 802.3ae 10GBASE-LR/LW, and 10G Fibre Channel 1200-SM-LL-L Digital diagnostics functions are available via a 2-wire serial interface.

The transceiver is a “limiting module”, i.e., it employs a limiting receiver. Host board designers using an EDC PHY IC should follow the IC manufacturer’s recommended settings for interoperating the host-board EDC PHY with a limiting receiver SFP+ module. The optical transceiver is compliant per the RoHS Directive 2011/65/EU.

Basic Specifications	
Form Type	SFP+
Max Data Rate	10.3125Gbps
Wavelength	1310nm
Max Cable Distance*	10km
Interface	LC duplex
Optical Components	DFB 1310nm
Cable Type	SMF
DOM Support	Yes
TX Power	-8.2~0.5dBm
Receiver Sensitivity	< -14.4dBm
Commercial Temperature Range	0 to 70°C (32 to 158°F)

## Specifications

<b>General Product Characteristics</b>					
Parameter	Symbol	Min	Typ.	Max	Unit
Bit Rate	BR	9.95		10.5	Gbps
Bit Error Ratio	BER			$10^{-12}$	
Max. Supported Link Length	$L_{MAX}$			10	km
<b>Absolute Maximum Ratings</b>					
Parameter	Symbol	Min	Typ.	Max	Unit
Storage Temperature	$T_S$	-40		85	°C
Case Operating Temperature	$T_{OP}$	0		70	°C
Supply Voltage	$V_{CC}$	-0.5		4.0	V
Operating Relative Humidity	RH	0		85	%
Receiver Optical Damage Threshold	RxDamage	5			dBm
<b>Electrical Characteristics (TOP = 0 to 70°C, <math>V_{CC}</math> = 3.14 to 3.46 V)</b>					
Parameter	Symbol	Min	Typ.	Max	Unit
Power Supply Voltage	$V_{CC}$	3.14	3.30	3.46	V
Power Supply Current	$I_{CC}$		200	285	Ma
<b>Transmitter</b>					
Parameter	Symbol	Min	Typ.	Max	Unit
Input Differential Impedance	$R_{in}$		100	120	$\Omega$
Differential Data Input Swing	$V_{in,pp}$	180		850	mV
Transmit Disable Voltage	$V_D$	2		$V_{CC}$	V
Transmit Enable Voltage	$V_{EN}$	$V_{ee}$		0.8	V
<b>Receiver</b>					
Parameter	Symbol	Min	Typ.	Max	Unit
Differential Data Output Swing	$V_{out,pp}$	300		850	mV
Output Rise Time and Fall Time	$t_r$	28			ps
LOS Normal	$V_{LOS\ norm}$	$V_{ee}$		0.8	V
LOS Fault	$V_{LOS\ fault}$	2		$V_{CC}$	V
Power Supply Noise Tolerance	$V_{CC}/V_{CCR}$	Per SFF-8431 Rev 4.1			mV <sub>DD</sub>
<b>Optical Characteristics (TOP = 0 to 70°C, <math>V_{CC}</math> = 3.14 to 3.46 V)</b>					
<b>Transmitter</b>					
Parameter	Symbol	Min	Typ.	Max	Unit
Optical Modulation Amplitude	$P_{OMA}$	-5.2			dBm
Average Launch Power	$P_{AVE}$	-8.2		+0.5	dBm
Optical Wavelength	$\lambda$	1260		1355	nm
Side-Mode Suppression Ration	SMSR	30			dB
Optical Extinction Ratio	ER	3.5			dB
Transmitter and Dispersion Penalty	TDP			3.2	dB
Average Launch Power of OFF Transmitter	$P_{OFF}$			-30	dBm
Tx Jitter	$TX_j$	Per IEEE 802.3ae requirements			
Encircled Flux	<4.5 $\mu$ m <19 $\mu$ m	86		30	%
Relative Intensity Noise	$RIN_{12}OMA$			-128	dB/Hz
<b>Receiver</b>					
Parameter	Symbol	Min	Typ.	Max	Unit
Receiver Sensitivity (OMA) @ 10.3 Gbps	$R_{SENS1}$			-12.6	dBm
Stressed Receiver Sensitivity (OMA) @ 10.3 Gbps	$R_{SENS2}$			-10.3	dBm
Average Receive Power	$P_{AVE}$	-4.2		+0.5	dBm
Wavelength Range	$\lambda_C$	1260		1600	nm
Receiver Reflectance	$R_{RX}$			-12	dB
LOS De-Assert	$LOS_D$			-17	dBm
LOS Assert	$LOS_A$	-30			dBm
LOS Hysteresis		0.5			dB

## Dimensional Drawings

