# LC-2A

2-Channel Simultaneous 7.2V / 7.4V Li-ion battery charger for Canon, Panasonic, and Sony

## **PRO**Series

### **Product Description**

Designed with interchangeable battery interface plates, the LC-2A can simultaneously charge a range of popular 7.2V/7.4V Canon, Panasonic, and Sony Li-ion batteries. The charger includes 10 interface plates, 2 for each type, which are labeled for easy identification. Users can mix the interface plates and simultaneously charge two types of batteries. The charger has built-in LED indicators to notify users when their batteries are charging, fully charged, and if a battery or charger fault has occurred.

#### Features

- Charges Li-ion Canon, Panasonic, & Sony batteries
- 10 Interchangeable plates (2 for each interface)
- Simultaneous quick charge
- Auto safety protection
- Auto power-down if inactive for 1h
- Charger status LED indicators
- Universal AC input for world-wide use
- Light-weight and portable
- 2 Year warranty

#### Compatible Batteries (as of September 2015)

| Adaptor Type  | Interface Label | Compatible Batteries           |
|---------------|-----------------|--------------------------------|
| Panasonic     | PS              | IDX: SSL-VBG50                 |
| (Secured)     | P3              | Panasonic: VW-VBG6, VW, VBG260 |
| Panasonic     | P               | IDX: SL-VBD50                  |
| (Non-secured) | F               | Panasonic: VW-VBD55, VW-VBD58  |
| Canon         | С               | Canon: BP-955, BP-975          |
|               | CE              | Canon: BLP-E6                  |
| Sony          | S               | Sony: L Series                 |

IDX reserves the right to change the specifications contained herein without notice.



IDX System Technology, Inc. 19001 Harborgate Way, Suite 105 Torrance, CA 90501 USA T: (310) 328-2850 F: (310) 328-8202 E: idx.usa@idx.tv

#### **Technical Specifications**

Charge Current: 1.9A

Charge Method: Constant amperage / constant voltage

Input Voltage: AC-adaptor: 100-240V, 60/50Hz automatic DC Input: 12-19V (36W max)

**Protection:** Low Voltage charging, quick charging

**Dimensions:** 4.92 (W) x 1.57 (H) x 4.37 (D) inches

Weight: 0.42 lbs

**Standard Accessories:** Panasonic type (PS x2, P x2) Canon type (C x2, CE x2) Sony type (S x2)