

IN3144

Professional 3D Network Projector

Part #: IN3144

InFocus

The high-brightness, high-connectivity IN3144 projector brings superior performance to your meeting room or classroom at a price that fits your budget. Easily manage the IN3144 over your network and easily install it with AMX and Crestron room control systems.

Key Features

- ◆ XGA (1024 x 768) native resolution
- ◆ 5000 lumens
- ◆ 3D support for Blu-ray and more
- ◆ 10W speaker
- ◆ Two 1.4 HDMI, VGA and more
- ◆ Network Monitoring



High Connectivity

The IN3144 is loaded with connectivity options, including two HDMI ports and multiple audio ports. Project from PCs, Macs, video sources, tablets and smartphones.



Impressive Image Quality

With 5000 lumens, high contrast, six-segment color wheel, and BrilliantColor™ DLP imaging, the IN3144 projects big, bright,

colorful images with the lights on and the blinds open. The 1.5:1 zoom ratio and extensive throw ratio mean these projectors work in a wide variety of rooms.

Immersive 3D

The IN3144 incorporates 3D Triple Flash technology and supports multiple forms of 3D, including HDMI, Blu-Ray, 3D broadcasting, video games and NVIDIA 3DTV PC connectivity. Display 3D in 1080p full HD over HDMI. Compatible with [144Hz DLP Link™ 3D glasses](#).

Network Support and Digital Control

Remotely manage and support your projector from a single computer via your existing network with [free ProjectorNet 4.0 software](#) from InFocus. Crestron Roomview enables instant, intuitive operation without a control processor or custom programming. AMX Device Discovery lets an AMX controller detect the projector dynamically and configure it for the remote control.

Specifications*

Projector		IN3144
Resolution – Native	XGA (1024 x 768)	
Display Technology	DLP	
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
Speakers	Mono 10W x 1	
Lamp Brightness	5,000 lumens	
Lamp Brightness – Eco Mode	4,000 lumens	
Lamp Life	3,500 hours	
Lamp Life – Low Power	4,500 hours	
Lamp Life – Dynamic Mode	6,000 hours	
Lamp Power	310W	
Lamp Power – Low Power	245W	
Lamp Power – Dynamic Mode	93W	
Replacement Lamp	SP-LAMP-098	
Contrast Ratio	16,000:1	
Color Wheel	6 Segment	
Number of Colors	16.7 million	
Synch Scan Frequency – Horizontal	15 - 91.4 KHz	
Synch Scan Frequency – Vertical	24 - 30 KHz	
Aspect Ratio	4:3	
Aspect Ratio Compatibility	16:9, 16:10, 2.35:1	
Projection Distance – Minimum	1 m	
Projection Distance – Maximum	10 m	
Projection Lens F-Stop – Minimum	2.42	
Projection Lens F-Stop – Maximum	2.97	
Lens Type	Manual zoom and focus	
Image Size – Minimum	22 in	
Image Size – Maximum	270 in	
Projection Offset	14%	
Keystone Correction	+/- 40°	
Connectors – Inputs	3.5mm microphone line in, 3.5mm mono audio, HDMI x2, Composite video, S-video, VGA x2, RCA L/R audio, USB mini (for service)	
Connectors – Outputs	3.5mm audio output, VGA, USB-A 5V1.5A, 3.5mm 12V Screen trigger	
Control	RS232, RJ-45 (Ethernet)	
Audible Noise	< 32 dBA at 0°F / -17.8°C	
Audible Noise – Eco Mode	< 30 dBA at 0°F / -17.8°C	
Included Accessories	Power cord, Remote, VGA cable, Documentation, Quick Start Guide, User Manual (CD)	
Product Warranty	2 years	
Lamp Warranty	6 months	
Accessories Warranty	90 days	
Power Consumption	410.0W max	
Power Consumption – Eco Mode	320.0W max	
Power Consumption – Dynamic Mode	93.0W max	
Power Standard	AC 100 to 240V, 50/60	
Operating Conditions	41 to 104°F at 2500 to 10000 ft / 5 to 40°C at 762 to 3048 m	
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Hungarian	
Throw and Zoom		
Throw Ratio – Minimum	1.83:1	
Throw Ratio – Maximum	2.75:1	
Zoom Ratio	1.5:1	
Shipping		
Product Dimensions	5 x 12.4 x 8.5 in / 127 x 315 x 215.9 mm	

Projector	IN3144
Product Weight	6.9 lbs / 3.1 kg
Shipping Dimensions	8.2 x 15.4 x 14.5 in / 208.3 x 391.2 x 368.3 mm
Shipping Weight	10.3 lbs / 4.7 kg

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

- 1 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM1)
- Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
- Projector Lamp for IN3144, IN3146, IN3148HD (SP-LAMP-098)
- LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
- Motorized Electric Projector Screen: 100 in., 4:3 (SC-MOT-100)
- Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4)
- Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4)
- Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB)
- Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW)
- Motorized Electric Projector Screen: 84 in., 4:3 (SC-MOT-84)
- Motorized Electric Projector Screen: 120 in., 4:3 (SC-MOT-120)
- Manual Pull Down Projector Screen: 84 in., 4:3 (SC-MAN-84)
- Manual Pull Down Projector Screen: 100 in., 4:3 (SC-MAN-100)
- Manual Pull Down Projector Screen: 120 in., 4:3 (SC-MAN-120)
- Manual Pull Up Projector Screen: 80 in., 4:3 (SC-PU-80)
- Manual Pull Up Projector Screen: 100 in., 4:3 (SC-PU-100)
- Fixed Frame Projector Screen: 84 in., 4:3 (SC-FF-84)
- Fixed Frame Projector Screen: 100 in., 4:3 (SC-FF-100)
- Fixed Frame Projector Screen: 120 in., 4:3 (SC-FF-120)
- Projector Lock by PC Guardian (SEC-LOCK-01)
- DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)
- 2 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM2)