# INF7530eAG

The most education-friendly JTouch ever

Part #: INF7530eAG



With 4K resolution, Total Touch Control, built-in education features, and the ability to natively run Android apps, the INF7530eAG is an all-in-one teaching, collaboration, and presentation solution.

## **Key Features**

- Friendly, easy-for-anyone interface with Total Touch Control
  - no need for a remote
- Built-in whiteboard, browser, media player, and AirPlay capability
- Annotate over any application, video input, website, or document
- Brilliant 75-inch, 4K resolution anti-glare screen
- Add any Android app
- Customize your whiteboard background



# Open Android Platform

Expand and customize your platform with any Android application or game. Simply download and install as you would on your phone.

#### Four Critical Applications

All JTouch Plus models include the four critical applications needed for interactive touch panels. These include Casting, Whiteboarding, Browsing, and File Viewing. Create on a full-featured digital whiteboard, present videos and photos, browse the web, easily connect and share content from your Apple, Windows, or Android devices with wireless casting.

## **Intuitive Touch**

Erase, zoom, and pull up menu options quickly and easily with incredibly intuitive touch gestures on the JTouch Plus. Use one finger to draw, two fingers to move, and three fingers to erase on the whiteboard or when annotating on any screen. A simple swipe gesture on either side of the screen reveals a full menu of further options.

# Interactive Digital Whiteboard

Draw, write, and capture notes on a fully customizable, built-in digital whiteboard. Choose any background on a multi-screen canvas with room for free-form drawings, diagrams, and more. Draw using your finger or one of the provided styli using a complete collection of digital pens, highlighters, shapes, lines, and colors.

### Multi-input Touch Monitor

Plug up to eight devices into your INF7530eAG monitor. HDMI-based sources can also connect via five separate USB-B ports to access the panel's touch control. Front access IO ports make it convenient to connect, view, and touch control any user's PC temporarily with both HDMI and Touch USB.

#### Watch the Video

#### **Optional PC**

# Specifications\*

Diagonal Size         75°           Resolution - Native         4K UHD (3840 x 2160)           Display Technology         Direct-LED backlight           Touch Screen Features         Multi-touch, Anti-glare           Glass Strength         4mm thick, heat treated           Scratch Resistance         7 Mohs           Contrast Ratio         1,200:1           Display Brightness         350 cd/m²           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176°           Speakers         Stereo 10W x 2           RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 [Ethernet], VGA, USB 3.0 x, 2, well and USB (Android), PC Audio In (stereo, VGA Audio source), I/8° Microphone (Mono linked to OPS), USB 2.0           Display Connectors - Outputs         3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm sheen audio, PC Audio In (stereo, VGA Audio source), I/8° Microphone (Mono linked to OPS), USB 2.0           Display Connectors - Outputs         Ac 100 to 240V, 50/60           PC         PC           PC         PC           PC         PC           PC         PC           PC         PC           PC         PC         <	Display	INF7530eAG
Resolution — Native         4K UHD (3840 x 2160)           Display Technology         Direct-LED backlight           Touch Screen Features         Multi-touch, Anti-glare           Glass Strength         4mm thick, heat treated           Scratch Resistance         7 Mohs           Contrast Ratio         1,200:1           Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8,0 ms           Pixel Pitch         0,429 mm           Viewing Angle         176'           Speakers         Stree 10W x 2           ReA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8' Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2           Display Connectors - Inputs         35.mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone           Power Standard         AC 100 to 240V, 50/B0           PC         C           PC Hardware         OPS Bay           System         VICE AGAINST AND		
Display Technology         Direct-LED backlight           Touch Screen Features         Multi-touch, Anti-glare           Glass Strength         4mm thick, heat treated           Scratch Resistance         7 Mohs           Contrast Ratio         1,200-1           Display Brightness         350 cd/m2           Refresh Rate         104 2           Response Time         8.0 ms           Pixel Pitch         0,429 mm           Viewing Angle         176*           Speakers         Stereo 10W x 2           RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB, (Android), PC Audio In (stereo, VGA Audio source), V3* Microphone (Mono linked to OPS), USB 2.0           Display Connectors – Inputs         3.5mm stereo audio, RS232, EMDM, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone           Power Standard         AC 100 to 240V, 50/60           PC         V           PC Hardware         OPS Bay           System         V           Included Accessories         Nower cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77F / 25°C	<u> </u>	• •
Touch Screen Features         Multi-touch, Anti-glare           Glass Strength         4mm thick, heat treated           Contrast Ratio         1,200:1           Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         80 ms           Pixel Pitch         0,429 mm           Viewing Angle         175°           Speakers         Stereo 10W x 2           Display Connectors – Inputs         RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Rdcia USB (Android), PC Audio In (stereo, VGA Audio source), I/8° Microphone (Mono linked to 0PS), USB 2.0 x2, OPS PC USB x2           Display Connectors – Outputs         3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm headphone           Power Standard         AC 100 to 240V, 50/60           PC         V           PC Hardware         OPS Bay           System         V           Pickladded Accessories         V ower cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Audible Noise         4 00 dBA at 77F / 25°C           Operating Conditions         2 to 104°F at 10 to 100000 ff / 10 to 4000 dBA m           Mounting Pattern         V ESA 400×600mm wi		
Glass Strength         4mm thick, heat treated           Scratch Resistance         7 Mohs           Contrast Ratio         1,200:1           Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176*           Speakers         Stereo 10W x 2           Display Connectors – Inputs         RCA stere audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x 2, Media USB (Android), PC Audio in (stereo, VGA Audio source), V8* Microphone (Mono linked to OPS), USB 2.0 x 2, OPS PC USB x 2           Display Connectors – Outputs         RCA stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone           Power Standard         410 to 2 400 v, 50/60           PC         VERY           PC Hardware         OPS Bay           System         Viewel Add Accessories         Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Audible Noise         40 dBA at 777F / 25°C           Operating Conditions         32 to 104°F at 0 to 100000 ft/ 0 cat 0 to 3048 m           Mounting Pattern         VESA 400×600mm with M8 screws           Product W	. , 0,	
Scratch Resistance         7 Mohs           Contrast Ratio         1,200:1           Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0,429 mm           Viewing Angle         176*           Speakers         Stereo 10W x 2           Bisplay Connectors – Inputs         RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB, Android), PC Audio in (stereo, VGA Audio source), V8* Microphone (Mono linked to OPS), USB 2.0 x2, CPS PC USB x2.2           Display Connectors – Outputs         3.5mm stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone           Power Standard         AC 100 to 240V, 50/60           PC Hardware         OPS Bay           System           Uncluded Accessories         Wireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77F / 25°C		
Contrast Ratio         1,200:1           Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0,429 mm           Viewing Angle         176°           Speakers         Stereo 10W x 2           Display Connectors – Inputs         RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, X2, OPS PC USB x2           Display Connectors – Outputs         3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone           Power Standard         AC 100 to 240V, 50/60           PC         V           PC Clardware         OPS Bay           System         V           Vireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77F / 25°C	9	
Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176¹           Speakers         Stereo 10W x 2           RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to 0PS), USB 2.0 x2, 0PS PC USB x2           Display Connectors − Outputs         3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone           Power Standard         AC 100 to 240V, 50/60           PC         V           PC Hardware         OPS Bay           System         V           Included Accessories         Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77F / 25°C		
Refesh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176*           Speakers         Stereo 10W x 2           RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8* Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2           Display Connectors – Outputs         3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone           Power Standard         AC 100 to 240V, 50/60           PC           PC Hardware           PO FB By           System           Urcluded Accessories         Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77F / 25°C		
Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176°           Speakers         Stereo 10W x 2           RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8° Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2           Display Connectors – Outputs         3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone           Power Standard         AC 100 to 240V, 50/60           PC Hardware         OPS Bay           System           Included Accessories         Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77°F / 25°C	. , .	
Pixel Pitch 0.429 mm  Viewing Angle 176°  Speakers Stereo 10W x 2  RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2  Display Connectors – Outputs 3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone  Power Standard AC 100 to 240V, 50/60  PC  PC Hardware OPS Bay  System  Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter  Wireless Collaboration Casting embedded  Audible Noise 40 dBA at 77°F / 25°C  Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m  Mounting Pattern VESA 400×600mw with M8 screws  Product Warranty 2 years  Product Warranty 2 years  Product Weight 39 lbs / 63 kg  Shipping Dimensions 450 servers and some size in 165 or 1988.8 x 350.5 mm	Refresh Rate	120 Hz
Viewing Angle     176°       Speakers     Stereo 10W x 2       Display Connectors – Inputs     RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x 2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x 2, OPS PC USB x 2       Display Connectors – Outputs     3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone       Power Standard     AC 100 to 240V, 50/60       PC       PC Hardware       OPS Bay       System       Included Accessories     Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter       Wireless Collaboration     Casting embedded       Audible Noise     < 40 dBA at 77°F / 25°C	Response Time	8.0 ms
SpeakersStereo 10W x 2Display Connectors – InputsRCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2Display Connectors – Outputs3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm HeadphonePower StandardAC 100 to 240V, 50/60PCPC HardwareOPS BaySystemIncluded AccessoriesPower cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi AdapterWireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77F / 25°C	Pixel Pitch	0.429 mm
RCA stereo audio, RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2  Display Connectors – Outputs 3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone  Power Standard AC 100 to 240V, 50/60  PC  PC Hardware OPS Bay  System  Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter  Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77"F / 25"C  Operating Conditions 32 to 104"F at 0 to 10000 ft / 0 to 40"C at 0 to 3048 m  Mounting Pattern VESA 400×600mm with M8 screws  Product Warranty 2 years  Product Dimensions 41.6 x 68.4 x 4.4 in / 1056.6 x 1737.4 x 111.8 mm  Product Weight 139 lbs / 63 kg  Shipping Dimensions 45.9 x 78.3 x 13.8 in / 1165.9 x 1988.8 x 350.5 mm	Viewing Angle	176°
Display Connectors – Inputs  Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8* Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2  3.5mm stereo audio, RCA stereo audio, RS232, HDMI, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone  Power Standard  AC 100 to 240V, 50/60  PC  PC Hardware  OPS Bay  System  Included Accessories  Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter  Casting embedded  Audible Noise  40 dBA at 77*F / 25°C  Operating Conditions  Out of 40°C at 0 to 3048 m  Mounting Pattern  VESA 400×600mm with M8 screws  Product Warranty  2 years  Product Dimensions  41.6 x 68.4 x 4.4 in / 105.6 x 1737.4 x 111.8 mm  Product Weight  Shipping Dimensions  Action Sala in / 1165.9 x 1988.8 x 350.5 mm	Speakers	Stereo 10W x 2
Display Connectors – Outputs         Headphone           Power Standard         AC 100 to 240V, 50/60           PC           PC Hardware         OPS Bay           System         Included Accessories         Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77°F / 25°C           Operating Conditions         32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m           Mounting Pattern         VESA 400×600mm with M8 screws           Product Warranty         2 years           Product Dimensions         41.6 x 68.4 x 4.4 in / 1056.6 x 1737.4 x 111.8 mm           Product Weight         139 lbs / 63 kg           Shipping Dimensions         45.9 x 78.3 x 13.8 in / 1165.9 x 1988.8 x 350.5 mm	Display Connectors – Inputs	Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0
PC Hardware OPS Bay  System  Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years  Product Dimensions 41.6 × 68.4 × 4.4 in / 1056.6 × 1737.4 × 111.8 mm  Product Weight 139 lbs / 63 kg  Shipping Dimensions 45.9 × 78.3 × 13.8 in / 1165.9 × 1988.8 × 350.5 mm	Display Connectors – Outputs	
PC Hardware OPS Bay  System  Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C  Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m  Mounting Pattern VESA 400×600mm with M8 screws  Product Warranty 2 years  Product Dimensions 41.6 x 68.4 x 4.4 in / 1056.6 x 1737.4 x 111.8 mm  Product Weight 139 lbs / 63 kg  Shipping Dimensions 45.9 x 78.3 x 13.8 in / 1165.9 x 1988.8 x 350.5 mm	Power Standard	AC 100 to 240V, 50/60
Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years Product Dimensions 41.6 × 68.4 × 4.4 in / 1056.6 × 1737.4 × 111.8 mm Product Weight 139 lbs / 63 kg Shipping Dimensions 45.9 × 78.3 × 13.8 in / 1165.9 × 1988.8 × 350.5 mm	PC	
Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter  Casting embedded Audible Noise <ul> <li>40 dBA at 77°F / 25°C</li> </ul> 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m   Mounting Pattern  VESA 400×600mm with M8 screws  Product Warranty  2 years  Product Dimensions  41.6 x 68.4 x 4.4 in / 1056.6 x 1737.4 x 111.8 mm  Product Weight  Shipping Dimensions  45.9 x 78.3 x 13.8 in / 1165.9 x 1988.8 x 350.5 mm  Product Dimensions  Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter  Casting embedded  40 dBA at 77°F / 25°C  20 to 10000 ft / 0 to 40°C at 0 to 10000 ft / 0 to 40°C at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m  VESA 400×600mm with M8 screws  Product Warranty  2 years  41.6 x 68.4 x 4.4 in / 1056.6 x 1737.4 x 111.8 mm  Product Weight  39 lbs / 63 kg  Shipping Dimensions	PC Hardware	OPS Bay
Wireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77°F / 25°C	System	
Audible Noise       < 40 dBA at 77°F / 25°C	Included Accessories	Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter
Operating Conditions         32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m           Mounting Pattern         VESA 400×600mm with M8 screws           Product Warranty         2 years           Product Dimensions         41.6 x 68.4 x 4.4 in / 1056.6 x 1737.4 x 111.8 mm           Product Weight         139 lbs / 63 kg           Shipping Dimensions         45.9 x 78.3 x 13.8 in / 1165.9 x 1988.8 x 350.5 mm	Wireless Collaboration	Casting embedded
Operating Conditions         0 to 40°C at 0 to 3048 m           Mounting Pattern         VESA 400×600mm with M8 screws           Product Warranty         2 years           Product Dimensions         41.6 x 68.4 x 4.4 in / 1056.6 x 1737.4 x 111.8 mm           Product Weight         139 lbs / 63 kg           Shipping Dimensions         45.9 x 78.3 x 13.8 in / 1165.9 x 1988.8 x 350.5 mm	Audible Noise	< 40 dBA at 77°F / 25°C
Product Warranty         2 years           Product Dimensions         41.6 x 68.4 x 4.4 in / 1056.6 x 1737.4 x 111.8 mm           Product Weight         139 lbs / 63 kg           Shipping Dimensions         45.9 x 78.3 x 13.8 in / 1165.9 x 1988.8 x 350.5 mm	Operating Conditions	
Product Dimensions       41.6 × 68.4 × 4.4 in / 1056.6 × 1737.4 × 111.8 mm         Product Weight       139 lbs / 63 kg         Shipping Dimensions       45.9 × 78.3 × 13.8 in / 1165.9 × 1988.8 × 350.5 mm	Mounting Pattern	VESA 400×600mm with M8 screws
Product Dimensions     1056.6 x 1737.4 x 111.8 mm       Product Weight     139 lbs / 63 kg       Shipping Dimensions     45.9 x 78.3 x 13.8 in / 1165.9 x 1988.8 x 350.5 mm	Product Warranty	2 years
Shipping Dimensions 45.9 x 78.3 x 13.8 in / 1165.9 x 1988.8 x 350.5 mm	Product Dimensions	
Shipping Dimensions 1165.9 x 1988.8 x 350.5 mm	Product Weight	139 lbs / 63 kg
Shipping Weight 177 lbs / 80.3 kg	Shipping Dimensions	
	Shipping Weight	177 lbs / 80.3 kg

<sup>\*</sup> Product specifications, terms, and offerings are subject to change at any time without notice.

#### Accessories

1 Year Extended Warranty for 75-inch JTouch (EPW-75JT1)

Mobile Cart Pro for up to 75-inch Displays (Black) (INF-MOBCARTPRO-B)

Wall Mount for up to 75-inch Display (INF-WALLMNT2)

Extra Large Mobile Cart for up to 86-inch Display (INF-MCART-PL)

Deluxe Mobile Cart for up to 100-inch Display (INA-MCARTDX)

Mobile Cart for Vertical Lift Mount (INA-CARTBB)

VESA Interface Bracket for Vertical Lift Mounts (INA-VESABB)

Vertical Lift Display Wall Mount (INA-MNTBB70)

Floor Support for Lift Wall Mount (INA-SUPPORTBB)

Extra Large Wall Mount for up to 86-inch Display (INF-WALLMNT3)

Remote Control for Mondopad, BigTouch or JTouch (INA-REMOTE2)

Mini USB WiFi Adapter (INA-WIFIUSB-3)

Qwizdom Software Bundle (INS-QBUNDLE)
Ximbus Software (INS-QXIM1T40-1Y)
Oktopus Blend Software (INS-QBLEND1T40-1Y)
2 Year Extended Warranty for 75-inch JTouch (EPW-75JT2)
3 Year Extended Warranty for 75-inch JTouch (EPW-75JT3)