



8451 Paired - Audio, Control and Instrumentation Cable



For more information please
call

1-800-Belden1

See Put-ups and Colors

Description:

22 AWG stranded (7x30) tinned copper conductors, twisted pair, polypropylene insulation, overall 100% Beldfoil® shield, 22 AWG stranded tinned copper drain wire, paper wrap, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	22
Stranding	7x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PP - Polypropylene
Nom. Insulation Wall Thickness	.008 in.
Lay Length	1.75 in.
Twists/ft.	6.86

Pair Color Code Chart :

Number	Color
1	Black & Red

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil® (Z-Fold®)
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	22
Outer Shield Drain Wire Stranding	7x30
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------



8451 Paired - Audio, Control and Instrumentation Cable

Outer Jacket Nominal Wall Thickness	.020 in.
-------------------------------------	----------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.138 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
Bulk Cable Weight	14.1 lbs/1000 ft.
Max. Recommended Pulling Tension	27 lbs.
Min. Bend Radius (Install)	1.4 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR
CEC/C(UL) Specification	CMG

FLAME TEST:

UL Flame Test	UL1666 Riser
CSA Flame Test	FT4

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	45 Ohms
Nom. Inductance	.17 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	34 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	67 pF/ft
Nominal Velocity of Propagation	66 %
Nominal Delay	1.5 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	14.5 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	14.1 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	2.9 Amps per conductor @ 25°C

NOTES:

Notes	Unique paper separator facilitates jacket stripping.
-------	--

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8451 0081000	2 #22 PP SHLD PVC FR	1000	16	GRAY	C
8451 008500	2 #22 PP SHLD PVC FR	500	8	GRAY	



8451 Paired - Audio, Control and Instrumentation Cable

8451 008U1000	2 #22 PP SHLD PVC FR	U1000	16	GRAY	
8451 008U500	2 #22 PP SHLD PVC FR	U500	8.5	GRAY	
8451 010100	2 #22 PP SHLD PVC FR	100	2.3	BLACK	
8451 0101000	2 #22 PP SHLD PVC FR	1000	16	BLACK	C
8451 010500	2 #22 PP SHLD PVC FR	500	8	BLACK	
8451 010U1000	2 #22 PP SHLD PVC FR	U1000	16	BLACK	
8451 010U500	2 #22 PP SHLD PVC FR	U500	8.5	BLACK	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 09-03-2004

© 2005 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.