

SPECIFICATIONS

Pixel Pitch: 2.6mm

Physical Density: 123,904 (dots/m2)

LED Type: SMD Chip LED Size: SMD1515

Module Size: 250 x 250mm Module Resolution: 88 x 88 pixels **Drive Mode: Constant Current Drive**

Horizontal and Vertical View Angle: H:140° | V:120°

Scan Way: 1/22

Cabinet Size: 500 x 500mm

Cabinet Resolution: 176 x 176 pixels Cabinet Weight: ≥ 19.8 lbs. (≥ 9.0 kg) Cabinet Material: Die Cast Aluminum Alloy Brightness: 1200 (cd/m2) (after calibration)

Gray Scale: 14bit

Refresh Rate: Variable Up To 3840Hz Input Voltage: AC110V-220V, 50/60Hz Cabinet Max Power Consumption: 135W

Cabinet Average Max Power Consumption: 65W

Protection Level: IP20

Environment: Indoors | -20° - 40° C | 10 - 90% RH

Life Span: \geq 50,000 Hours

OPTIONAL ACCESSORIES

EVH120 - EVHD Series Rear Support Bracket - Install Version

EVH254 - EVHD Series Single Panel Rigging Bar

EVH270 - EVHD Series Rear Support Bracket - Quick Rig Version **EVH120 -** EVHD Series Rear Support Bracket - Install Version

EVH286 - EVHD Series 8 Panel Transport Case Specifications are subject to change without notice ©Elation Professional 08/16/17



SPECIAL ORDER ITEM

EVHD2™ SKU# EVH228

The EVHD2™ is a 2.6mm pixel pitch black face LED display. It's light weight durable diecast aluminum frame and modular front maintenance design, allows for easy installation and service. Features include a seamless bezelfree design, no fan metal cooling structure, and excellent color uniformity and brightness. The EVHD2™ is ideal for any broadcast installations.

