

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

www.tripplite.com

# 1.92kW Single-Phase Metered PDU, 120V (12 5-15/20R), L5-20P / 5-20P, 110-127V Input, 15ft Cord, 1U Rack-Mount

MODEL NUMBER: PDUMH20





## Description

Tripp Lite Metered PDU / Power Distribution Units offer real-time local reporting of load level in amps via built-in digital meter. Enables visual current monitoring of PDU output current to prevent circuit overloads as additional equipment is added. Offers reliable rackmount multi-outlet power distribution from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

## **Features**

- 20A single phase 120V Metered Power Distribution Unit / PDU (Agency de-rated to 16A continuous)
- Built-in 2 digit visual meter continuously reports PDU load level in amps
- Attached NEMA L5-20P 20A 120V input plug with 15 ft. / 4.5m line cord
- Includes 5-20P 20A 120V plug adapter
- 1U horizontal rackmount format installs in one rack space
- 12 NEMA 5-15/20R outlets
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Mounting ears are reversible for front or rear facing rackmount installation
- Optional PDUSIDEBRKT enables 0U vertical rackmount in compatible racks
- Back panel grounding lug

## **Specifications**

## **Highlights**

- Metered single phase 20A 120V PDU
- 1U horizontal rackmount; digital current meter
- NEMA 5-20P / L5-20P input; 15
   ft. / 4.5m line cord
- 12 NEMA 5-15/20R outlets
- Reversible housing; 4.5 in. /
   11.4cm depth

## Package Includes

- PDUMH20 Metered rackmount
   PDU
- L5-20R to 5-20P plug adapter
- Owner's manual with warranty information



OVERVIEW	
UPC Carton UPC#	037332142504
PDU Type	Metered
OUTPUT	
Output Capacity Details	2.03kW (127V), 1.92kW (120V), 1.6kW (100V) / 20A total capacity (Agency de-rated to 16A); 16A max per outlet
Frequency Compatibility	50 / 60 Hz
Output Receptacles	(12) 5-15/20R
Output Nominal Voltage	100; 120; 127
Overload Protection	20A circuit breaker
INDUT	
INPUT	400, 400, 407
PDU Input Voltage	100; 120; 127
Recommended Electrical Service	20A 120V
Maximum Input Amps	20
Maximum Input Amps Details	Agency de-rated to 16A continuous
PDU Plug Type	NEMA 5-20P; NEMA L5-20P
Input Cord Length (ft.)	15
Input Cord Length (m)	4.57
Input Phase	Single-Phase
USER INTERFACE, ALERTS & CON	TROLS
Front Panel LCD Display	Digital display reports total PDU output current in amps
Switches	n/a
PHYSICAL	
Minimum Required Rack Depth (inches)	9.5
Minimum Required Rack Depth (cm)	24.13
Shipping Dimensions (hwd / in.)	9.200 x 2.250 x 20.400
Shipping Dimensions (hwd / cm)	23.37 x 5.72 x 51.82
Shipping Weight (lbs.)	5.9000
Shipping Weight (kg)	2.68
Unit Dimensions (hwd / in.)	1.75 x 17.5 x 4.5
Unit Dimensions (hwd / cm)	4.45 x 44.5 x 11.4
Unit Weight (lbs.)	3
Unit Weight (kg)	1.36





Material of Construction	Metal	
Form Factors Supported	1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation	
PDU Form Factor	Horizontal (1U)	
Outlets Measurement (Center to Center)	30.20mm	
ENVIRONMENTAL		
Storage Temperature Range	5 to 122F (-15 to 50C)	
Relative Humidity	5-95% non-condensing	
Operating Elevation (ft.)	0-10,000	
Operating Elevation (m)	0-3000	
SPECIAL FEATURES		
TVSS Grounding	Back panel grounding lug	
CERTIFICATIONS		
Certifications	Tested to UL60950-1 (USA) and CAN/CSA C22.2 No. 60950-1-03 (Canada), RoHS Compliant	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>