INF8630AG

Customizable, open Android platform, 86-inch display

Part #: INF8630AG

InFocus

With 4K resolution, Total Touch Control™, and the ability to natively run Android apps, the JTouch Plus INF8630AG is a fully customizable, all-in-one collaboration and presentation solution.

Currently available only in US & Canada Key Features

- Navigate a friendly, easy-for-anyone interface with Total
 Touch Control
 - no need for a remote
- Built-in whiteboard, browser, media player, and AirPlay capability
- Annotate over any application or video input
- Comment and draw over websites, documents, and more
- Brilliant 86-inch, 4K resolution screen with anti-glare
- Add any Android app
- Customize your whiteboard background



Open Android Platform

Expand and customize your platform with any Android application or game. Simply download and install as you would on your phone.

Four Critical Applications

All JTouch Plus models include the four critical applications needed for interactive touch panels. These include Casting, Whiteboarding, Browsing, and File Viewing. Create on a full-featured digital whiteboard, present videos and photos, browse the web, easily connect and share content from your Apple, Windows, or Android devices with wireless casting.

Intuitive Touch

Erase, zoom, and pull up menu options quickly and easily with incredibly intuitive touch gestures on the JTouch Plus. Use one finger to draw, two fingers to move, and three fingers to erase on the whiteboard or when annotating on any screen. A simple swipe gesture on either side of the screen reveals a full menu of further options.

Interactive whiteboard

Draw, write, and capture notes on a fully customizable, built-in digital whiteboard. Choose any background on a multi-screen canvas with room for free-form drawings, diagrams, and more. Draw using your finger or one of the provided styli using a complete collection of digital pens, highlighters, shapes, lines, and colors.

Multi-input Touch Monitor

Plug up to eight devices into your INF8630AG monitor. HDMI-based sources can also connect via five separate USB-B ports to access the panel's touch control. Front access IO ports make it convenient to connect, view, and touch control any user's PC temporarily with both HDMI and Touch USB.

Optional PC

Turn your INF8630AG into a fully integrated, powerful all-inone Windows 10 PC with touch by adding the optional Core i5 OPS PC Module (coming soon).

Specifications*

Diagonal Size 86' Resolution – Native 4K UHD (3840 x 2160) Display Technology Direct-LED backlight Touch Screen Features Multi-touch, Anti-glare Glass Strength 4mm thick, heat treated Scratch Resistance 7 Mohs Contrast Ratio 1,200-1 Display Brightness 450 cd/m2 Refresh Rate 120 Hz Response Time 0,429 mm Viewing Angle 176' Speakers Sterce 10W x 2 Speakers Sterce 10W x 2 Display Connectors – Inputs RCA LPR audio Display Connectors – Outputs RS232, 35mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard AC 100 to 240V, 50/50 FC Hardware PC Hardware OPS Bay System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Quide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77F / 25°C Operating Conditions 32 to 104°F at 0 to 100000 ft /	Display	INF8630AG
Display Technology Direct-LED backlight Touch Screen Features Multi-touch, Anti-glare Glass Strength 4mm thick, heat treated Scratch Resistance 7 Mohs Contrast Ratio 1,200-1 Display Brightness 450 cd/m2 Refersh Rate 100 Hz Response Time 80 ms Viewing Angle 176* Speakers Stereo 10W x 2 Speakers Stereo 10W x 2 Display Connectors – Inputs RS232, Component video, Composite video, HDMI x 5, Ry-45 (Ethernet), VGA, USB 3.0 x 2, Media USB (Android), PC Audio in (stereo, VGA Audio source), VS* Microphone (Mono linked to 0PS), USB 2.0 x 2, 0PS PC USB x 2, RCA UR audio Power Standard RS232, S5mm PC audio, USB-B x 4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA UR audio Power Standard RS232, S5mm PC audio, USB-B x 4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA UR audio Power Standard PS bay Wireless Collaboration Se bay System Standard System Standard Wireless Collaboration 2 40 dBA at 77F / 25°C Operating Conditions 32 to 104°F at 0 to 100000 ft / 0 to 40°C at 0 to 3048 m	Diagonal Size	86"
Touch Screen Features Multi-touch, Anti-glare Glass Strength 4mm thick, heat treated Contrast Ratio 7 Mohs Contrast Ratio 120-01 Display Brightness 450 cd/m2 Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Stereo 10W x 2 Speakers Stereo 10W x 2 Refresh Composite video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 35mm PC audio, USB-B x4 for touchscreen control, SPDIF, 35mm Headphone, RCA L/R audio Power Standard 0PS Bay System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise 4 dd BA at 77F /25°C Operating Conditions 32 to 104F at 0 to 100000 ft/ 0 to 40°C at 0 to 3048 m Mounting Pattern YESA 400x700 with M8 screws <	Resolution – Native	4K UHD (3840 x 2160)
Glass Strength 4mm thick, heat treated Scratch Resistance 7 Mohs Contrast Ratio 1,200-1 Display Brightness 450 cd/m2 Refresh Rate 120 Hz Response Time 8.0 ms Prixel Pitch 0.429 mm Viewing Angle 176* Speakers Stereo 10W x 2 Speakers RS232, Component video, Composite video, HDML x 5, RI-45 [Ethernet), VGA, USB 3.0 x2, Media USB (Android), Poly Composite video, HDML x 5, RI-45 [Ethernet), VGA, USB 3.0 x2, Media USB (Android), Poly Composite video, HDML x 5, RI-45 [Ethernet), VGA, USB 3.0 x2, Media USB (Android), Poly Composite video, VGA Audio source), I/8* Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, Somm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard OPS Bay Poster Total Card Accessories Product Accessories Power cord, Remote, Stylus, HDML Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration 2 40 dBA at 77F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0"C at 0 to 3048 m Mounting Pattern VESA 400x700 with MB screws Product Warranty 2 years<	Display Technology	Direct-LED backlight
Scratch Resistance 7 Mohs Contrast Ratio 1,200-1 Display Brightness 450 cd/m2 Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 50° Speakers Stereo 10W x 2 Speakers Stereo 10W x 2 Display Connectors – Inputs RS232, Component video, Composite video, HDMI x 5, RI-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), Prower Standard Display Connectors – Outputs RS232, 35mm PC audio, USB-8x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard PS232, 35mm PC audio, USB-8x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard OPS Bay System PC VEC PC Viceles Collaboration OPS Bay Number of Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Viceles Collaboration 2 string embedded Audible Noise 4 0 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 100000 ft / 0 and to 3048 m Option Lively Conditions	Touch Screen Features	Multi-touch, Anti-glare
Contrast Ratio 1,200:1 Display Brightness 450 cd/m² Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176* Speakers Stereo 10W x 2 Explay Connectors – Inputs RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio in (stereo, VGA Audio source), 1/8* Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard Act 100 to 240V, 50/60 PC Yester System Included Accessories Foliculed Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77F / 25°C	Glass Strength	4mm thick, heat treated
Display Brightness 450 cd/m2 Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Stereo 10W x 2 Response Time RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8° Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Inputs RS232, 3.5mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard Ac 100 to 240V, 50/60 PC PC PC Power Standard Power Standard OPS Bay System Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise 4.0 dBA at 77F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400x700 with M8 screws Product Warranty 2 years Product Weight 184.5 lbs / 837 x 86 6 x 14.2 in / 1491 x 2199.6 x 360.7 mm Shipping Dimensions	Scratch Resistance	7 Mohs
Refresh Rate 120 Hz Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Stereo 10W x 2 Display Connectors – Inputs RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), VB" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RAC AU Ra audio Power Standard x 6232, 35mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard x 6100 to 240V, 50/60 PC Hardware OPS Bay System V System System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration C asting embedded Audible Noise < 40 dBA at 777° / 25°C	Contrast Ratio	1,200:1
Response Time 8.0 ms Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Stereo 10W x 2 Bisplay Connectors – Inputs RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC	Display Brightness	450 cd/m2
Pixel Pitch 0.429 mm Viewing Angle 176° Speakers Stere 10W x 2 Display Connectors – Inputs RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), V/8" Microphone (Mono linked to DPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 35mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard Ac 100 to 240V, 50/60 PC PC PC PS Bay System System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Vierburge Conditions 32 to 104°F at 0 to 100000 ft / 0 to 304B m Mounting Pattern VESA 400x700 with M8 screws Product Warranty 2 years Product Dimensions 47.3 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mm Product Weight 58.7 x 8.66.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Refresh Rate	120 Hz
Viewing Angle 176° Speakers Stereo 10W x 2 Display Connectors – Inputs RS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 3.5mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC PC PC Hardware OPS Bay System System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C	Response Time	8.0 ms
SpeakersStereo 10W x 2Display Connectors – InputsRS232, Component video, Composite video, HDMI x 5, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audioDisplay Connectors – OutputsRS232, 3.5mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audioPower StandardAC 100 to 240V, 50/60PCPCPCPC HardwareOPS BayIncluded AccessoriesPower cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi AdapterWireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77F / 25°COperating Conditions3 to 104"F at 0 to 10000 ft / 0 to 40"C at 0 to 3048 mMounting PatternVESA 400x700 with M8 screwsProduct Warranty2 yearsProduct Dimensions473 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mmProduct Weight184.5 lbs / 83.7 kgShipping Dimensions58.7 x 8.66 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Pixel Pitch	0.429 mm
RS232, Component video, Composite video, HDMI x 5, RJ-45 [Ethernet], VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio Display Connectors – Outputs RS232, 35mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio Power Standard AC 100 to 240V, 50/60 PC PC PC Hardware OPS Bay System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise 40 dBA at 77" / 25"C Operating Conditions 32 to 104"F at 0 to 10000 ft / 0 to 40"C at 0 to 3048 m Mounting Pattern VESA 400x700 with M8 screws Product Warranty 2 years Product Dimensions 47.3 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mm Product Weight 184.5 lbs / 83.7 kg Shipping Dimensions \$85.7 x 86.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Viewing Angle	176°
Display Connectors – InputsPC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audioDisplay Connectors – OutputsRS232, 3.5mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audioPower StandardAC 100 to 240V, 50/60PCPC HardwareOPS BaySystemIncluded AccessoriesPower cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi AdapterWireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77"F / 25"C	Speakers	Stereo 10W x 2
Power Standard AC 100 to 240V, 50/60 PC PC Hardware OPS Bay System Included Accessories Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C	Display Connectors – Inputs	PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2,
PC PC Hardware OPS Bay System System Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400x700 with M8 screws Product Warranty 2 years Product Dimensions 47.3 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mm Product Weight 184.5 lbs / 83.7 kg Shipping Dimensions 58.7 x 86.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Display Connectors – Outputs	RS232, 3.5mm PC audio, USB-B x4 for touchscreen control, SPDIF, 3.5mm Headphone, RCA L/R audio
PC HardwareOPS BaySystemIncluded AccessoriesPower cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi AdapterWireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77°F / 25°COperating Conditions32 to 104°F at 0 to 100000 ft / 0 to 40°C at 0 to 3048 mMounting PatternVESA 400x700 with M8 screwsProduct Warranty2 yearsProduct Dimensions47.3 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mmProduct Weight184.5 lbs / 83.7 kgShipping Dimensions58.7 x 8.6.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Power Standard	AC 100 to 240V, 50/60
Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise <40 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400x700 with M8 screws Product Warranty 2 years Product Dimensions 47.3 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mm Product Weight 184.5 lbs / 83.7 kg Shipping Dimensions 58.7 x 86.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	PC	
Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400x700 with M8 screws Product Warranty 2 years Product Dimensions 47.3 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mm Product Weight 184.5 lbs / 83.7 kg Shipping Dimensions 58.7 x 86.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	PC Hardware	OPS Bay
Wireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77°F / 25°C	System	
Audible Noise < 40 dBA at 77°F / 25°C	Included Accessories	Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter
Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m Mounting Pattern VESA 400x700 with M8 screws Product Warranty 2 years Product Dimensions 47.3 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mm Product Weight 184.5 lbs / 83.7 kg Shipping Dimensions 58.7 x 86.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Wireless Collaboration	Casting embedded
Operating Conditions0 to 40°C at 0 to 3048 mMounting PatternVESA 400x700 with M8 screwsProduct Warranty2 yearsProduct Dimensions47.3 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mmProduct Weight184.5 lbs / 83.7 kgShipping Dimensions58.7 x 86.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Audible Noise	< 40 dBA at 77°F / 25°C
Product Warranty2 yearsProduct Dimensions47.3 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mmProduct Weight184.5 lbs / 83.7 kgShipping Dimensions58.7 x 86.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Operating Conditions	
Product Dimensions 47.3 x 78.3 x 4.6 in / 1201.4 x 1988.8 x 116.8 mm Product Weight 184.5 lbs / 83.7 kg Shipping Dimensions 58.7 x 86.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Mounting Pattern	VESA 400x700 with M8 screws
Product Dimensions 1201.4 x 1988.8 x 116.8 mm Product Weight 184.5 lbs / 83.7 kg Shipping Dimensions 58.7 x 86.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Product Warranty	2 years
Shipping Dimensions 58.7 x 86.6 x 14.2 in / 1491 x 2199.6 x 360.7 mm	Product Dimensions	
Shipping Dimensions 1491 x 2199.6 x 360.7 mm	Product Weight	184.5 lbs / 83.7 kg
Shipping Weight 242.5 lbs / 110 kg	Shipping Dimensions	
	Shipping Weight	242.5 lbs / 110 kg

^{*} Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

Deluxe Mobile Cart for up to 100-inch Display (INA-MCARTDX)

1 Year Extended Warranty for 86-inch JTouch (EPW-86JT1)

 ${\sf Extra\ Large\ Wall\ Mount\ for\ up\ to\ 86-inch\ Display\ (INF-WALLMNT3)}\\$

Mini USB WiFi Adapter (INA-WIFIUSB-3)

Remote Control for Mondopad, BigTouch or JTouch (INA-REMOTE2)

Extra Large Mobile Cart for up to 86-inch Display (INF-MCART-PL)

Mobile Cart for Vertical Lift Mount (Large) (INA-CARTBBXL)

Vertical Lift Display Wall Mount (Large) (INA-MNTBB138)

VESA Interface Bracket for Vertical Lift Mounts (Large) (INA-VESABBXL)

Floor Support for Lift Wall Mount (INA-SUPPORTBB)

BigNote Whiteboarding Software (INS-BNOTE1)

BigNote, 10 Seat (INS-BNOTE10)

Virtual Training Services, 1 Hour (INS-VTRAINING1)

Virtual Training Services, 2 Hours (INS-VTRAINING2)

2 Year Extended Warranty for 86-inch JTouch (EPW-86JT2)

3 Year Extended Warranty for 86-inch JTouch (EPW-86JT3)