

G-440, G-850 & G-1200

The G-SERIES power amplifiers have been designed to provide great efficiency, dynamics and reliability at a very affordable price, for a variety of fixed and mobile audio applications.

The G-SERIES circuitry and selected components offer excellent sound quality and high fidelity audio reproduction. The compact design improves the price/performance ratio, while the rugged metal chassis guarantees maximum sturdiness. The G-SERIES amplifiers are available in three models.

The G-SERIES amplifiers are equipped with a highly visible LED display system, which provides precise information on signal status in any lighting condition. The connection system includes XLR and TRS 1/4" JACKS for audio input and twist-lock connectors for power outputs. Standard 19" rack mountable sturdy metal chassis makes installation easy while providing maximum protection. The three models of the G-Series deliver the right amount of power to your loudspeakers: the G-440 is 2x145W at 8 Ohms, the G-880 is 2x240W at 8 Ohms, and the G-1200 is 2x400W at 8 Ohms.









G-440, G-850 & G-1200

Specifications

Frequency Response: 20Hz-20kHz +/-0.5dB

Sensitivity: 1.0 Vrms Signal to Noise: 98dB Slew Rate: 22V/us

Damping Factor: >400:1 @ 1KHz, 8 ohms

Cross Talk: -82 dB (1KHz)

Harmonic Distortion THD: <0.1% (20~20000Hz)

Input Impedance: 10K ohm balanced **Protection**: Thermal, Short, DC

Controls: On/Off, 2 Input level controls

Indicators: 2 LED signal, 2 LED clip, 1 LED power, Limit & Bridge

Power Connector: Captive 15amp cable **Input Connectors:** 2 (x) XLR, (2) (x) 1/4" TRS

Output Connectors: 3 (x) Twist-lock

Cooling: Fan Size: 2 Rack Units

G-SERIES SPECIFICATIONS		G-440	G-850	G-1200
Rated Power Output 1KHz, THD < 0.5%	8 ohm	2 x 145	2 x 240	2 x 400
	4 ohm	2 x 210	2 x 340	2 x 660
	Bridge 8 ohm	440	850	1200
Voltage Gain		31dB	33dB	35dB
Dimensions (WxHxD)	Inches (mm)	19" x 3.48" x 13.1" (482 x 88.5 x 333)	19" x 3.48" x 17.13" (482 x 88.5 x 435)	19" x 3.48" x 18.25" (482 x 88.5 x 463)
Weight	Lbs (Kg)	28.66 lbs (13Kg)	36.38 lbs (16.5Kg)	49.6 lbs (22.5Kg)











Specifications subject to change without notice.

601 E. Pawnee Wichita, KS 67211 316. 263.2852 FAX 316.263.0642 www.galaxyaudio.com

Distributed outside the United States by **E and E Exports, Inc.** 2815 Junipero Ave. Suite 101Signal Hill, CA 92614 562.988.3447 FAX 562.989.3037 Distributed in Canada by **Audio Distributors International (ADI)** 1275 Newton, unit 6 Boucherville, QC J4B 5H2 Canada 450.449.8177 FAX 450.449.8180