

# SELF POWERED SPEAKER/AMPLIFIER

ARCHITECTS AND ENGINEERS  
SPECIFICATIONS / TECHNICAL DATA

3 Source, 6", Integratable on a 2X2 Tile  
with UL Listed Metal Backcan



## GENERAL SPECIFICATIONS

<b>MODEL NUMBER:</b>	<b>2X2AMP-HD2S61</b>
<b>ELECTRICAL AMPLIFIER:</b>	
Input voltage, nominal	(25 watts) 15 volts DC
Input current, operating (15VDC)	1.45 amperes peak
Input volt-amperes, peak (15VDC)	22 volt-amperes
Input voltage, maximum	16.5 volts, DC
<b>Frequency Response,</b>	
EQ set to flat	20Hz to 20 kHz
Bass	±10dB@50Hz
Treble	±10dB@10kHz
THD + Noise	<1% at 13.5 watts, "A" weighted
S/N	>82 dB
Max Power Output (28V in)	40 watts
DC Power, Standby	1.4 watts
AC Power, Sleep Mode	1.4 watts
<b>DC Power,</b>	
Short Circuit protected	Yes
Over current protected	Yes
Over voltage protected	Yes
Over temperature protected	Yes
Minimum Load Impedance	4.0 Ω (Two 8 Ω Speakers in parallel)
Minimum Input impedance, Priority in	10,000 Ω
Minimum Input impedance, RJ45 in	150,000 Ω
Minimum Input impedance, mini-jack	37,000 Ω
Min. Input Impedance, Mini-Jack:	2300 Ω
Woofer Size:	6.5 Inches
Weight of Amplifier/Speaker:	15 Lbs.
Height of Amplifier/Speaker:	4.5 Inches
Backcan:	UL Listed Enclosure (Included)
Tile Bridge:	2X2 Metal Tile (Included)
Warranty:	1 Year

\*\*Mechanical "UL Rating" is dependent upon use of the Backcan and Tile Bridge.

Note: Maximum power requires the replacement of the 15 Volt supply with a 22 Volt supply and Energy Star and UL approvals no longer apply.



**OWI Incorporated**  
17141 Kingsview Avenue, Carson, CA 90746 USA  
Tel: 310.515.1900  
Toll Free: 800.638.1694  
Fax: 310.515.1606  
Web: www.owi-inc.com  
E-mail: info@owi-inc.com

