

SONY



3LCD Laser Projectors

VPL-FHZ120L (12,000lm, WUXGA)

VPL-FHZ90L (9,000lm, WUXGA)



BrightEra™
Long Lasting Optics

Z-Phosphor
LASER LIGHT SOURCE

The latest in high-brightness laser projectors.
Ideal for large venues, mid-sized classrooms and conference rooms.



For auditoriums/halls



For lecture theatres/
conference rooms



For museums

SPECIFICATIONS

		VPL-FHZ120L	VPL-FHZ90L
Display system		3 LCD system	
Display device	Size of effective display area	1" x 3 BrightEra LCD Panel, Aspect ratio: 16:10	
	Number of pixels	6,912,000 (1920 x 1200 x 3) pixels	
Projection lens *1	Focus	Powered/Manual (Depend on lens)	
	Zoom	Powered/Manual	Powered/Manual (Depend on lens)
		Ratio	Depend on lens
	Throw Ratio	Depend on lens	
	Lens shift	Powered/Manual	Powered
Range Vertical		Depend on lens	
Range Horizontal		Depend on lens	
Light source		Laser+Phosphor	
Laser life *4		20,000 H	
Auto filter cleaning		Yes	
Screen size (Max)		40" to 600" (depend on projection lens)	
Light output*2	Mode: Standard	12,000 lm	9,000 lm
	Colour light output*2	12,000 lm	9,000 lm
Constant brightness *2 *4		10,000 lm (14,000 H)	8,000 lm (14,000 H)
Colour calibration		Yes	
Colour space *2		sRGB 100%	—
Lens functions	Bayonet lens attachment function	Yes	
	Lens position memory function	Yes (Requires optional VPLL-Z4111 lens)	
Displayable scanning frequency	Horizontal	15 kHz to 92 kHz	
	Vertical	48 Hz to 92 Hz	
Display resolution	Computer signal input	Maximum display resolution: 1920 x 1200 dots	
	Video signal input	NTSC, PAL, SECAM, 480/60i, 576/50i, 480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i The following items are available for digital signal only; 1080/60P, 1080/50p, 1080/24p	
Keystone correction (Max.)*1 *5	Horizontal	+/- 30 degrees	
	Vertical	+/- 30 degrees	
INPUT OUTPUT (Computer/Video/Control)	INPUT A	RGB/Y PB PR input connector: 5 BNC (female)	
	INPUT B	RGB input connector: Mini D-sub 15-pin (female)	
	INPUT C	DVI input connector: DVI-D 24-pin (single link), HDCP support, HDCP: v1.4	
	INPUT D	HDMI input connector: HDMI 19-pin, HDCP support, HDCP: v1.4	
	INPUT E	HDBaseT interface connector: RJ45, 3 play	
	OUTPUT 1	Monitor output for Input A/Input B Connector: Mini D-sub 15-pin (female)	
USB		Type-A x 1	
Operating temperature/Operating humidity		0°C to 45°C (32°F to 109°F)/20% to 80% (no condensation)	
Storage temperature/Storage humidity		-10°C to +60°C (14°F to +140°F)/20% to 80% (no condensation)	
Power requirements		AC 100 V to 240 V	
Power Consumption	AC 100V to 120V	1150W	950W
	AC 220V to 240V	1150W	950W
Dimensions (W x H x D) (without protrusions)		Approx. 544 x 205 x 564 mm (21 13/32 x 8 1/16 x 22 7/32 inches)	
Mass (without optional projection lens)		28 kg (62 lb)	
Supplied accessories		Remote commander RM-PJ30	
Optional accessories		Projection Lens VPLL-4008/Z4111/Z4015/Z4019/Z4025/Z4045	

*1 Depend on lens.

*2 The values are estimate.

*3 The figures are approximate. They are very depending on the environment or how the projector is used.

*4 The picture quality may deteriorate when the V Keystone function is used for it is an electrical correction.

KEY FEATURES

- Bright and vibrant image
- Long-lasting brightness
- Richer Colour reproduction
- Industry-leading wide lens shift

OPTIONAL LENS INFORMATION

	Throw ratio	Lens shift range	
		Vertical	Horizontal
VPLL-4008	1.00:1	+/- 32%	+/- 15%
VPLL-Z4111*	1.30:1 to 1.95:1	+/- 99%	+/- 51%
VPLL-Z4015	1.85:1 to 2.44:1	+/- 98%	+/- 51%
VPLL-Z4019	2.41:1 to 3.07:1	+/- 107%	+/- 60%
VPLL-Z4025	3.02:1 to 5.58:1	+/- 107%	+/- 60%
VPLL-Z4045	5.56:1 to approx. 7.5 :1	+/- 107%	+/- 60%

Please note. Optional lenses throw ratio is different to other models: (VPL-FHZ700L, FH500L and FX500L)

*VPLL-Z4111 is standard lens for the VPL-FHZ120L & VPL-FHZ90L

©2018 Sony Imaging Products & Solutions Inc. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. Information in this brochure is as of February 2018. The values for mass and dimension are approximate. "SONY" is a registered trademark of Sony Corporation.

"Z-Phosphor", "BrightEra" and "Remote Commander" are trademarks of Sony Corporation. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.

HDBaseT™ and the HDBaseT Alliance logo are the trademarks of the HDBaseT Alliance.

All other trademarks are the property of their respective owners. Please visit Sony's professional website or contact your Sony representative for specific models available in your region.