IN136

InFocus

The Superpowered Projector Designed for Use with Google Chromecast and Other Devices Part #: IN136

The InFocus IN136 WXGA projector combines stellar image performance, long-life lamp and low cost with the ability to create a more powerful and dynamic education experience. Simply insert your Google ChromeCast, Intel Computer Stick, Android solution, or other device into the projector's TechStation internal HDMI 1.4 bay and turn your projector into an all-in-one classroom solution.

Key Features

- ♦ WXGA (1280 x 800) resolution
- TechStation lets you customize your projector with the devices you already use
- ♦ Powered HDMI for mobile charging and device power
- 28,500:1 contrast ratio and up to 4000 lumens for depth of image and life-like colors
- ♦ Long life lamp of up to 15,000 hours
- Class-leading, whisper-quiet design















Customize your projector using TechStation

With an HDMI port and multiple ways to connect your devices, the TechStation superpowers your projector and enables more effective learning by working seamlessly with the tools you already use. After connecting your device, close up the TechStation's lid to create a streamlined, all-in-one solution for streaming audio and video.

IN130 Series projectors work with:

- Google ChromeCast Ultra
- Intel Computer Stick
- Asus Chromebit
- Amazon Fire TV Stick
- Android stick

 And more HDMI-supported devices to enable casting, streaming, and wireless



when not in use, and save even more money over the life of the projector.

Over 1 Billion Colors

BrilliantColor™ DLP imaging technology lets images shine with over 1 billion colors that ensure life-like color accuracy and eyecatching presentations. Get better, brighter images on whiteboards, blackboards, or beige walls, in any light.

Engage Audiences from Every Angle with 3D

Bring content to life with support for multiple forms of 3D -- including Blu-Ray, 3D broadcasting, videos games and PC connectivity. All your audience needs are 144Hz DLP Link 3D glasses (sold separately).



Quietest Projector in its Class

Make sure students always hear the lessons, not the fans. With only 21dB in eco mode, IN136 projector was designed to be quieter, with Smooth Flow fan technology, a cooling-efficient enclosure, and silent bearings.

Save Energy with Value that Lasts

IN130 projectors are designed to fit your budget go the distance with ultra-long lamp life of up to 15,000 hours and no filters to clean or replace. Unlike other imaging technologies, the TI DLP® chip ensures no image decay over time so your projector lasts longer. Activate Dynamic Mode to dim the image

Easy to Install and Manage

Quickly and simply install and manage your projector over your school's network with free ProjectorNet 4.1 software from InFocus, or choose to utilize Crestron Roomview or AMX Device Discovery.

Specifications*

Projector	IN136
Resolution – Native	WXGA (1280 x 800)
Display Technology	DLP
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Speakers	Mono 10W x 1
Lamp Brightness	4,000 lumens
Lamp Brightness – Eco Mode	3,200 lumens
Lamp Life	5,500 hours
Lamp Life – Low Power	10,000 hours
Lamp Life – Dynamic Mode	15,000 hours
Lamp Power	245W

Image Size – Maximum 256 in Image Size – Maximum 256 in Projection Offset 112.4% + 5% V Keystone Correction ± 40°V Connectors – Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise – Eco Mode < 21 dBA at 0°F / 17.8°C Included Accessories Power Cord, Remote, HDMI Cable, Documentation, User Manual (CD) 3D Support 1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption – Standby Mode 1.8W max Power Consumption – Eco Mode 1.8W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/05 Operating Conditions 41 to 104°F at 0 to 100000 ft / 5 to 40°C at 0 to 3048 m Decumentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Hungarian, Malay, Hindi, Filipino, Frais, Japanese, Thai Security Features Kensington lock port Security Features Kensington lock port TicchStation W	Projector	IN136
Calor Wheel High Speed 6 Segment RYGCWB Number of Colors 107 billion Synch Scan Frequency – Horizontal 51.5° 978 kHz Synch Scan Frequency – Vertrical 56 - 120 kHz Aspect Ratio Compatibility 43, 169, 2341, 12.1, 139, 15.9, 54 Projection Lans F Stop – Maximum 2.50 Projection Lans F Stop – Maximum 2.57 Lera Type Manual focus Image Size – Maximum 2.56 in Projection Instead Residence of Projection Offset 12.4% + 5% V Keystone Correction 4.07V Connectors – Outputs 3.5mm audio comput. Monitor out (VGA) Contectors – Outputs 3.5mm audio comput. Monitor out (VGA) Control Acquisite Noise – Eco Mode < 21 clids at CF + 7/8/C	Lamp Power – Eco Mode	170W
Number of Colors 1.07 billion Synch Sean Frequency - Horizontal 31.5 "976 KHz Synch Sean Frequency - Vertical 56 120 KHz Appert Ratio 43.169.2.351,1s1,2s1,139,159,54 Projection Lens F-Stop - Minimum 2.50 Lens Type Manual Focus Lens Type Manual	Contrast Ratio	28,500:1
Synch Scan Frequency - Hartzontal 31.5 ° 97.6 KHz Synch Scan Frequency - Vertical 56 - 120 KHz Aspect Ratio 16:10 Aspect Ratio Compatibility 43, 16.92, 32.5d, 11, 2:1, 13.9; 15.9; 5.4 Projection Lens FStop - Maximum 2.67 Lens Type Manual focus Image Size - Maximum 2.51 Projection DRS - Maximum 2.56 in Projection ORS - Maximum 2.56 in Controctor - Outputs 3.5mm audio corput, Monitor out (VGA) Connectors - Dutputs 3.5mm audio output, Monitor out (VGA) Control 8.5232, IR Remote Audible Notes - Eco Mode < 2.168 at 075 / 7375C	Color Wheel	High Speed 6 Segment RYGCWB
Synch Sequency - Vertical 56 - 120 KHz Aspect Ratio 1610 Aspect Ratio Compatibility 43, 169, 2,351, 11, 21, 139, 159, 54 Projection Lens F-Strop - Minimum 2,50 Projection Lens F-Strop - Minimum 2,50 Lens Type Manual focus Lens Type Manual focus Lens Type Manual focus Image Size - Minimum 235 Image Size - Maximum 255 in Projection Diffset 12,42% x X X Keystana Cornaction 40°V Connectors - Outputs 3,5mm audio, Composite video, WGA, HDM11,4a x2 (with 1,4a 2D support), USB-A (TechStation Connection) Connectors - Outputs 3,5mm audio, Composite video, WGA, HDM11,4a x2 (with 1,4a 2D support), USB-A (TechStation Connection) Connectors - Outputs 3,5mm audio, Composite video, WGA, HDM11,4a x2 (with 1,4a 2D support), USB-A (TechStation Connection) Connectors - Outputs 4,10°V 2,10°X	Number of Colors	1.07 billion
Aspect Ratio 16:10 Aspect Ratio Compatibility 4:3, 16:9, 2.35.1, 13, 2:1, 13.9, 15:9, 5:4 Projection Lens F-Stop — Minimum 2:67 Lens Type Manual focus Image Size — Maximum 2:51 Projection Lens F-Stop — Maximum 2:58 in Projection Offste 11:24% – 5% V Keystone Correction 4:40°V Connectors — Inputs 3:5mm audio composite video, VGA, HDMI 1:4a x3 (with 1:4a 3D support), USB-A (TechStation Connection) Control RS232, IR Remote Control RS232, IR Remote Control RS232, IR Remote Included Accessories Power consumption 30 Support 10800 @ 60 6Hz, All HDMI 1:4a 3D formats, DLP Link 3D glasses required Power Consumption — Standby Mode 1:8W max Power Consumption — Eco Mode 1:8W max Power Consumption — Eco Mode 2:20 OW max Power Standard <t< td=""><td>Synch Scan Frequency – Horizontal</td><td>31.5 ~ 97.6 KHz</td></t<>	Synch Scan Frequency – Horizontal	31.5 ~ 97.6 KHz
Aspect Ratio Compatibility 4.3, 16.9, 2.35t, 1t. 2.1, 13.9, 15.9, 5.4 Projection Lens F-Stop – Maximum 2.50 Lens Type Manual focus Image Size – Minimum 25 in Image Size – Maximum 256 in Projection Diffset 112.4% - 5% V Keystone Correction 4 60V Connectors – Inputs 3.5mm audio output, Monitor out (VGA) Control 85.32, IR Remote Audible Noise – Eco Mode < 21.08 at 0.07 + 71.8°C	Synch Scan Frequency – Vertical	56 - 120 KHz
Projection Lens F-Stop – Minimum 2.50 Projection Lens F-Stop – Maximum 2.57 Lens Type Manual focus Image Size – Minimum 23 in Langa Size – Minimum 256 in Projection Offsat 112.4% + 5% V Keystane Correction 2 40°V Connectors – Inpute 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 14a 30 support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio, Lomposite video, VGA, HDMI 14a x3 (with 14a 30 support), USB-A (TechStation Connection) Control RS232, IR Remote Audible Noise – Eco Mode < 21.48 at 0°F / 17.8°C	Aspect Ratio	16:10
Projection Lens F-Stop – Maximum 2.67 Lens Type Manual focus Image Size – Minimum 25 in Projection Offset 12.4% + 5% V Krystone Correction + 40°V Connectors – Inputs 3.5mm audio output, Monitor out (VGA) Connectors – Duputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise – Eco Mode < 21 dBA at 0°F / 128°C	Aspect Ratio Compatibility	4:3, 16:9, 2.35:1, 1:1, 2:1, 13:9, 15:9, 5:4
Lens Type Manual focus Image Size – Maximum 23 in Image Size – Maximum 256 in Projection Offset 112.4% + 5% V Keystone Correction 4 0°V Connectors – Inputs 3.5mm audio, Composite videe, VGA, HDM1.4a x3 (with 1.4a 3D support), USP-A (TechStation Connection) Control Responsibility Control RS232, IR Remote Lendid Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 3D Support 1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption 300,00W max Power Consumption – Low Power Standby 0,5W max Power Consumption – Eco Mode 1,8W max Power Consumption – Eco Mode 20,00W max Power Consumption – Eco Mode 200W max Power Consumption – E	Projection Lens F-Stop – Minimum	2.50
Image Size – Maximum 25 in Image Size – Maximum 25 in Projection Offset 112.4% + 5% V Keystone Correction ± 40°V Connectors – Inputs 3.5mm audio, Composite video, VGA, HDM11.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Control 82323, IR Remote Audible Noise – Eco Mode < 21 dBA at 0°F / +178°C	Projection Lens F-Stop – Maximum	2.67
Image Size — Maximum	Lens Type	Manual focus
Projection Offset 112.4% + 5% V Keystone Correction ± 40°V Connectors - Inputs 3.5mm audio Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Control RS232, IR Remote Audible Noise - Eco Mode < 21 dBA at Off - 17.8°C	Image Size – Minimum	23 in
Keystone Correction ± 40°V Connectors – Inputs 3.5mm audio output, Monitor out (VGA) Connectors – Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise – Eco Mode < 21 dBA at OT F / 178°C	Image Size – Maximum	256 in
Connectors − Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a x3 D support), USB-A (TechStation Connection) Connectors − Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise − Eco Mode < 21 d8A at CF / -17.8°C	Projection Offset	112.4% +- 5% V
Connectors — Outputs 35mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise — Eco Mode < 21 dBA at OTF /-178°C	Keystone Correction	± 40°V
Control RS232, IR Remote Audible Noise — Eco Mode < 21 dBA at 0°F / 178°C Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 30 Support 1080 pg 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption – Standby Mode 1.8W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 1047° at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Path, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Maximum 1 m	Connectors – Inputs	3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)
Audible Noise – Eco Mode < 21 dBA at 0°F / -178°C	Connectors – Outputs	3.5mm audio output, Monitor out (VGA)
Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 30 Support 1080 p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption	Control	RS232, IR Remote
3D Support 1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption — Low Power Standby 0.5W max Power Consumption — Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Benul Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Prabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Assorthomebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoon Throw Distance — Maximum 1 m Throw Ratio — Maximum 1.54.1 Throw Ratio — Maximum 1.72:1 Zoom Ratio 1.1.1 Shipping Product Dimensions 7.1 lbs / 3.2 kg	Audible Noise – Eco Mode	< 21 dBA at 0°F / -17.8°C
Power Consumption 300.0W max Power Consumption – Standby Mode 1.8W max Power Consumption – Low Power Standby 0.5W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 4L to 104T at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Maximum 1 m Throw Distance – Maximum 1 0 m Throw Ratio – Maximum 1.54:1 Throw Ratio – Maximum <t< td=""><td>Included Accessories</td><td>Power cord, Remote, HDMI Cable, Documentation, User Manual (CD)</td></t<>	Included Accessories	Power cord, Remote, HDMI Cable, Documentation, User Manual (CD)
Power Consumption – Standby Mode 1.8W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Frinish, Arabic, Indonesian, Portuguese Benglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Frinish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, as Chrome Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Throw Distance – Minimum 1 m Throw Distance – Maximum 1 m Throw Ratio – Maximum 1.54:1 Throw Ratio – Maximum 1.72:1 Soom Ratio 1.12 Stipping Yell State – Minimum Product Dimensions 49 × 9.3 × 12.3 in / 12.45 ×	3D Support	1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required
Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104°F at 0 to 100000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Addition Minimum 1 m Throw Ratio – Maximum 10 m Throw Ratio – Maximum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 × 9.3 × 12.3 in / 124.5 × 236.2 × 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 × 13.3 × 15.7 in / 195.6 × 337.8 × 398.8 mm	Power Consumption	300.0W max
Power Consumption — Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Kensington lock port Throw And Zoom Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Maximum 1 m Throw Ratio – Maximum 1 D m Throw Ratio – Maximum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 12.4 s x 236.2 x 312.4 mm Product Weight 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Consumption – Standby Mode	1.8W max
Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104"F at 0 to 10000 ft / 5 to 40"C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Politsh, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Maximum 1 m Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.54:1 Zoom Ratio 1.1:1 Shipping 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Consumption – Low Power Standby	0.5W max
Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Minimum 1 m Throw Distance – Maximum 10 m Throw Ratio – Maximum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Consumption – Eco Mode	220.0W max
Operating Conditions5 to 40°C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, PortugueseMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationKensington lock portThrow and ZoomWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Minimum1.54:1Throw Ratio – Maximum1.72:1Zoom Ratio1.1:1ShippingProduct Dimensions49 × 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Umensions7.7 k 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Standard	AC 100 to 240V, 50/60
Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Pollish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Minimum 1 m Throw Distance – Maximum 10 m Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 × 9.3 × 12.3 in / 124.5 × 236.2 × 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions	Operating Conditions	
Menu LanguagesRussian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationWorks with Google Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and ZoomThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Minimum1.54:1Throw Ratio – Maximum1.72:1Zoom Ratio1.72:1Zoom Ratio1.1:1ShippingProduct Dimensions4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Documentation Languages	
TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Minimum 1 m Throw Distance – Maximum 10 m Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Menu Languages	Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian,
Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and ZoomThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Minimum1.54:1Throw Ratio – Maximum1.72:1Zoom Ratio1.1:1ShippingProduct Dimensions4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Security Features	Kensington lock port
Throw Distance – Minimum 1 m Throw Distance – Maximum 10 m Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	TechStation	
Throw Distance – Maximum 10 m Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw and Zoom	
Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Distance – Minimum	1 m
Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Distance – Maximum	10 m
Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 12.4 s x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Ratio – Minimum	1.54:1
Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Ratio – Maximum	1.72:1
Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Zoom Ratio	1.1:1
Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Shipping	
Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Product Dimensions	
Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Product Weight	
		7.7 x 13.3 x 15.7 in /
	Shipping Weight	9.9 lbs / 4.5 kg

^{*} Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

SimpleShare Presentation System (INA-SIMPS1)
Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1)
DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)
Soft Carry Case for Value Projectors (CA-SOFTVAL-2)
SimpleShare (INA-SIMS1)

SimpleShare Touch Presentation System (INA-SIMINT1)

SimpleShare Transmitter (INA-SIMTM1)

SimpleShare Receiver (INA-SIMRC1)

SimpleShare Transmitter with Paired USB Touch Adapter (INA-SIMTTM1)

SimpleShare Interactive Receiver (INA-SIMRINT1)

SimpleShare Charging Station (INA-SIMCH1)

LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)

2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)